

Tremco Vulkem 45 SSL White

INGREDIENTS	CAS NO	%	8HR OEL
di-sec-octyl phthalate	117-81-7	<1	5 mg/m3
Stoddard Solvent	8052-41-3.	3-7	790 mg/m3
xylene	1330-20-7	1-5	350 mg/m3
ethylbenzene	100-41-4	<1	434 mg/m3



UN No: 3082 Hazchem Code: •3Z DG Class: 9

Subsidiary Risk: Not Applicable

Packing Group: III

Poisons Schedule: Not Applicable



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION







Acute Health Effects: Irritating to respiratory system and skin.

Risk of serious damage to eyes.

Chronic Health Effects:

May impair fertility.

May cause harm to the unborn child.

* - limited evidence

PRECAUTIONS FOR USE













Appropriate engineering controls:	Local Exhaust Ventilation recommended.
Glasses:	Consider chemical goggles.
Gloves:	1.NITRILE
Respirator:	Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report.
Fire/Explosion Hazard:	Vapours/gas heavier than air. Toxic smoke/fumes in a fire.
Environment:	Very toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment. May cause long-term adverse effects in the environment. Use appropriate container to avoid environmental contamination. Avoid release to the environment. Refer to special instructions/Safety data sheets.

PROPERTIES





Does not mix with water. Sinks in water.Combustible.

EMERGENCY







FIRST AID

Swallowed:	Give water (if conscious). Seek medical advice. Do NOT give milk or oil. Do NOT give alcohol.
Eye:	Wash with running water (15 mins). Medical attention.

Skin: Remove contaminated clothing. Wash with soap & water.

Inhaled: Fresh air. Rest, keep warm. If breath shallow, give

oxygen. Medical attention.

Advice To
Doctor:

Treat symptomatically.
Evaluate for respiratory distress. Consider lavage

with cuffed tube. NO adrenalin.

Fire Fighting: Keep containers cool. Foam.

Eliminate ignition sources. **Spills and**Pollutant.

Disposal: Prevent from entering drains.

Contain spillage by any means.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS







Explosive Radioactive Oxidizing

X X X

- Must not be stored together