

PPG Colorant Raw Umber

INGREDIENTS	CAS NO	%	8HR OEL
ethylene glycol	107-21-1	15-40	10 mg/m3
diethylene glycol	111-46-6	5-10	100 mg/m3
silica crystalline - quartz	14808-60-7	0.5-1.5	0.1 mg/m3
ferric oxide	1309-37-1	10-30	5 mg/m3

UN No: **Not Applicable**
 Hazchem Code: **Not Applicable**
 DG Class: **Not Applicable**
 Subsidiary Risk: **Not Applicable**
 Packing Group: **Not Applicable**
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

Harmful by inhalation and if swallowed.
 Irritating to eyes.
 HARMFUL-May cause lung damage if swallowed.

Chronic Health Effects:

Limited evidence of a carcinogenic effect.
 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

* – limited evidence

PRECAUTIONS FOR USE



Appropriate engineering controls:

Local Exhaust Ventilation recommended.

Glasses:

Consider chemical goggles.

Gloves:

1.NITRILE

Respirator:

Type AX-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation:

Store in cool, dry, protected area.

PROPERTIES



Liquid.Does not burn.

EMERGENCY



FIRST AID

Swallowed:

Give water (if conscious). Seek medical advice.
 Do NOT give milk or oil.
 Do NOT give alcohol.

Eye:

Wash with running water.

Skin:

Remove contaminated clothing. Wash with soap & water.

Inhaled:

Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.

Advice To Doctor:

Emesis - test for acidosis/hypocalcaemia. Consider ethanol therapy.

Fire Fighting:

Keep surrounding area cool. Water spray/fog.

Spills and Disposal:

Spilled liquid has low temperature and evaporates quickly.
 Control vapour with water spray/ fog.
 Absorb with dry agent.
 Stop leak if safe to do so.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Flammable Explosive Radioactive Oxidizing

x x x x

x — Must not be stored together