

# Plusco 416 Wireline Grease Seal

INGREDIENTS	CAS NO	%	8HR OEL
naphthenic distillate, heavy, hydrotreated (severe)	64742-52-5.	33-35	5 mg/m3
mineral oil	Not Available	60-65	5 mg/m3

UN No: Not Applicable

Hazchem Code: Not Applicable

DG Class: None Subsidiary Risk: None Packing Group: None Poisons Schedule: S5



## NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- **▶ 3:** High
- ▶ 4: Extreme

## **HEALTH HAZARD INFORMATION**



**Acute Health** Effects:

Vapours may cause drowsiness and dizziness.

### PRECAUTIONS FOR USE













Appropriate engineering controls:	Local Exhaust Ventilation recommended.
Glasses:	Consider chemical goggles.
Gloves:	PVC chemical resistant type.
Respirator:	Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children.
Fire/Explosion Hazard:	Toxic smoke/fumes in a fire. Dispose of this material and its container at hazardous or special waste collection point.

## **PROPERTIES**







Liquid. Does not mix with water. Floats on water. Combustible.

## **EMERGENCY**









### **FIRST AID**

Swallowed:	Give water (if conscious). Seek medical advice.
Eye:	Wash with running water.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Fresh air. Rest, keep warm. If breath shallow, give oxygen. Medical attention.
Advice To Doctor:	Emesis generally unnecessary. Debride for subcutaneous injection.
Fire Fighting:	Foam.
Spills and Disposal:	Eliminate ignition sources. Absorb with dry agent. Stop leak if safe to do so. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way.

## SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

Must not be stored together