

CRC 2-26 Multi-Purpose Precision Lubricant

INGREDIENTS	CAS NO	%	8HR OEL
distillates, petroleum, light, hydrotreated	64742-47-8	60-70	5 mg/m3
isoparaffins petroleum hydrotreated HFP	64742-47-8.	65-75	790 mg/m3
isoparaffins petroleum hydrotreated HFP	64742-47-8.	42	790 mg/m3
1,1,1-trichloroethane	71-55-6	29	555 mg/m3



UN No: 1950 Hazchem Code: 2YE DG Class: 2.1

Subsidiary Risk: Not Applicable
Packing Group: Not Applicable
Poisons Schedule: Not Applicable



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- **▶ 3**: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

Vapours may cause drowsiness and dizziness.

PRECAUTIONS FOR USE













Gloves:	When handling larger quantities:
Respirator:	Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area. Use only in well ventilated areas. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children. Keep away from heat.
Fire/Explosion Hazard:	HIGHLY FLAMMABLE. Vapours/gas heavier than air. Toxic smoke/fumes in a fire. Risk of explosion if heated under confinement. Use only in well ventilated areas. Dispose of this material and its container at hazardous or special waste collection point.
Environment:	Very toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment. Use appropriate container to avoid environmental contamination. Avoid release to the environment. Refer to special instructions/Safety data sheets.

PROPERTIES









Liquid.

Gas.

Does not mix with water.Flammable.

EMERGENCY



F	IR	SI	ΓΔ	(IE

Swallowed:	Give water (if conscious). Seek medical advice.
Skin:	Wash with soap & water. Apply cleansing cream.
Advice To Doctor:	Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.
Fire Fighting:	Keep containers cool. Water spray/ fog.
Spills and Disposal:	Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so. Use only in well ventilated areas. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS









Radioactive Oxidizing

x x