


Hilti FS-One High Performance Intumescent Firestop Sealant

INGREDIENTS	CAS NO	%	8HR OEL
ETHYLENE GLYCOL	107-21-1	NotSpec.	10 mg/m3
talc	14807-96-6	NotSpec.	2.5 mg/m3
red iron oxide	1332-37-2	NotSpec.	5 mg/m3
EPI-CARB -F (Calcium Carbonate)	471-34-1	NotSpec.	10 mg/m3

UN No: **Not Applicable**
 Hazchem Code: **Not Applicable**
 DG Class: **Not Applicable**
 Subsidiary Risk: **Not Applicable**
 Packing Group: **Not Applicable**
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION

PRECAUTIONS FOR USE



Appropriate engineering controls:	General Exhaust Ventilation adequate.
Glasses:	Consider chemical goggles.
Gloves:	1.NATURAL+NEOPRENE 2.NITRILE
Respirator:	Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area.

PROPERTIES



Liquid. Mixes with water.

EMERGENCY



FIRST AID

Swallowed:	Rinse mouth with water.
Eye:	Wash with running water. For discomfort seek medical advice.
Skin:	Wash with soap
Inhaled:	Fresh air. Rest, keep warm.
Advice To Doctor:	Treat symptomatically.
Fire Fighting:	Water spray/ fog. No restrictions on extinguisher type.
Spills and Disposal:	Absorb with dry agent. Stop leak if safe to do so.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

x — Must not be stored together