

Caltex Gas Turbine Oil 46

INGREDIENTS	CAS NO	%	8HR OEL
paraffinic distillate, heavy, solvent-dewaxed (mild)	64742-65-0	>90	5 mg/m3
additives	Not Available	1-5	-

UN No: Not Applicable Hazchem Code: Not Applicable DG Class: Not Applicable Subsidiary Risk: Not Applicable Packing Group: Not Applicable Poisons Schedule: Not Applicable



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ **3**: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

Vapours may cause drowsiness and dizziness.

Chronic **Health Effects:** May cause CANCER.

* – limited evidence

PRECAUTIONS FOR USE











Appropriate engineering controls:	Local Exhaust Ventilation recommended.
Glasses:	Consider chemical goggles.
Gloves:	PVC chemical resistant type.
Respirator:	Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area. Keep out of reach of children.
Fire/Explosion Hazard:	Toxic smoke/fumes in a fire.

PROPERTIES







Liquid.

Does not mix with water. Floats on water.Combustible.

EMERGENCY







FIRST AID

Give water (if conscious). Seek medical advice.

Swallowed: Do NOT give milk or oil.

Do NOT give alcohol.

Eye: Wash with running water. Wash with soap

Fresh air. Rest, keep warm. If breathing shallow, Inhaled:

give oxygen. Medical attention.

Emesis generally unnecessary. Debride for

Advice To subcutaneous injection.

Evaluate for respiratory distress. Consider lavage Doctor:

with cuffed tube. NO adrenalin.

Fire Fighting: Foam.

Skin:

Eliminate ignition sources. Absorb with dry agent.

Stop leak if safe to do so.

Spills and This material and its container must be disposed of Disposal: in a safe way.

To clean the floor and all objects contaminated by

this material, use water and detergent.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

Must not be stored together