

# 94 CD-LR DEVELOPER

INGREDIENTS	CAS NO	%	8HR OEL
triethanolamine	102-71-6	15-<30	5 mg/m3
disodium N,N-bis(sulfonatoethyl)hydroxylamine	133986-51-3	5-<10	-
water	7732-18-5	>10	-

UN No: Not Applicable Hazchem Code: Not Applicable DG Class: Not Applicable Subsidiary Risk: Not Applicable Packing Group: Not Applicable Poisons Schedule: Not Applicable



## NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

#### **HEALTH HAZARD INFORMATION**













**Acute Health** Effects:

Harmful: danger of serious damage to health by prolonged exposure through inhalation. Irritating to respiratory system and skin. Risk of serious damage to eyes.

May cause SENSITISATION by skin contact.

Chronic **Health Effects:**  Harmful: danger of serious damage to health by prolonged exposure through inhalation.

\* – limited evidence

## PRECAUTIONS FOR USE





Hazard:









Appropriate engineering controls:	Local Exhaust Ventilation recommended.
Glasses:	Consider chemical goggles.
Gloves:	1.BUTYL 2.NEOPRENE 3.PVA
Respirator:	Type AEK-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area.
Fire/Explosion	Toxic smoke/fumes in a fire

Toxic smoke/fumes in a fire.

### **PROPERTIES**





Liquid. Mixes with water. Alkaline.Combustible.

#### **EMERGENCY**







### **FIRST AID**

Swallowed:	Give water (if conscious). Seek medical advice.
Eye:	Wash with running water (15 mins). Medical attention.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Fresh air. Rest, keep warm. If breath shallow, give oxygen. Medical attention.
Advice To Doctor:	Supportive care. Irrigate eyes with saline. Supportive care.
Fire Fighting:	Water spray/ fog.
Spills and Disposal:	Eliminate ignition sources. Absorb with dry agent. Stop leak if safe to do so.

### SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS









Flammable Explosive Radioactive Oxidizing x x x