

Chevron Phillips Drill-Thin Thinner

INGREDIENTS	CAS NO	%	8HR OEL
silica crystalline - quartz	14808-60-7	0.1-1	0.1 mg/m3
ferrous sulfate monohydrate	17375-41-6	5-9	1 mg/m3
tannins, sulfomethylated	68201-64-9	50-80	-
stannous sulfate	7488-55-3	3-7	2 mg/m3

UN No: **Not Applicable**
 Hazchem Code: **Not Applicable**
 DG Class: **Not Applicable**
 Subsidiary Risk: **Not Applicable**
 Packing Group: **Not Applicable**
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION

PRECAUTIONS FOR USE



Glasses:	Consider chemical goggles.
Respirator:	Type AX-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children.
Fire/Explosion Hazard:	Toxic smoke/fumes in a fire. Dispose of this material and its container at hazardous or special waste collection point.
Environment:	Harmful to aquatic organisms.

PROPERTIES



Solid.
Mixes with water. Combustible.

EMERGENCY



FIRST AID

Swallowed:	Give water (if conscious). Seek medical advice.
Eye:	Wash with running water.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Fresh air. Rest, keep warm.
Advice To Doctor:	Treat symptomatically. Treat symptoms NOT history. Emesis. Deferoxamine may be antidotal.
Fire Fighting:	Water spray/ fog. No restrictions on extinguisher type.
Spills and Disposal:	Eliminate ignition sources. Avoid dust. Sweep shovel to safe place. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Oxidizing

x

x — Must not be stored together