

ACF 50

INGREDIENTS	CAS NO	%	8HR OEL
naphtha, petroleum, hydrodesulfurised heavy	64742-82-1.	5-15	790 mg/m3
1,1,1,2-tetrafluoroethane	811-97-2	5-10	4240 mg/m3
carbon dioxide	124-38-9	1	22500 mg/m3
neutral oil, C20-50 hydrotreated, high viscosity	72623-85-9.	>70	5 mg/m3



UN No: 1950 Hazchem Code: 2Y DG Class: 2.2

Subsidiary Risk: Not Applicable Packing Group: Not Applicable Poisons Schedule: Not Applicable



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Repeated exposure may cause skin dryness and

* - limited evidence



cracking.

PRECAUTIONS FOR USE









Gloves:	When h

When handling larger quantities:

Respirator:

Type AX-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation:

Store in cool, dry, protected area. Use only in well ventilated areas. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children. Keep away from heat.

Fire/Explosion Hazard:

Vapours/gas heavier than air. Toxic smoke/fumes in a fire. Risk of explosion if heated under confinement. Use only in well ventilated areas. Dispose of this material and its container at hazardous or special waste collection point.

PROPERTIES





Liquid. Gas.Combustible.

EMERGENCY



FIRST AID

Skin:	Wash with soap & water. Apply cleansing cream.
Advice To Doctor:	Emesis generally unnecessary. Debride for subcutaneous injection.
Fire Fighting:	Keep containers cool. Water spray/ fog.
Spills and Disposal:	Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so. Use only in well ventilated areas. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

Must not be stored together