

Magnaflux Zyglo Developer AP-9F

INGREDIENTS	CAS NO	%	8HR OEL
acetone	67-64-1	40-70	1185 mg/m3
isopropanol	67-63-0	10-30	983 mg/m3
carbon dioxide	124-38-9	7	9000 mg/m3
pentaerythritol	115-77-5	10-30	10 mg/m3



UN No: 1993 Hazchem Code: •3YE DG Class: 3

Subsidiary Risk: Not Applicable

Packing Group: II

Poisons Schedule: Not Applicable



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION







Acute Health Effects: Irritating to eyes.

Vapours may cause drowsiness and dizziness.

Chronic **Health Effects:** Repeated exposure may cause skin dryness and

cracking.

* – limited evidence

PRECAUTIONS FOR USE















Appropriate engineering controls:	Local Exhaust Ventilation recommended.
Glasses:	Consider chemical goggles.
Gloves:	1.PE/EVAL/PE 2.NITRILE, PVC
Respirator:	Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Keep out of reach of children. Keep container in a well ventilated place. Keep away from sources of ignition. No smoking.
Fire/Explosion Hazard:	HIGHLY FLAMMABLE. Vapours/gas heavier than air. Toxic smoke/fumes in a fire. In case of fire and/or explosion, DO NOT BREATHE FUMES.

PROPERTIES







Liquid.

Mixes with water. Highly flammable.











FIRST AID

Swallowed:	Give water (if conscious). Seek medical advice.
Eye:	Wash with running water.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
Advice To Doctor:	No antidote. Supportive care. Severe exposure indicated by respiratory distress/hypotension Managements is essentially supportive.
Fire Fighting:	Keep containers cool. Water spray/ fog. Foam - alcohol type.
Spills and Disposal:	Spilled liquid has low temperature and evaporates quickly. Eliminate ignition sources. Consider evacuation. Prevent from entering drains. Contain spillage by any means. Control vapour with water spray/ fog. Absorb with dry agent. Stop leak if safe to do so. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

this material, use water.



Explosive







Radioactive Oxidizing

x x x x - Must not be stored together