

## Saudi Industrial Redox AK Alkyd Zinc Chromate Primer 1106

INGREDIENTS	CAS NO	%	8HR OEL
mineral spirit	64475-85-0	20-35	-
alkyd resin, proprietary	Not Available	20-25	-
rust inhibitor pigments	Not Available	5	-



UN No: 1263  
 Hazchem Code: •3Y  
 DG Class: 3  
 Subsidiary Risk: **Not Applicable**  
 Packing Group: III  
 Poisons Schedule: **Not Applicable**



## NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

## HEALTH HAZARD INFORMATION



## Acute Health Effects:

Irritating to eyes.  
 Irritating to respiratory system.  
 Irritating to skin.  
 Vapours may cause drowsiness and dizziness.

## PRECAUTIONS FOR USE



## Appropriate engineering controls:

Local Exhaust Ventilation recommended.

## Glasses:

Consider chemical goggles.

## Gloves:

PVC chemical resistant type.

## Respirator:

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

## Storage and Transportation:

Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children.

## Fire/Explosion Hazard:

Flammable. Vapours/gas heavier than air. Toxic smoke/fumes in a fire. Dispose of this material and its container at hazardous or special waste collection point.

## PROPERTIES



Liquid. Does not mix with water. Sinks in water. Flammable.

## EMERGENCY



## FIRST AID

## Swallowed:

Give water (if conscious). Seek medical advice. Do NOT give milk or oil. Do NOT give alcohol.

## Eye:

Wash with running water.

## Skin:

Remove contaminated clothing. Wash with soap & water.

## Inhaled:

Fresh air. Rest, keep warm. If breath shallow, give oxygen. Medical attention.

## Advice To Doctor:

Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.


## Fire Fighting:

Foam.

## Spills and Disposal:

Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means. Control vapour with water spray/ fog. Absorb with dry agent. Stop leak if safe to do so. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

## SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

			
Explosive	Toxic	Radioactive	Oxidizing
x	x	x	x

x — Must not be stored together