

Baker Tretolite DMO22113

INGREDIENTS	CAS NO	%	8HR OEL
xylene	1330-20-7	10-30	350 mg/m3
methanol	67-56-1	10-30	262 mg/m3
naphthalene	91-20-3	1-5	52 mg/m3
solvent naphtha petroleum, heavy aromatic	64742-94-5	10-30	-



UN No: 1993
 Hazchem Code: *3YE
 DG Class: 3
 Subsidiary Risk: **Not Applicable**
 Packing Group: II
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

Toxic by inhalation, in contact with skin and if swallowed.
 Irritating to eyes and skin.
 Toxic: Danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.
 HARMFUL-May cause lung damage if swallowed.
 Vapours may cause drowsiness and dizziness.

Chronic Health Effects:

May cause CANCER by inhalation.
 Repeated exposure may cause skin dryness and cracking.
 * – limited evidence

PRECAUTIONS FOR USE



Appropriate engineering controls:

Local Exhaust Ventilation recommended.

Glasses:

Consider chemical goggles.

Gloves:

1.SARANEX-23 2.SARANEX-232-PLY

Respirator:

Type AX-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation:

Store in cool, dry, protected area.
 Restrictions on Storage apply. Refer to Full Report.
 Take precautionary measures against static discharges.
 Dispose of this material and its container at hazardous or special waste collection point.
 Keep locked up.
 Keep out of reach of children.
 Keep away from living quarters.
 Keep container in a well ventilated place.
 Keep away from food, drink and animal feeding stuffs.
 Keep away from sources of ignition. No smoking.

Fire/Explosion Hazard:

HIGHLY FLAMMABLE.
 Toxic smoke/fumes in a fire.
 Take precautionary measures against static discharges.
 Dispose of this material and its container at hazardous or special waste collection point.
 In case of fire and/or explosion, DO NOT BREATHE FUMES.

Environment:

Toxic to aquatic organisms.
 May cause long-term adverse effects in the aquatic environment. Use appropriate container to avoid environmental contamination.
 Avoid release to the environment. Refer to special instructions/Safety data sheets.

PROPERTIES



Liquid.
 Does not mix with water.
 Floats on water. Highly flammable.

EMERGENCY



FIRST AID

Swallowed:

If more than 15 mins from Doctor, INDUCE VOMITING (if conscious).
 Do NOT give milk or oil.
 Do NOT give alcohol.

Eye:

Wash with running water (15 mins). Medical attention.

Skin:

Wipe-off with clean/dry cloth. Remove contaminated clothing. Wash with water & soap. MEDICAL ATTENTION.

Inhaled:

Fresh air. Rest, keep warm. If breath shallow, give oxygen. Medical attention.

Advice To Doctor:

Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.
 Decontaminate with ipecac or lavage. Ethanol therapy.

Fire Fighting:

Keep containers cool.
 Foam.

Spills and Disposal:

Eliminate ignition sources.
 Consider evacuation.
 Prevent from entering drains.
 Contain spillage by any means.
 Control vapour with water spray/ fog.
 Absorb with dry agent.
 Stop leak if safe to do so.
 Take precautionary measures against static discharges.
 Dispose of this material and its container at hazardous or special waste collection point.
 This material and its container must be disposed of in a safe way.
 To clean the floor and all objects contaminated by this material, use water and detergent.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Flammable

Explosive

Toxic

Radioactive

Oxidizing

x

x

x

x

x

x — Must not be stored together