

Chevron Diesel Fuel No. 2

INGREDIENTS	CAS NO	%	8HR OEL
naphthalene	91-20-3	0.02-0.2	52 mg/m3
middle distillate	68476-34-6	>60	-
sulfur	7704-34-9.	trace	-



UN No: 1202 Hazchem Code: 3Y DG Class: 3 Subsidiary Risk: None Packing Group: III

Poisons Schedule: Not Applicable



NFPA Rating:

- ▶ 0: Minimum
- ▶ 2: Moderate
- ▶ **3:** High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION







Acute Health Effects: HARMFUL-May cause lung damage if swallowed. Vapours may cause drowsiness and dizziness.

Chronic Health Effects: Limited evidence of a carcinogenic effect. Repeated exposure may cause skin dryness and cracking.

* - limited evidence

PRECAUTIONS FOR USE





Appropriate



point.







engineering controls:	Local Exhaust Ventilation recommended.
Glasses:	Consider chemical goggles.
Gloves:	1.TEFLON
Respirator:	Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children. Keep away from food, drink and animal feeding stuffs.
Fire/Explosion	Flammable. Vapours/gas heavier than air. Toxic smoke/fumes in a fire. Dispose of this material and its container at hazardous or special waste collection.

PROPERTIES









Liquid. Does not mix with water. Floats on water. Flammable.

EMERGENCY









FIRST AID

Swallowed:

Give water (if conscious). Seek medical advice. Do NOT give milk or oil. Do NOT give alcohol.

Eye: Wash with running water.

Remove contaminated clothing. Wash with soap & Skin:

Fresh air. Rest, keep warm. If breath shallow, give Inhaled:

oxygen. Medical attention.

Fire Fighting:

Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means. Absorb with dry

agent. Stop leak if safe to do so. Dispose of this Spills and material and its container at hazardous or special

Disposal: waste collection point. This material and its container must be disposed of in a safe way. To clean the floor

and all objects contaminated by this material, use

water and detergent.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS









Toxic Radioactive Oxidizing Explosive Х х х

- Must not be stored together