

Nalco Ec5580A Static Dissipator Additive

INGREDIENTS	CAS NO	%	8HR OEL
kerosene	8008-20-6	>60	5 mg/m3
o-xylene	95-47-6	10-30	350 mg/m3
dodecylbenzenesulfonic acid	27176-87-0	5-10	-
solvent naphtha petroleum, heavy aromatic	64742-94-5	5-10	-



UN No: 2924
 Hazchem Code: •3W
 DG Class: 3
 Subsidiary Risk: 8
 Packing Group: III
 Poisons Schedule: S5



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

PROPERTIES



Liquid. Corrosive. Flammable.

EMERGENCY



FIRST AID

Swallowed:	Give water (if conscious). URGENT MEDICAL ATTENTION. Do NOT give milk or oil. Do NOT give alcohol.
Eye:	Wash with running water (15 mins). Medical attention.
Skin:	Flood body with water. Remove contaminated clothing. Wash with water
Inhaled:	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
Advice To Doctor:	Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.
Fire Fighting:	Foam.

Spills and Disposal: Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means. Control vapour with water spray/ fog. Absorb with dry agent. Stop leak if safe to do so. Use only in well ventilated areas. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

Explosive	Toxic	Radioactive	Oxidizing
x	x	x	x

x — Must not be stored together

HEALTH HAZARD INFORMATION



Acute Health Effects:

Harmful by inhalation.
 Harmful in contact with skin.
 Causes burns.
 Risk of serious damage to eyes.
 HARMFUL-May cause lung damage if swallowed.
 Vapours may cause drowsiness and dizziness.

PRECAUTIONS FOR USE



Appropriate engineering controls:

Local Exhaust Ventilation recommended.

Glasses:

Consider full face-shield.

Gloves:

1.PVA 2.VITON

Respirator:

Type AB-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation:

Restrictions on Storage apply. Refer to Full Report. Use only in well ventilated areas. Dispose of this material and its container at hazardous or special waste collection point. Keep locked up. Keep out of reach of children. Keep away from living quarters. Keep away from food, drink and animal feeding stuffs.

Fire/Explosion Hazard:

Flammable. Toxic smoke/fumes in a fire. Use only in well ventilated areas. Dispose of this material and its container at hazardous or special waste collection point.