

Octel Metal Deactivator (DMD)

INGREDIENTS	CAS NO	%	8HR OEL
xylene	1330-20-7	20-30	350 mg/m3
phenol	108-95-2	1	4 mg/m3
N,N'-salicylidene-1,2-diaminopropane	94-91-7	70-85	-
mixed cresols and xylenols	Not Available	0-5	-



UN No: 1307
 Hazchem Code: 3Y
 DG Class: 3
 Subsidiary Risk: **Not Applicable**
 Packing Group: III
 Poisons Schedule: S5



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

Harmful by inhalation, in contact with skin and if swallowed.
 Irritating to eyes, respiratory system and skin.
 May cause SENSITISATION by skin contact.
 Possible risk of irreversible effects.

PRECAUTIONS FOR USE



Appropriate engineering controls:	General Exhaust Ventilation adequate.
Glasses:	Consider chemical goggles.
Gloves:	1.PE/EVAL/PE 2.VITON 3.PVA
Respirator:	Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Keep out of reach of children. Keep away from food, drink and animal feeding stuffs.
Fire/Explosion Hazard:	Flammable. Vapours/gas heavier than air. Toxic smoke/fumes in a fire.
Environment:	Toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment. Use appropriate container to avoid environmental contamination. Avoid release to the environment. Refer to special instructions/Safety data sheets.

PROPERTIES



Liquid.
 Does not mix with water.
 Sinks in water. Flammable.

EMERGENCY



FIRST AID

Swallowed:	Contact Doctor or Poisons Centre. Give glass of water.
Eye:	Wash with running water.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
Advice To Doctor:	Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.
Fire Fighting:	Foam.
Spills and Disposal:	Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

Explosive	Toxic	Radioactive	Oxidizing
x	x	x	x

x — Must not be stored together