

## Sigma Paints 0834 Sigmaputz 2mm

INGREDIENTS	CAS NO	%	8HR OEL
naphtha petroleum, heavy, hydrotreated	64742-48-9.	<5	5 mg/m3
silica crystalline - quartz	14808-60-7	NotSpec.	0.1 mg/m3
calcium carbonate	471-34-1	NotSpec.	10 mg/m3
titanium dioxide	13463-67-7	NotSpec.	10 mg/m3

UN No: **Not Applicable**  
 Hazchem Code: **Not Applicable**  
 DG Class: **Not Applicable**  
 Subsidiary Risk: **Not Applicable**  
 Packing Group: **Not Applicable**  
 Poisons Schedule: **Not Applicable**



## NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

## HEALTH HAZARD INFORMATION

## PRECAUTIONS FOR USE



<b>Appropriate engineering controls:</b>	General Exhaust Ventilation adequate.
<b>Glasses:</b>	Consider chemical goggles.
<b>Gloves:</b>	PVC chemical resistant type.
<b>Respirator:</b>	Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
<b>Storage and Transportation:</b>	Store in cool, dry, protected area.

## PROPERTIES



Liquid. Mixes with water. Combustible.

## EMERGENCY



## FIRST AID

<b>Swallowed:</b>	Give water (if conscious). Seek medical advice.
<b>Eye:</b>	Wash with running water (15 mins). Medical attention.
<b>Skin:</b>	Remove contaminated clothing. Wash with soap & water.
<b>Inhaled:</b>	Fresh air. Rest, keep warm.
<b>Advice To Doctor:</b>	Treat symptomatically.
<b>Fire Fighting:</b>	Water spray/ fog. No restrictions on extinguisher type.
<b>Spills and Disposal:</b>	Eliminate ignition sources. Absorb with dry agent. Stop leak if safe to do so.

## SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

**x** — Must not be stored together