

Ecolab Endust

INGREDIENTS	CAS NO	%	8HR OEL
distillates, petroleum, middle, hydrotreated	64742-46-7	20-50	5 mg/m3
distillates, petroleum, light, hydrotreated	64742-47-8	5-20	5 mg/m3
iso-butane	75-28-5	5-20	-
propane	74-98-6	1-5	N/A



UN No: 1950
 Hazchem Code: 2YE
 DG Class: 2.1
 Subsidiary Risk: **Not Applicable**
 Packing Group: **Not Applicable**
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

Vapours may cause drowsiness and dizziness.

PROPERTIES



Liquid.
 Gas. Extremely flammable.

EMERGENCY



FIRST AID

Swallowed:	Do NOT give milk or oil. Do NOT give alcohol.
Skin:	Wash with soap & water. Apply cleansing cream.
Advice To Doctor:	Emesis generally unnecessary. Debride for subcutaneous injection. Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.
Fire Fighting:	Keep containers cool. Water spray/ fog.
Spills and Disposal:	Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive

x



Toxic

x



Radioactive

x



Oxidizing

x

x — Must not be stored together

PRECAUTIONS FOR USE



Gloves:	When handling larger quantities:
Respirator:	Type AX-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area.
Fire/Explosion Hazard:	HIGHLY FLAMMABLE. Toxic smoke/fumes in a fire. Risk of explosion if heated under confinement.