

SPX Hydraulic Technologies Tabular Support

INGREDIENTS	CAS NO	%	8HR OEL
SILICA AMPHOROUS	7631-86-9	64	2 mg/m3
ALUMINA H152, H155	1344-28-1.	36	10 mg/m3

UN No: Not Applicable

Hazchem Code: Not Applicable

DG Class: **None** Subsidiary Risk: **None** Packing Group: **None**

Poisons Schedule: Not Applicable



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ **3**: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION

PRECAUTIONS FOR USE














PROPERTIES







Solid. Does not mix with water. Sinks in water. Does not burn.

EMERGENCY





	RS1	ГΛ	ID
ГΙ	ROI	ıA	ıv

Swallowed:	Give water (if conscious). Seek medical advice.
Eye:	Wash with running water.
Skin:	Wash with soap
Inhaled:	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
Advice To Doctor:	Deferoxamine is preferred chelator. Supportive care. "metal fume fever". Remove from exposure. Treatment is supportive.
Fire Fighting:	Keep surrounding area cool. Water spray/fog.
Spills and Disposal:	Avoid dust. Sweep shovel to safe place. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

x — Must not be stored together