

MAGNAFLUX SKC-S

INGREDIENTS	CAS NO	%	8HR OEL
butane	106-97-8	0-30	1900 mg/m3
alkanes, C7-10-iso-	90622-56-3	>70	-



UN No: 1950
 Hazchem Code: 2YE
 DG Class: 2.1
 Subsidiary Risk: **Not Applicable**
 Packing Group: **Not Applicable**
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

Vapours may cause drowsiness and dizziness.

Chronic Health Effects:

Repeated exposure may cause skin dryness and cracking.

* – limited evidence

PRECAUTIONS FOR USE



Appropriate engineering controls:

General Exhaust Ventilation adequate.

Glasses:

Consider chemical goggles.

Gloves:

When handling larger quantities:
 General purpose rubber glove.

Respirator:

Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation:

Store in cool, dry, protected area.

Fire/Explosion Hazard:

HIGHLY FLAMMABLE.
 Vapours/gas heavier than air.
 Toxic smoke/fumes in a fire.
 Risk of explosion if heated under confinement.

PROPERTIES



Liquid.

Gas.

Does not mix with water.

Floats on water. Extremely flammable.

EMERGENCY



FIRST AID

Swallowed:

Contact Doctor or Poisons Centre.
 Give glass of water.

Eye:

Wash with running water (15 mins). Medical attention.

Skin:

Wash with soap & water. Apply cleansing cream.

Inhaled:

Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.

Advice To Doctor:

Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.

Fire Fighting:

Keep containers cool.
 Water spray/ fog.

Spills and Disposal:

Eliminate ignition sources.
 Prevent from entering drains.
 Contain spillage by any means.
 Absorb with dry agent.
 Stop leak if safe to do so.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive

Toxic

Radioactive

Oxidizing

x

x

x

x

x — Must not be stored together