

# AEC AWC-A-905

INGREDIENTS	CAS NO	%	8HR OEL
aluminium sulfate	17927-65-0	47	2 mg/m3
water	7732-18-5	53	-



UN No: 3264 Hazchem Code: 2X DG Class: 8

Subsidiary Risk: Not Applicable

Packing Group: III

Poisons Schedule: Not Applicable

### NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

### **HEALTH HAZARD INFORMATION**





**Acute Health** Effects: Causes burns.

Risk of serious damage to eyes. Possible risk of irreversible effects.

### PRECAUTIONS FOR USE











Appropriate engineering controls:	General Exhaust Ventilation adequate.
Glasses:	Consider full face-shield.
Gloves:	1.NEOPRENE 2.VITON 3.BUTYL
Respirator:	Particulate. (AS/NZS 1716 & 1715, EN 143:000 & 149:001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report.
Fire/Explosion Hazard:	Toxic smoke/fumes in a fire. Attacks metals to liberate hydrogen.

#### **PROPERTIES**

Corrosive. Acid.Does not burn.

#### **EMERGENCY**











## **FIRST AID**

Swallowed:	Give water (if conscious). URGENT MEDICAL ATTENTION.
Eye:	Wash with running water (15 mins). Medical attention.
Skin:	Flood body with water. Remove contaminated clothing. Wash with water
Inhaled:	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
Advice To Doctor:	Airway problems - 100% O2. Treat burns as thermal. Retract eyelids - irrigate 30 mins. Retract eyelids/ Irrigate 30 mins. Deferoxamine is preferred chelator.
Fire Fighting:	Keep surrounding area cool. Water spray/fog.
Spills and Disposal:	Prevent from entering drains. Contain spillage by any means. Neutralize with soda ash/ lime.

# SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS





x - Must not be stored together