

1,4-DIOXANE

INGREDIENTS	CAS NO	%	8HR OEL	
1.4-dioxane	123-91-1	>=99	36 mg/m3	



UN No: 1165* Hazchem Code: •2YE

DG Class: 3

Subsidiary Risk: Not Applicable

Packing Group: II

Poisons Schedule: Not Applicable



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION









Irritating to eyes.

Irritating to respiratory system.

Chronic **Health Effects:** Limited evidence of a carcinogenic effect. Repeated exposure may cause skin dryness and cracking.

* - limited evidence

PRECAUTIONS FOR USE













Appropriate engineering controls:

Local Exhaust Ventilation recommended.

Glasses:

Consider chemical goggles.

Gloves:

1.PE/EVAL/PE 2.PVA 3.TEFLON

Respirator:

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or

national equivalent)

Storage and Transportation:

Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Use only in well ventilated areas. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children. Keep container in a well ventilated place. Keep away from sources of ignition. No smoking. Handle and open container with care.

Fire/Explosion

Hazard:

HIGHLY FLAMMABLE. Vapours/gas heavier than air. Toxic smoke/fumes in a fire. Use only in well ventilated areas. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. In case of fire and/or explosion, DO NOT BREATHE FUMES.

PROPERTIES











EMERGENCY











FIRST AID

TIKST AID	
Swallowed:	Give water (if conscious). Seek medical advice.
Eye:	Wash with running water.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Fresh air. Rest, keep warm. If breath shallow, give oxygen. Medical attention.
Advice To Doctor:	Treat symptomatically.

Fire Fighting:

Keep containers cool. Water spray/ fog. Foam alcohol type.

Eliminate ignition sources. Consider evacuation. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so. Use only in well ventilated areas. Take precautionary measures against static discharges.

Spills and Disposal:

Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS









Radioactive Oxidizing Х

- Must not be stored together

Х