

## Exxon Mobilube HD 85W - 140

INGREDIENTS	CAS NO	%	8HR OEL
oleyl amine	112-90-3	0.1-<1	-
mineral oil	Not Available	>60	5 mg/m3
isobutene, sulfurised	68511-50-2	1-<5	-

UN No: **Not Applicable**  
 Hazchem Code: **Not Applicable**  
 DG Class: **None**  
 Subsidiary Risk: **None**  
 Packing Group: **None**  
 Poisons Schedule: **Not Applicable**



## NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

## HEALTH HAZARD INFORMATION

## PRECAUTIONS FOR USE



<b>Appropriate engineering controls:</b>	General Exhaust Ventilation adequate.
<b>Glasses:</b>	Consider chemical goggles.
<b>Gloves:</b>	PVC chemical resistant type.
<b>Respirator:</b>	Type AK-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
<b>Storage and Transportation:</b>	Store in cool, dry, protected area. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children.
<b>Fire/Explosion Hazard:</b>	Vapours/gas heavier than air. Toxic smoke/fumes in a fire. Dispose of this material and its container at hazardous or special waste collection point.

## PROPERTIES



Liquid. Does not mix with water. Floats on water. Combustible.

## EMERGENCY



## FIRST AID

<b>Swallowed:</b>	Rinse mouth with water.
<b>Eye:</b>	Wash with running water. For discomfort seek medical advice.
<b>Skin:</b>	Remove contaminated clothing. Wash with soap & water.
<b>Inhaled:</b>	Fresh air. Rest, keep warm.
<b>Advice To Doctor:</b>	Emesis generally unnecessary. Debride for subcutaneous injection.
<b>Fire Fighting:</b>	Foam.
<b>Spills and Disposal:</b>	Eliminate ignition sources. Absorb with dry agent. Stop leak if safe to do so. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way.

## SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

**x** — Must not be stored together