

HEMPADURE HI-BUILD 4520

INGREDIENTS	CAS NO	%	8HR OEL
xylene	1330-20-7	12.5-15	350 mg/m3
ethylbenzene	100-41-4	1-3	434 mg/m3
bisphenol A/ diglycidyl ether polymer, high molecular weight	25068-38-6	15-25	-
n-butanol	71-36-3	5-10	N/A



UN No: 1263 Hazchem Code: •3Y DG Class: 3

Subsidiary Risk: Not Applicable

Packing Group: III

Poisons Schedule: Not Applicable



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION











Acute Health Effects: Harmful by inhalation and in contact with skin.

Irritating to skin.

Risk of serious damage to eyes.

May cause SENSITISATION by skin contact.

Chronic **Health Effects:** Limited evidence of a carcinogenic effect.

* - limited evidence

PRECAUTIONS FOR USE

















Appropriate engineering controls:

Local Exhaust Ventilation recommended.

Glasses:

Consider chemical goggles.

Gloves:

1.TEFLON 2.PVA

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or

Respirator:

national equivalent)

Store in cool, dry, protected area.

Restrictions on Storage apply. Refer to Full Report. Keep out of reach of children.

Storage and Transportation:

Keep away from food, drink and animal feeding

Handle and open container with care.

Fire/Explosion

Environment:

Flammable.

Hazard:

Toxic smoke/fumes in a fire.

Toxic to aquatic organisms.

May cause long-term adverse effects in the

aquatic environment. Use appropriate container to

avoid environmental contamination.

Avoid release to the environment. Refer to special

instructions/Safety data sheets.

PROPERTIES







Liquid.Flammable.

May form explosive peroxides.

EMERGENCY









FIRST AID

Give water (if conscious). Seek medical advice. Swallowed: Do NOT give milk or oil.

Do NOT give alcohol.

Wash with running water (15 mins). Medical Eye: attention.

Remove contaminated clothing. Wash with soap & Skin:

water.

Fresh air. Rest, keep warm. If breathing shallow, Inhaled:

give oxygen. Medical attention.

Evaluate for respiratory distress. Consider lavage Advice To

with cuffed tube. NO adrenalin. Doctor:

Fire Fighting: Foam.

> Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means.

Absorb with dry agent. Spills and

Stop leak if safe to do so. Disposal:

This material and its container must be disposed of

in a safe way.

To clean the floor and all objects contaminated by

this material, use water and detergent.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS









Explosive

x

Toxic Radioactive Oxidizing x x

- Must not be stored together