

## DAPCO 3300 Silicone Adhesive, Part B

INGREDIENTS	CAS NO	%	8HR OEL
Toluene (Reference Fuel)	108-88-3	30-60	191 mg/m3
ISOPROPYL ALCOHOL	67-63-0	30-60	983 mg/m3
3-aminopropyltriethoxysilane	919-30-2	<5	-
N-[3-(trimethoxysilyl)propyl]ethylenediamine	1760-24-3	<5	-



UN No: 1133  
 Hazchem Code: •3YE  
 DG Class: 3  
 Subsidiary Risk: **None**  
 Packing Group: II  
 Poisons Schedule: S6



## NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

## HEALTH HAZARD INFORMATION



## Acute Health Effects:

Harmful if swallowed.  
 Irritating to eyes.  
 Irritating to skin.  
 May cause SENSITISATION by inhalation.  
 May cause SENSITISATION by skin contact.  
 HARMFUL-May cause lung damage if swallowed.  
 Vapours may cause drowsiness and dizziness.

## Chronic Health Effects:

Harmful: danger of serious damage to health by prolonged exposure through inhalation.  
 Possible risk of harm to the unborn child.  
 \* – limited evidence

## PRECAUTIONS FOR USE



## Appropriate engineering controls:

Local Exhaust Ventilation recommended.

## Glasses:

Consider chemical goggles.

## Gloves:

1.PE/EVAL/PE 2.PVA 3.VITON

## Respirator:

Type AK-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

## Storage and Transportation:

Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Not recommended for interior use on large surface areas. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children. Keep container tightly closed. Keep container dry. Keep container in a well ventilated place. Keep away from food, drink and animal feeding stuffs. Keep away from sources of ignition. No smoking. Handle and open container with care.

## Fire/Explosion Hazard:

HIGHLY FLAMMABLE. Vapours/gas heavier than air. Toxic smoke/fumes in a fire. Reacts with water. Not recommended for interior use on large surface areas. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. In case of fire and/or explosion, DO NOT BREATHE FUMES.

## PROPERTIES



Liquid. Highly flammable. Contact with water liberates extremely flammable gases. May form explosive peroxides.

## EMERGENCY



## FIRST AID

## Swallowed:

Give water (if conscious). Seek medical advice. Do NOT give milk or oil. Do NOT give alcohol.

## Eye:

Wash with running water.

## Skin:

Remove contaminated clothing. Wash with soap & water.

## Inhaled:

Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.

## Advice To Doctor:

Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin. Severe exposure indicated by respiratory distress/hypotension. Management is essentially supportive.


## Fire Fighting:

Foam. Do NOT fight fire with water.

## Spills and Disposal:

Eliminate ignition sources. Consider evacuation. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so. Not recommended for interior use on large surface areas. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way.

## SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive Toxic Radioactive Oxidizing

x x x x

x — Must not be stored together