

Dow Corning valve lube 3452

INGREDIENTS	CAS NO	%	8HR OEL
trifluoropropylmethylsiloxane	63148-56-1	>60	-
polytetrafluoroethylene	9002-84-0	30-60	-

UN No: **Not Applicable**
 Hazchem Code: **Not Applicable**
 DG Class: **Not Applicable**
 Subsidiary Risk: **Not Applicable**
 Packing Group: **Not Applicable**
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION

PRECAUTIONS FOR USE



Appropriate engineering controls:	Local Exhaust Ventilation recommended.
Glasses:	Safety Glasses. Consider chemical goggles.
Gloves:	PVC chemical resistant type. Leather Gloves.
Respirator:	Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area.
Fire/Explosion Hazard:	Toxic smoke/fumes in a fire.

PROPERTIES



Does not mix with water.
 Sinks in water. Combustible.

EMERGENCY



FIRST AID

Swallowed:	A-P
Eye:	Wash with running water.
Skin:	Remove contaminated clothing. Wash with soap & water. For burns: Apply cold water. Do NOT remove clothes from area. Cover wound. NO OINTMENTS.
Inhaled:	Fresh air. Rest, keep warm.
Advice To Doctor:	Treat symptomatically.
Fire Fighting:	Foam.
Spills and Disposal:	Eliminate ignition sources.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Oxidizing

x

x — Must not be stored together