

## NORDSTORM 1033 BULK SEALANT

INGREDIENTS	CAS NO	%	8HR OEL
silica amorphous, fumed, crystalline free	112945-52-5	5-15	-
silica amorphous, fumed	112945-52-5	1-5	-
polyester resin, proprietary	Not Available	80-90	-
performance additives	Not Available	<5	-

UN No: **Not Applicable**  
 Hazchem Code: **Not Applicable**  
 DG Class: **Not Applicable**  
 Subsidiary Risk: **Not Applicable**  
 Packing Group: **Not Applicable**  
 Poisons Schedule: **Not Applicable**



## NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

## HEALTH HAZARD INFORMATION



## Chronic Health Effects:

Repeated exposure may cause skin dryness and cracking.

\* – *limited evidence*

## PRECAUTIONS FOR USE



## Appropriate engineering controls:

General Exhaust Ventilation adequate.

## Glasses:

Consider chemical goggles.

## Gloves:

PVC chemical resistant type.

## Storage and Transportation:

Store in cool, dry, protected area.

## Fire/Explosion Hazard:

Toxic smoke/fumes in a fire.

## PROPERTIES



Does not mix with water.  
 Sinks in water. Combustible.

## EMERGENCY



## FIRST AID

**Swallowed:** Rinse mouth with water.

**Eye:** Wash with running water.

**Skin:** Remove contaminated clothing. Wash with soap & water.

**Inhaled:** Fresh air. Rest, keep warm.

**Advice To Doctor:** Treat symptomatically.

**Fire Fighting:** Foam.

**Spills and Disposal:** Eliminate ignition sources.

## SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Oxidizing

x

x — *Must not be stored together*