

PRO-SEAL 890 (PART A & B)

INGREDIENTS	CAS NO	%	8HR OEL
manganese dioxide	1313-13-9	60	1 mg/m3

UN No: **Not Applicable**
 Hazchem Code: **Not Applicable**
 DG Class: **Not Applicable**
 Subsidiary Risk: **Not Applicable**
 Packing Group: **Not Applicable**
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects: Harmful by inhalation and if swallowed. Irritating to eyes.

Chronic Health Effects: Harmful: danger of serious damage to health by prolonged exposure through inhalation.
 * – limited evidence

PRECAUTIONS FOR USE



Appropriate engineering controls: Local Exhaust Ventilation recommended.

Glasses: Consider chemical goggles.

Respirator: Type AX-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation: Store in cool, dry, protected area.

Fire/Explosion Hazard: Toxic smoke/fumes in a fire.

PROPERTIES



Does not mix with water.

Sinks in water. Contact with combustible material may cause fire.
 Does not burn.

EMERGENCY



FIRST AID

Swallowed: Give milk or water. If more than 15 mins from Doctor, INDUCE VOMITING (if conscious).

Eye: Wash with running water.

Skin: AX-P

Inhaled: Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.

Advice To Doctor: Treat symptomatically. Supportive care.

Fire Fighting: Keep surrounding area cool. Water spray/fog.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Flammable	Explosive	Toxic	Radioactive	Oxidizing
x	x	x	x	x

x — Must not be stored together