

## Kam Controls Generator Solution A

INGREDIENTS	CAS NO	%	8HR OEL
chloroform	67-66-3	10-~30	10 mg/m3
sulfur dioxide	7446-09-5	1-~5	5.2 mg/m3
xylene	1330-20-7	30-~60	350 mg/m3
methanol	67-56-1	10-~30	262 mg/m3



UN No: **1992**  
 Hazchem Code: **\*3WE**  
 DG Class: **3**  
 Subsidiary Risk: **6.1**  
 Packing Group: **II**  
 Poisons Schedule: **S6**



## NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

## PROPERTIES



Liquid. Highly flammable.

## EMERGENCY



## FIRST AID

<b>Swallowed:</b>	Give water (if conscious). URGENT MEDICAL ATTENTION. Do NOT give milk or oil. Do NOT give alcohol.
<b>Eye:</b>	Wash with running water (15 mins). Medical attention.
<b>Skin:</b>	Wipe-off with clean/dry cloth. Remove contaminated clothing. Wash with water & soap. MEDICAL ATTENTION.
<b>Inhaled:</b>	Fresh air. Rest, keep warm. If breath shallow, give oxygen. Medical attention.
<b>Advice To Doctor:</b>	Treat symptomatically. NO adrenalin. Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin. Decontaminate with ipecac or lavage. Ethanol therapy.
<b>Fire Fighting:</b>	Keep containers cool. Foam.
<b>Spills and Disposal:</b>	Eliminate ignition sources. Consider evacuation. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

## SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Flammable	Explosive	Toxic	Radioactive	Oxidizing
x	x	x	x	x

x — Must not be stored together

## HEALTH HAZARD INFORMATION



## Acute Health Effects:

Toxic by inhalation.  
 Toxic in contact with skin.  
 Toxic if swallowed.  
 Irritating to respiratory system.  
 Irritating to skin.  
 Toxic: Danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.  
 Risk of serious damage to eyes.  
 Vapours may cause drowsiness and dizziness.

## Chronic Health Effects:

Limited evidence of a carcinogenic effect.  
 Harmful: danger of serious damage to health by prolonged exposure through inhalation and if swallowed.  
 Possible risk of harm to the unborn child.

\* — limited evidence

## PRECAUTIONS FOR USE



## Appropriate engineering controls:

Local Exhaust Ventilation recommended.

## Glasses:

Consider chemical goggles.

## Gloves:

1.SARANEX-232-PLY 2.SARANEX-23

## Respirator:

Type BEKAX-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

## Storage and Transportation:

Restrictions on Storage apply. Refer to Full Report. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. Keep locked up. Keep out of reach of children. Keep away from living quarters. Keep container in a well ventilated place. Keep away from food, drink and animal feeding stuffs. Keep away from sources of ignition. No smoking.

## Fire/Explosion Hazard:

HIGHLY FLAMMABLE. Toxic smoke/fumes in a fire. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. In case of fire and/or explosion, DO NOT BREATHE FUMES.

## Environment:

Harmful to aquatic organisms.