

Champion Corton KR70-SJ

INGREDIENTS	CAS NO	%	8HR OEL
distillates, petroleum, middle, chemically-neutralised	64742-30-9.	60-90	5 mg/m3
naphthalene	91-20-3	<0.1	52 mg/m3
butanol, branched and linear, low boiling	90530-13-5	10-30	-
fatty acids, tall oil, DETA, dodecylbenzenesulfonate salts	68956-43-4	1-10	-

UN No: Not Applicable Hazchem Code: Not Applicable DG Class: Not Applicable Subsidiary Risk: Not Applicable Packing Group: Not Applicable Poisons Schedule: Not Applicable



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION













Irritating to eyes and skin. May cause SENSITISATION by skin contact. HARMFUL-May cause lung damage if swallowed. Vapours may cause drowsiness and dizziness.

PRECAUTIONS FOR USE













Appropriate engineering controls:	Local Exhaust Ventilation recommended.
Glasses:	Consider chemical goggles.
Gloves:	PVC chemical resistant type.
Respirator:	Type AK-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area.
Fire/Explosion Hazard:	Toxic smoke/fumes in a fire.
Environment:	Very toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment. Use appropriate container to avoid environmental contamination. Avoid release to the environment. Refer to special instructions/Safety data sheets.

PROPERTIES





Liquid.In use, may form flammable/ explosive vapour-air mixture Combustible.

EMERGENCY









FIRST AID

Swallowed:	Give water (if conscious). Seek medical advice. Do NOT give milk or oil. Do NOT give alcohol.
Eye:	Wash with running water.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
Advice To Doctor:	Emesis generally unnecessary. Debride for subcutaneous injection.
Fire Fighting:	Foam.
Spills and	Eliminate ignition sources.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

Absorb with dry agent.

Stop leak if safe to do so.







Explosive Radioactive Oxidizing х х

Disposal: