

# Tesla TESLAN 1101 ZN---CNT Low VOC Epoxy Primer - Part B

INGREDIENTS	CAS NO	%	8HR OEL
n-butanol	71-36-3	20-30	-
tall oil/ tetraethylenepentamine polyamides	68513-05-3	<10	-
Struers Epofix Hardener	112-24-3	1-5	-
tetraethylenepentamine	112-57-2	<0.5	-



UN No: 1263 Hazchem Code: •3Y DG Class: 3

Subsidiary Risk: None Packing Group: III

Poisons Schedule: Not Applicable



#### NFPA Rating:

- ▶ 0: Minimum
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

#### **HEALTH HAZARD INFORMATION**



















Harmful by inhalation. Harmful if swallowed. Irritating to respiratory system. Irritating to skin.

Risk of serious damage to eyes.

May cause SENSITISATION by skin contact. Vapours may cause drowsiness and dizziness.

**Chronic Health** 

Effects:

**Acute Health** 

Effects:

Harmful: danger of serious damage to health by prolonged exposure through inhalation. May cause harm to the unborn child. Possible risk of impaired fertility.

\* - limited evidence

## PRECAUTIONS FOR USE





**Appropriate** 













engineering controls:	Local Exhaust Ventilation recommended.
Glasses:	Consider full face-shield.
Gloves:	1.NEOPRENE 2.HYPALON 3.PVA
Respirator:	Type AK-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Not recommended for interior use on large surface areas. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children. Keep away from food, drink and animal feeding stuffs.
Fire/Explosion Hazard:	Flammable. Vapours/gas heavier than air. Toxic smoke/fumes in a fire. Not recommended for interior use on large surface areas. Dispose of this material and its container at hazardous or special waste

collection point.

### **PROPERTIES**



Liquid.Flammable.











#### **FIRST AID**

Give water (if conscious). URGENT MEDICAL Swallowed: ATTENTION. Do NOT give milk or oil. Do NOT give

alcohol.

Wash with running water (15 mins). Medical attention. Eye:

Flood body with water. Remove contaminated clothing. Skin:

Wash with water

Fresh air. Rest, keep warm. If breath shallow, give Inhaled:

oxygen. Medical attention.

Fire Fighting: Foam.

Spills and

Disposal:

Spilled liquid has low boiling temperature and evaporates quickly. Eliminate ignition sources. Consider evacuation. Prevent from entering drains. Contain spillage by any means. Control vapour with water spray/ fog. Absorb with dry agent. Stop leak if safe to do so. Not recommended for interior use on

large surface areas. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and

detergent.

## SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS









Explosive Toxic Radioactive Oxidizing х х

- Must not be stored together