

Ecolab M290

INGREDIENTS	CAS NO	%	8HR OEL
ETHYL ALCOHOL	64-17-5	10-30	1880 mg/m3
benzyl C12-16-alkyldimethylammonium chloride	68424-85-1	30-60	-



UN No: 2920 Hazchem Code: •3W DG Class: 8 Subsidiary Risk: 3 Packing Group: II

Poisons Schedule: Not Applicable



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ **3**: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION









Acute Health Effects: Harmful in contact with skin. Harmful if swallowed. Causes severe burns.

Risk of serious damage to eyes.

PRECAUTIONS FOR USE















Appropriate engineering controls:

Local Exhaust Ventilation recommended.

Consider full face-shield.

Glasses: Gloves:

1.BUTYL 2.NEOPRENE 3.NITRILE

Respirator:

Type AK-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88

or national equivalent)

Storage and Transportation:

Restrictions on Storage apply. Refer to Full Report. Dispose of this material and its container at hazardous or special waste collection point. Keep locked up. Keep out of reach of children. Keep away from living quarters. Keep away from food, drink and animal feeding stuffs.

Fire/Explosion Hazard:

HIGHLY FLAMMABLE. Toxic smoke/fumes in a fire. Attacks metals to liberate hydrogen. Dispose of this material and its container at hazardous or special waste collection point.

Environment:

Very toxic to aquatic organisms. Use appropriate container to avoid environmental contamination. Avoid release to the environment. Refer to special instructions/Safety data sheets.

PROPERTIES







Liquid. Mixes with water. Corrosive. Acid. Flammable.

EMERGENCY









FIRST AID

Give water (if conscious). URGENT MEDICAL Swallowed:

> Wash with running water (15 mins). Medical Eye:

Flood body with water. Remove contaminated Skin: clothing. Wash with water

Fresh air. Rest, keep warm. If breath shallow, give Inhaled:

oxygen. Medical attention.

Airway problems - 100% O2. Treat burns as thermal. Advice To Retract eyelids - irrigate 30 mins. Retract eyelids/ Doctor:

Irrigate 30 mins. Supportive care.

Fire Fighting: Keep containers cool. Water spray/ fog.

> Eliminate ignition sources. Pollutant. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Neutralize with soda ash/ lime. Stop leak if safe to do so. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material,

use water.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS





Spills and

Disposal:





Explosive Toxic

Radioactive Oxidizing x x x

- Must not be stored together