




## Scheduling Plugins



# Extension Points



# Extension Points



# Scheduler Profiles



Profile 1	my-scheduler-2
Profile 2	my-scheduler-3
Profile 3	my-scheduler-4



my-scheduler



default-scheduler

my-scheduler-2-config.yaml

```
apiVersion: kubescheduler.config.k8s.io/v1
kind: KubeSchedulerConfiguration
profiles:
- schedulerName: my-scheduler-2
- schedulerName: my-scheduler-3
- schedulerName: my-scheduler-4
```

my-scheduler-config.yaml

```
apiVersion: kubescheduler.config.k8s.io/v1
kind: KubeSchedulerConfiguration
profiles:
- schedulerName: my-scheduler
```

scheduler-config.yaml

```
apiVersion: kubescheduler.config.k8s.io/v1
kind: KubeSchedulerConfiguration
profiles:
- schedulerName: default-scheduler
```



Profile 1	my-scheduler-2	TaintToleration	MyCustomPluginA	MyCustomPluginA
Profile 2	my-scheduler-3	preScore	score	
Profile 3	my-scheduler-4			

my-scheduler-2-config.yaml

```
apiVersion: kubescheduler.config.k8s.io/v1
kind: KubeSchedulerConfiguration
profiles:
- schedulerName: my-scheduler-2
  plugins:
    score:
      disabled:
        - name: TaintToleration
      enabled:
        - name: MyCustomPluginA
        - name: MyCustomPluginB
- schedulerName: my-scheduler-3
  plugins:
    preScore:
      disabled:
        - name: '*'
    score:
      disabled:
        - name: '*'
- schedulerName: my-scheduler-4
```

[https://github.com/kubernetes/community/blob/master/contributors/devel/sig-scheduling/scheduling\\_code\\_hierarchy\\_overview.md](https://github.com/kubernetes/community/blob/master/contributors/devel/sig-scheduling/scheduling_code_hierarchy_overview.md)

<https://kubernetes.io/blog/2017/03/advanced-scheduling-in-kubernetes/>

<https://jvns.ca/blog/2017/07/27/how-does-the-kubernetes-scheduler-work/>

<https://stackoverflow.com/questions/28857993/how-does-kubernetes-scheduler-work>