UMTS/HSDPA

Quectel UC15 UMTS/HSDPA Module



Dual-mode&Multi-band

for UMTS&GSM









LCC Package



Embedded Abundant Protocols



eCall



Compact Size



USB 2.0 High Speed




USB Drivers



Quectel Enhanced AT Commands

Key Benefits

- ♥ Worldwide UMTS/HSDPA and GSM/GPRS/EDGE coverage
- Minimal SMT form factor ideal for small end products with tight space
- High-quality data and image transmission even in hazard conditions and dark environment
- Fast time-to-market: Reference designs, evaluation tools and timely technical support minimize design-in time and development efforts
- Robust mounting and interfaces



UC15 is a cost effective UMTS/HSDPA module featuring a maximum data rate of 3.6Mbps downlink and 384Kbps uplink. Designed to be compatible with Quectel GSM/GPRS M10 module in the compact and unified form factor, it provides a flexible and scalable platform for migrating from GSM/GPRS/ EDGE to UMTS/HSDPA. This enables integrators and developers to design their applications once and take advantage of true worldwide coverage and service flexibility afforded by the combination of the two most prevalent cellular technologies worldwide.


Its advanced LCC package allows fully automated manufacturing for high volume applications and copper-surfaced bottom design optimizes heat dissipation. The tiny profile in cost optimized SMT form factor and highly integration level enable integrators and developers to easily design their applications and truly benefit from the module's small size, low power consumption and mechanical intensity.

A rich set of Internet protocols, industry-standard interfaces (USB/UART/ADC/NETLIGHT/PCM) and abundant functionalities (USB drivers for Windows XP, Windows Vista, Windows 7, Windows 8, Windows CE, Linux, Android/eCall) extend the applicability of the module to a wide range of M2M applications such as automotive, metering, security, CPE and wireless POS.



Quectel UC15 UMTS/HSDPA Module

OUECTE UC15 UC15EA-128-NCH-STD UC15EQAR01A01M1024 29.0 mm



General Features

UC15-E

900/2100MHz@UMTS 900/1800MHz@GSM

UC15-A

Frequency Bands 850/1900MHz@UMTS

850/900/1800/1900MHz@GSM

UC15-T

850/2100MHz@UMTS

850/900/1800/1900MHz@GSM

HSDPA Release 5 (category 6)

EDGE Downlink only

GPRS Multi-slot Class 12

UMTS Release 99/5

GSM Release 99/4

Supply Voltage Range 3.3V ~ 4.3V, 3.8V typ.

Operation Temperature -40 °C ~ +85 °C

29.0mm×29.0mm×2.5mm **Dimensions**

Weight Approx. 4.3q

3GPP TS27.007, 27.005 and other enhanced AT Control via AT commands

Commands

Specifications

Point-to-point MO and MT SMS SMS Cell Broadcast Text and PDU Mode

> **HSDPA** Max.3.6Mbps (DL)

Max.384Kbps (DL)/Max.384Kbps (UL) **UMTS**

EDGE Max.236.8Kbps (DL) DATA

> **GPRS** Max.85.6Kbps (DL)/Max.85.6Kbps (UL)

GSM: 14.4 Kbps (DL)/14.4 Kbps (UL) CSD

WCDMA: 64 Kbps (DL)/64 Kbps (UL)

Speech Codec Modes

Voice

Drivers

HR, FR, EFR, AMR, AMR-WB

Echo Arithmetic

Echo Cancellation Noise Reduction

TCP/UDP/PPP/FTP/HTTP/SMTP/MMS/SSL/ **Protocols**

PING/NITZ/NTP/HTTPS/SMTPS

Special Features

Windows XP, Windows Vista, Windows 7, Windows 8, Windows CE5.0/ 6.0/7.0, Windows **USB Serial**

Mobile 6.1/6.5*, Linux 2.6 or later, Android 2.3 or

Windows CE6.0*, Windows Mobile 6.1/6.5*, RIL

Android 2.3/4.0

MUX Linux 2.6 or later, Android 2.3 or later

eCall Accident, Emergency Services

Firmware Update via USB and UART Interface Firmware Update

QuecFile File System Access and Management

FOTA QuecFOTA, DFOTA

QuecLocator

Electrical Characteristics

29.0 mm

Class 3 (24dBm +1/-3dB) for UMTS bands Class 4 (33dBm ±2dB) for GSM 850/900MHz **Output Power** Class 1 (30dBm ±2dB) for GSM 1800/1900MHz

2.5 mm

65µA@Power off

1.8mA@GSM Sleep,DRX=9 1.7mA@UMTS Sleep,DRX=9 260mA@GSM voice, max power 480mA@UMTS voice, max power 480mA@GPRS data, max power

475mA@HSDPA, max power

-110dBm@UMTS Bands Sensitivity -108.5dBm@GSM 900MHz

-108.5dBm@GSM 1800MHz

Interfaces

Consumption

USB 2.0 High Speed

2 Analog Input and Output Channels (Optional) Audio Analog

Audio Digital Digital Audio through PCM Interface (Optional)

UART 1×Full Functions **USIM** 1.8V/3V ADC ×2. 12bits

NETLIGHT Indication for network activity status

STATUS Indication for Power On and Off Status

Certification

CE/GCF/IC/FCC/PTCRB/NTC/AT&T/Rogers/ Approval NCC

* Under development

