



Application Programming Interface Technical Documentation

GIG WORKERS API

PERTUBUHAN KESELAMATAN SOSIAL (PERKESO)

Release Name	GIG Workers API Documentation v2.1
Release Version	2.1
Release Date	03 February 2026
Updated Date	07 May 2026
Security Level	Gig Worker Platform Provider



Acknowledgement

Revision History

Version	Date	Author(s)	Document History Record
0.1	03 February 2025	Norhaslinda Binti Mohd Drill	Initial draft.
0.2	07 March 2025	Norhaslinda Binti Mohd Drill	Adding API package specifications.
1.0	11 March 2025	Norhaslinda Binti Mohd Drill	Adding sandbox package and data objects specifications.
2.0	06 February 2026	Norhaslinda Binti Mohd Drill	Adding generate token details.
2.1	07 May 2026	Norhaslinda Binti Mohd Drill	Adding callback details.



Distribution History

Version	Date	Receiver Name	Receiver Email	Approve / Acknowledge By
1.0	11 March 2025	Norhaslinda Mohd Drill	norhaslinda.drill@perkeso.gov.my	Edmund Cheong Peck Huang
2.0	06 February 2026	Norhaslinda Mohd Drill	norhaslinda.drill@perkeso.gov.my	Edmund Cheong Peck Huang
2.1	07 May 2026	Norhaslinda Mohd Drill	norhaslinda.drill@perkeso.gov.my	Edmund Cheong Peck Huang

Abbreviations

#	Name	Descriptions
1	API	API known as Application Programming Interface. It is a set of programming code that enables data transmission between one software product and another.
2	Platform Provider	Authorized users or clients who have an access to use GIG Workers API upon PERKESO approval.
3	User / OBS	Public user or known as “Orang Bekerja Sendiri (Self Employed)”, the one who uses a Platform system/application that integrates with GIG Worker API.
4	HTTP	HTTP known as Hypertext Transfer Protocol. It was designed for communication between web browsers and web servers, but it can also be used for other purposes.
5	IETF	Internet Engineering Task Force



Table of Content

1. Introduction	6
1.1. Overview	6
1.2. Purpose	6
1.3. Methods	6
1.4. Authorization	6
2. Getting Started	8
2.1. Introduction	8
2.2. Authorization	8
2.3. Request ID	8
2.4. HTTP Request	8
2.5. HTTP Status Code	9
2.6. Response Types	10
2.7. Sample API Request	10
3. Sandbox Package	11
3.1. Prerequisite	11
3.2. How to Request	11
3.3. How to Get Started	11
3.4. How to Go Live	11
4. Callback Details	12
4.1. Batch Registration	12
4.1.1. Success	12
4.1.2. Fail	13
4.1.3. Error	13
4.2. Deduction	14
4.3. Contribution	15
4.3.1. Contribution	15
5. Data Object Package	17
5.1. Introduction	17
5.2. Data Objects	17
5.2.1. Pagination	17
5.2.1.1. Attributes	17
5.2.2. ID-Name	18
5.2.2.1. Attributes	18
5.2.3. Check User	18
5.2.3.1. Attributes	18
5.2.4. User Details	18



5.2.4.1. Attributes	18
5.2.5. Update User Details	19
5.2.5.1. Attributes	19
5.2.6. Address	20
5.2.6.1. Attributes	20
5.2.7. Next of KIN	20
5.2.7.1. Attributes	20
5.2.8. Sector	20
5.2.8.1. Attributes	20
5.2.9. Classes	21
5.2.9.1. Attributes	21
5.2.10. State	21
5.2.10.1. Attributes	21
5.2.11. Plan Details	21
5.2.11.1. Attributes	21
5.2.12. Self-Employed Contribution	22
5.2.12.1. Attributes	22
6. API Package	24
6.1. Prerequisite	24
6.1.1. HTTP Status Code	24
6.2. Check Existence of A User	24
6.3. Register User	26
6.4. Get Sectors	28
6.5. Get States and Cities	29
6.6. Update User Details	31
6.7. Get Contribution List	34
6.8. Submit Deduction	36
6.9. Cancel Deduction	38
6.10. Check Existence of Users by IC Number in Batch	39
6.11. Register User in Batch	40
6.12. Update Users' Details in Batch	43
6.13. Generate Token	46



1. Introduction

1.1. Overview

This document describes technical features, parameters and Application Programming Interface (API) for the Gig Worker Platform Providers with ease of integration for ACT 789 contributions. GIG Worker API provides a mechanism for the Platform Provider to share and receive data beyond their own boundaries in an authorised way, allowing broader use of that data.

This document helps Gig Worker Platform to integrate PRIHATIN into their systems or applications, with minimal guidance from PRIHATIN support.

1.2. Purpose

The purpose of this GIG Worker API is to enable Gig Worker Platform Providers to submit a portion of the Gig Worker's job amount (1.25% from the job amount) to the GIG Worker Platform system.

On the new day of calendar month. PRIHATIN will create a contribution for the Gig Worker based on the deduction amount submitted to the OBS wallet. A contribution shall be created once OBS has sufficient wallet balance, and default to the Plan 1 Contribution amount monthly.

The features and functionalities that will be covered in the API are only available for the listed end-point in this document.

1.3. Methods

This API adopts REST (REpresentational State Transfer) convention based on HTTP methods and use of JSON (JavaScript Object Notation). Thus, enabling a wide range of programming languages and RESTful libraries can be used to interact with Gig Worker API.

1.4. Authorization

Upon any Gig Worker Platform Provider onboarding registration request, an API authentication key will be issued by PERKESO. Each key is unique, and tied to a set of permissions. API clients are expected to use the correct (separate) keys for production and sandbox environments.



1.5. Service API

Gig Worker Platform provides two service domains that were catered for production and sandbox environments. Platform Provider will be provided with Authentication key.

Once the third party account is successfully registered, PERKESO will activate sandbox access first. The third party is required to test the integration in the sandbox environment and send to PERKESO the test cases result, in order for the production environment access to be activated. Service API details as follows:

1. Sandbox domain: <https://gig-sandbox.perkeso.gov.my>
2. Production domain: <https://gig-connector.perkeso.gov.my>



2. Getting Started

2.1. Introduction

The API is organized around REST (REpresentational State Transfer). It accepts form-encoded request bodies, returns JSON-encoded responses, and uses standard HTTP response codes, authentication, and verbs. All API requests shall be sent through HTTPS secured communication channel, using PERKESO SSL certificate.

2.2. Authorization

Each API account (GIG Worker Platform Provider) will be assigned an unique identifier, known as API authentication key. This is to control access to API web service. When an application is no longer consuming this API, this API authentication key shall be deactivated by PERKESO.

API authentication key will be sent in all API requests. All API requests must be made over HTTPS. Calls made over unsecured HTTP will fail. API requests without authentication will also fail. This is set in HTTP header:

```
Authorization: Bearer <API Authentication Key>
```

2.3. Request ID

For each API request sent to the PRIHATIN server, PRIHATIN will generate a unique identifier for it. This unique identifier will be set in the response header "Matrix-Request-Id". API consumers do not need to process or store it. This identifier will be useful for debugging and troubleshooting purposes.

2.4. HTTP Request

Allowed HTTPs request as follow:

Type	Descriptions	Available
GET	To retrieve a single or multiple resources	Yes
POST	To create new resource	Yes



PATCH	To update existing resource	Yes
PUT	To replace existing resource	Yes
DELETE	To delete resource	No

2.5. HTTP Status Code

Status codes are issued by a server in response to a client's request made to the server. It includes codes from IETF Request for Comments (RFCs), other specifications, and some additional codes used in some common applications of the HTTP.

The HTTPS status code as follow:

Code	Descriptions	Remarks
200	OK	Everything worked as expected.
202	Accepted	The request has been accepted for processing.
400	Bad Request	The request was unacceptable, often due to missing a required parameter.
401	Unauthorized	No valid API key provided.
402	Request Failed	The parameters were valid but the request failed.
403	Forbidden	The API key doesn't have permissions to perform the request.
404	Not Found	The requested resource doesn't exist.
409	Conflict	The request conflicts with another request (perhaps due to using the same idempotent key).
429	Too Many Requests	Too many requests hit the API too quickly. We recommend an exponential backoff of your requests.



503	Service Unavailable	Maintenance mode. It might occur when a shared DB/network is not accessible. Refer message parameter for the maintenance message.
5xx	Server Errors	Something went wrong on the server end (these are rare).

2.6. Response Types

PRIHATIN is adopting the JSend specification (for more details and examples, please refer to <https://github.com/omniti-labs/jsend>). The response types are the response that API shall receive in the API request parameters.

The response types as follow:

Type	Descriptions	Keys
success	All went well and data (where applicable) was returned.	status, data (optional)
fail	There was a problem with the data submitted, or some pre-condition of the API call wasn't satisfied.	status, data
error	An error occurred in processing the request.	status, message

2.7. Sample API Request

Use the following curl command to verify your API connection and authentication status:

```
curl --header "Authorization: Bearer <API Authentication Key>" <domain>/api/v1
```



3. Sandbox Package

3.1. Prerequisite

Have an API authentication key created by PERKESO that ties to your Gig Worker API account. In this section, this document will provide a guide on how to use the sandbox API URLs in the API Package.

3.2. How to Request

You may request PERKESO to provide you with an API authentication key. PERKESO shall create Gig Worker API accounts for Platform Provider in the Gig Worker sandbox environment. PERKESO shall request Innoractive to create the authentication Gig Worker API account for Platform Provider and provide the Authentication Key.

3.3. How to Get Started

PERKESO will provide you with an API Authentication key for the Sandbox. Once PERKESO has created a Gig Worker API account for you inside the Gig Worker sandbox environment, you may start the API integration in the Sandbox environment <https://gig-sandbox.perkeso.gov.my>, you may start by using the API Authentication key given.

3.4. How to Go Live

You may request PERKESO to provide you with an API Authentication key for Production. Once PERKESO has created a Gig Worker API account for you inside the Gig Worker production environment. You may proceed to use the Production environment <https://gig-connector.perkeso.gov.my/> once done all the integration and UAT accordingly as in the Sandbox environment.

This process shall be automatic once the enhancement for the Gig Worker Platform Provider onboarding and API Management application process is deployed.

Once the system is ready, the Gig Worker Platform Provider shall be able to register as a Gig Worker Platform through <https://prihatin.perkeso.gov.my/> by themselves. PERKESO shall go through and process the application at PRIHATIN Back Office. Gig Worker Platform Provider shall receive an email with the API Authentication key when their application review is completed.

4. Callback Details

4.1. Batch Registration

The results field returns an array of status objects. The schema of each object is dynamic and determined by the value of the status field (success, fail, or error).

Name	Type	Description
results	array	Mandatory. An array of objects.

4.1.1. Success

Name	Type	Description
status	string	Mandatory. Always returns success.
data	object	Mandatory. The container for the successful response payload.
user	object	Mandatory. An object containing the details of the newly created user.
user.id	integer	Mandatory. User ID.
user.ic_type	string	Mandatory. User IC number type.
user.ic_no	string	Mandatory. User IC number.
user.name	string	Mandatory. User name.
user.email	string	Mandatory. User email address.
user.mobile_no	string	Mandatory. User mobile number.
user.gender	string	Mandatory. Gender.
user.race	string	Mandatory. Race.
user.person_status	string	Mandatory. Person status.
user.nationality	string	Mandatory. Nationality.
user.plan	object	Mandatory. An object containing the details of the user's plan.



user.plan.id	integer	Mandatory. Plan ID.
user.plan.name	string	Mandatory. Plan name.
user.plan.yearly_amount	decimal	Mandatory. Yearly amount of the plan.
user.plan.monthly_amount	decimal	Mandatory. Monthly amount of the plan.
user.created_at	string	Mandatory. Created date in ISO 8601 extended format.
user.updated_at	string	Mandatory. Updated date in ISO 8601 extended format.

4.1.2. Fail

Name	Type	Description
status	string	Mandatory. Always returns fail.
data	object	Mandatory. A container for validation errors.
data.ic_type	string	Conditional. The specific reason for the failure.
data.ic_no	string	Conditional. The specific reason for the failure.
data.name	string	Conditional. The specific reason for the failure.
data.email	string	Conditional. The specific reason for the failure.
data.mobile_no	string	Conditional. The specific reason for the failure.

4.1.3. Error

Name	Type	Description
status	string	Mandatory. Always returns an error.
message	string	Mandatory. Description of the error encountered.

4.2. Deduction

This section defines the asynchronous callback payload for a deduction transaction.



Name	Type	Description
request	object	Mandatory. Object of deduction request.
request.request_id	string	Mandatory. The unique identifier for the deduction submission request provided by the platform provider.
request.request_amount	decimal	Mandatory. The total amount submitted by the platform provider.
request.accepted_amount	decimal	Mandatory. The total amount accepted by the Gig Worker Platform.
request.status	string	Mandatory. The status of the request.
data	array	Mandatory. The data array contains the results of the deduction for each requested item. This is a mixed-type array where an item is either an object (refer to 3.5.2.1. Processed) or a string (refer to 3.5.2.2. Fail).
data.{transaction}	string object	Mandatory. A dynamic key representing the Transaction ID from the platform provider. If the transaction fails, this returns a string (error code). If successful, it returns an object containing processing details.
data.{transaction}.status	string	Conditional. (Only if {data.transaction} is an object). The status of this specific transaction, possible values: ACCEPTED, PARTIAL_ACCEPTED, REJECTED, DUPLICATE_TRANSACTION
data.{transaction}.deduction_id	string	Conditional. (Only if {data.transaction} is an object). The deduction ID generated by the Gig Worker Platform. Returns null if the status is DUPLICATE_TRANSACTION.
data.{transaction}.accepted_amount	decimal	Conditional. (Only if {data.transaction} is an object). The accepted amount for this specific transaction.
data.{transaction}.rejected_amount	decimal	Conditional. (Only if {data.transaction} is an object). The rejected amount for this specific transaction.
received_at	string	Mandatory. Request received date in ISO 8601 extended format.
processed_at	string	Mandatory. Request processed date in ISO 8601 extended format.



4.3. Contribution

This callback is triggered by a scheduled system process to submit payable contributions. It provides a confirmation of all submitted records processed during the execution cycle.

Name	Type	Description
contributions	array	Mandatory. A collection of submitted contribution objects.

4.3.1. Contribution

Name	Type	Description
ic_no	string	Mandatory. User IC number.
plan	object	Mandatory. An object containing the details of the user's plan.
plan.id	integer	Mandatory. Plan ID.
plan.name	string	Mandatory. Plan name.
plan.yearly_amount	decimal	Mandatory. Yearly amount of the plan.
plan.monthly_amount	decimal	Mandatory. Monthly amount of the plan.
status	string	Mandatory. Contribution submission status.
contribution_id	integer	Mandatory. Contribution ID in Prihatin.
coverage_started_at	string	Mandatory. Coverage start date in ISO 8601 extended format.
coverage_ended_at	string	Mandatory. Coverage end date in ISO 8601 extended format.
created_at	string	Mandatory. Pre-contribution created date in ISO 8601 extended format.
updated_at	string	Mandatory. Pre-contribution updated date in ISO 8601 extended format.

5. Data Object Package

5.1. Introduction

In this section, this document will provide common data objects details that will be used on GIG Worker API return response.

5.2. Data Objects

5.2.1. Pagination

5.2.1.1. Attributes

Name	Type	Description
total	integer	Total number of items.
per_page	integer	Items per page.
current_page	integer	Current page number.
last_page	integer	Last page number.
next_page_url	string	Next page URL.
prev_page_url	string	Previous page URL.
from	integer	Index of the first item being paginated.
to	integer	Index of the last item being paginated.
data	array	The paginated data.



5.2.2. ID-Name

A generic object for key-value pairs usually used in form selections (e.g. state selection, racial selection).

5.2.2.1. Attributes

Name	Type	Description
id	integer	The value to provide on submission.
name	string	The name or value for display.

5.2.3. Check User

5.2.3.1. Attributes

Name	Type	Description
ic_no	string	IC Number.
name	string	User name.
email	string	User email address.
mobile_no	string	User mobile number.
result	string	Result of IC number checking in PRIHTAIN.

5.2.4. User Details

5.2.4.1. Attributes

Name	Type	Description
ic_type	string	User IC Number Type.
ic_no	string	User IC Number.
name	string	User name.
email	string	User email address.
mobile_no	string	User mobile number.

house_phone_no	string	User house phone number.
gender	string	Gender.
race	string	Race.
person_status	string	Person status.
nationality	string	Nationality.
plan_id	integer	Plan ID.
updated_at	timestamp	Updated date.
created_at	timestamp	Created date.
id	integer	User ID.
plan	object	<i>Plan Details</i> object.

5.2.5. Update User Details

5.2.5.1. Attributes

Name	Type	Description
ic_type	string	User IC Number Type.
ic_no	string	User IC Number.
name	string	User name.
email	string	User email address.
mobile_no	string	User mobile number.
house_phone_no	string	User house phone number.
gender	string	Gender.
race	string	Race.
person_status	string	Person status.
nationality	string	Nationality.
address	object	<i>Address</i> object.
next_of_kin	object	<i>Next of KIN</i> object.



5.2.6. Address

5.2.6.1. Attributes

Name	Type	Description
line_1	string	Address line 1.
line_2	string	Address line 2.
state_id	integer	State ID.
city_id	integer	City ID.
postcode	string	Postcode.

5.2.7. Next of KIN

5.2.7.1. Attributes

Name	Type	Description
name	string	Next of KIN name.
mobile_no	string	Next of KIN mobile number.
relation	string	Next of KIN relation.

5.2.8. Sector

5.2.8.1. Attributes

Name	Type	Description
code	string	Sector code.
name	string	Sector name.
classes	array	<i>Array of Classes</i> objects.



5.2.9. Classes

5.2.9.1. Attributes

Name	Type	Description
code	string	Class code.
name	string	Class name.

5.2.10. State

5.2.10.1. Attributes

Name	Type	Description
id	integer	ID.
name	string	Name.
cities	array	<i>Array of ID-Name objects.</i>

5.2.11. Plan Details

5.2.11.1. Attributes

Name	Type	Description
id	integer	ID.
name	string	Contribution plan name.
yearly_amount	decimal	Contribution plan yearly amount.
monthly_amount	decimal	Contribution plan monthly amount.
created_at	timestamp	Created date.
updated_at	timestamp	Updated date.



5.2.12. Self-Employed Contribution

5.2.12.1. Attributes

Name	Type	Description
id	integer	Contribution ID.
started_at	timestamp	Start date.
expired_at	timestamp	Expired date.
class	string	Class name.
class_code	string	Class code.
sector_code	integer	Sector code.
sector_name	string	Sector name.
contribution_plan	decimal	Contribution plan amount.
contribution_month	integer	Contribution months.
contribution_plan_id	integer	Contribution plan ID.
paid_amount	decimal	Paid amount.
contribution_status_id	integer	Contribution status ID.
contribution_status	string	Contribution status name.
payment_status_id	integer	Payment status ID.
payment_status	string	Payment status name.
receipt_url	string	Display receipt url.
mime_type	string	File MIME type.
extension	string	File extension.
scheme_id	integer	Scheme ID.
scheme_name	string	Scheme name.



6. API Package

6.1. Prerequisite

In this section, this document will provide each API URLs to be requested to get valid IDs to be used in the section below.

For all IDs and flags, please refer to this section.

For all requests, the header and body parameters in the section Getting Started will be required.

The base-url has to be your service API, either in sandbox or production environments.

6.1.1. HTTP Status Code

Code	Status	Description
200	OK	The request was successful. Used for standard data retrieval and immediate updates.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
400	Bad Request	The server cannot process the request due to a client error (e.g., malformed request syntax or invalid JSON).
404	Not Found	The requested resource could not be found in the system.
422	Unprocessable Entity	The request was well-formed but failed validation.

6.2. Check Existence of A User

This API will give output whether the Gig Workers IC has been registered at Prihatin.

Method	GET
Status Success	200
Pattern	<code>{{base-url}}/api/v1/obs/{ic_no}</code>
Header	<code>Authorization: Bearer <API Authentication Key></code>

Returns	<i>Check User</i> object in data attribute.
----------------	---

Path Variables			
Name	Type	Required	Description
ic_no	string	Y	IC Number to be checked.

Response Example
<pre>{ "status": "success", "data": { "ic_no": "900101015555", "name": "John Doe", "email": "john.doe2@example.com", "mobile_no": "60123456788", "result": "REGISTERED_USER" } }</pre>
<pre>{ "status": "success", "data": { "ic_no": "900101015555", "name": null, "email": null, "mobile_no": null, "result": "USER_NOT_REGISTERED" } }</pre>

6.3. Register User

This API is used to register the Gig Workers as PRIHATIN users.



Method	POST
Status Success	200
Pattern	{{base-url}}/api/v1/obs
Header	Authorization: Bearer <API Authentication Key>
Returns	User Details object in the data attribute.

Parameters			
Name	Type	Required	Description
ic_type	string	Y	IC Type Code. New IC value: "B", Old IC value: "L", Permanent Resident value: "PR".
ic_no	string	Y	IC Number
name	string	Y	Name
email	string	Y	Email
mobile_no	string	Y	Mobile Number. Must include country code "60". Example: "60XXXXXXXXXX"

Response Example
<pre>{ "status": "success", "data": { "user": { "ic_type": "B", "ic_no": "010101029999", "name": "John Doe 1", "email": "john.doe@example.com", "mobile_no": "60169999999", "gender": "M",</pre>

```
    "race": "0",
    "person_status": "P",
    "nationality": "MY",
    "plan_id": 1,
    "updated_at": "2026-02-05T05:54:45.000000Z",
    "created_at": "2026-02-05T05:54:45.000000Z",
    "id": 5118,
    "plan": {
      "id": 1,
      "name": "Plan 1",
      "yearly_amount": "157.20",
      "monthly_amount": "13.10",
      "created_at": "2026-01-28T03:20:43.000000Z",
      "updated_at": "2026-01-28T03:20:43.000000Z"
    }
  }
}
```

```
{
  "status": "fail",
  "data": {
    "ic_no": [
      "The New IC has already been registered."
    ],
    "email": [
      "The Email has already been registered."
    ],
    "mobile_no": [
      "The Mobile No has already been registered."
    ]
  }
}
```



6.4. Get Sectors

This API will give the output of sectors.

Method	GET
Status Success	200
Pattern	<code>{{base-url}}/api/v1/sectors</code>
Header	<code>Authorization: Bearer <API Authentication Key></code>
Returns	<i>Pagination</i> object with <i>array</i> of <i>Sector</i> objects in <i>data</i> attribute.

Parameters

No parameters

Response Example

```
{
  "status": "success",
  "total": 21,
  "per_page": 15,
  "current_page": 1,
  "last_page": 2,
  "next_page_url": "https://gig-connector.perkeso.gov.my/api/v1/sectors?page=2",
  "prev_page_url": null,
  "from": 1,
  "to": 15,
  "data": [
    {
      "code": "I",
      "name": "ACCOMMODATION",
      "classes": [
        {
          "code": "01",
```

```
        "name": "Homestay"
      },
      {
        "code": "02",
        "name": "Chalet"
      },
      {
        "code": "03",
        "name": "Motel"
      }
    ]
  }
]
```

6.5. Get States and Cities

This API will give the output of states and cities within states.

Method	GET
Status Success	200
Pattern	{{base-url}}/api/v1/states
Header	Authorization: Bearer <API Authentication Key>
Returns	Pagination object with array of State objects in <i>data</i> attribute.

Parameters

No parameters

Response Example

```
{
  "status": "success",
```

```
    "total": 16,
    "per_page": 15,
    "current_page": 1,
    "last_page": 2,
    "next_page_url": "https://gig-
connector.perkeso.gov.my/api/v1/states?page=2",
    "prev_page_url": null,
    "from": 1,
    "to": 15,
    "data": [
      {
        "id": 1,
        "name": "Johor",
        "cities": {
          "data": [
            {
              "id": 84,
              "name": "Ayer Baloi"
            },
            {
              "id": 366,
              "name": "Ayer Hitam"
            },
            {
              "id": 98,
              "name": "Ayer Tawar 2"
            }
          ]
        }
      }
    ]
  }
}
```



6.6. Update User Details

This API will enable Platform Providers to update Gig Workers' details.

Method	PATCH
Status Success	200
Pattern	{{base-url}}/api/v1/obs/{ic_no}
Header	Authorization: Bearer <API Authentication Key>
Returns	User Details object in <i>data</i> attribute.

Path Variables			
Name	Type	Required	Description
ic_no	string	Y	IC Number to be checked. To be provided in path.

Parameters
No parameters

Parameters			
Name	Type	Required	Description
house_phone_no	string	N	House phone number.
gender	string	Y	The gender of the user. Gender options: M = Male F = Female
race	string	Y	The race of the user. Race options:

			M = Malay C = Chinese I = Indian P = Native Peninsular H = Native Sabah K = Native Sarawak O = Others
person_status	string	Y	The person status of the user. Person status options: Public = "P" Retired Police = "RP" Retired Military = "RM" Others = "O"
nationality_id	string	Y	The nationality of the user. Options: Malaysian = "M" Permanent Resident = "PR"
address_line_1	string	Y	Address line 1. Must not be greater than 255 characters.
address_line_2	string	N	Address line 2. Must not be greater than 255 characters.
state_id	integer	Y	State ID. Use API-Endpoint Get States and Cities.
city_id	integer	Y	City ID. Use API-Endpoint Get States and Cities.
post_code	string	Y	Postcode. Must be between 4 and 5 digits.
next_of_kin_name	string	Y	The name of the user's next of kin. Must not be greater

			than 255 characters.
next_of_kin_mobile_no	string	Y	The mobile number of the user's next of kin.
next_of_kin_relation	string	Y	The relation of the user's next of kin. Options: Wife = "W" Husband = "H" Children = "C" Mother = "M" Father = "F" Sibling = "S" Others = "O"

Response Example

```
{
  "status": "success",
  "data": {
    "user": {
      "id": 5107,
      "ic_type": "B",
      "ic_no": "900101015555",
      "name": "John Doe",
      "email": "john.doe2@example.com",
      "mobile_no": "60123456788",
      "house_phone_no": null,
      "gender": "M",
      "race": "M",
      "person_status": "P",
      "nationality": "MY",
      "plan_id": 1,
      "created_at": "2026-02-04T01:11:18.000000Z",
      "updated_at": "2026-02-05T07:15:35.000000Z"
    }
  }
}
```



```
}
```

6.7. Get Contribution List

This API will output all the contributions with status "ACTIVE".

Method	GET		
Status Success	200		
Pattern	<code>{{base-url}}/api/v1/obs/{ic_no}/contributions</code>		
Header	<code>Authorization: Bearer <API Authentication Key></code>		
Returns			
	Name	Type	Description
	name	string	User name.
	ic_no	string	User IC Number.
	data	array	<i>Pagination</i> object with <i>Self-Employed Contribution</i> objects in <i>data</i> attribute.

Path Variables

Name	Type	Required	Description
ic_no	string	Y	IC Number to be checked.

Parameters

No parameters

Response Example

```
{
  "status": "success",
  "name": " Dhinesh Al Vijiakumar",
  "ic_no": "9811114088081",
  "total": 1,
  "per_page": 15,
  "current_page": 1,
  "last_page": 1,
  "next_page_url": null,
  "prev_page_url": null,
  "from": 1,
  "to": 1,
  "data": [
    {
      "started_at": "",
      "expired_at": "",
      "id": 1374728,
      "contribution_plan": "157.20",
      "class": "SERVICE PROVIDER",
      "sector_code": "P",
      "sector_name": "SERVICE PROVIDER",
      "contribution_month": 1,
      "paid_amount": "13.10",
      "contribution_status": "Active",
      "contribution_status_id": 2,
      "payment_status": "Paid",
      "payment_status_id": 2,
      "receipt_url": "https://prihatin-staging.perkeso.gov.my/session/download-receipt/MzQ2NzE3sgAA",
      "mime_type": "application/pdf",
      "extension": "pdf",
      "class_code": "01",
      "contribution_plan_id": 1,
      "scheme_id": 0,
      "scheme_name": "Normal Contribution"
    }
  ]
}
```



```
]
}

{
  "status": "error",
  "message": "User not found."
}
```

6.8. Submit Deduction

This API will enable Platform Providers to submit deduction details for Gig Workers.

Method	POST
Status Success	202
Pattern	{{base-url}}/api/v1/deductions
Header	Authorization: Bearer <API Authentication Key>
Returns	Empty array data.

Parameters			
Name	Type	Required	Description
request_id	string	Y	Request ID. The unique identifier for the deduction submission request.
deductions	array	Y	Array of deductions objects.
Deduction Object			
ic_no	string	Y	IC number. Must not be greater than 12 characters.



transaction_id	string	Y	Transaction ID.
transacted_at	string	Y	Transaction date time. Must be a valid date in the format Y-m-d H:i:s. Example: 2025-02-01 12:10:45
sector_code	string	Y	Sector code. Use API-Endpoint Get Sectors.
amount	number	Y	Must match the regex <code>/^\d+(\.\d{1,2})?\$/</code> . Must be at least 0.
start_point_latitude	number	Y	User's latitude when the job is started. Must be between -90 and 90.
start_point_longitude	number	Y	User's longitude when the job is started. Must be between -180 and 180.
end_point_latitude	number	Y	User's latitude when the job is ended. Must be between -90 and 90.
end_point_longitude	number	Y	User's longitude when the job is ended. Must be between -180 and 180.

Response Example

```
{  
  "status": "success",
```



```
"data": []  
}
```

6.9. Cancel Deduction

This API will enable Platform Providers to cancel a deduction for Gig Workers.

Method	PUT
Status Success	200
Pattern	{{base-url}}api/v1/deductions/{transaction_id}
Header	Authorization: Bearer <API Authentication Key>
Returns	Empty array data.

Path Variables

Name	Type	Required	Description
transaction_id	string	Y	The transaction ID of the deduction to be cancelled.

Parameters

No parameters

Response Example

```
{  
  "status": "success",  
  "data": []  
}
```



6.10. Check Existence of Users by IC Number in Batch

This API will give output whether the multiple Gig Workers IC has been registered at Prihatin.

Method	GET
Status Success	200
Pattern	{{base-url}}api/v1/check-ic?ic_no={ic_no}
Header	Authorization: Bearer <API Authentication Key>
Returns	Check User object in data attribute.

Path Variables

Name	Type	Required	Description
ic_no	string	Y	IC number to be checked. Can be multiple IC numbers with comma (",") separated.

Parameters

No parameters

Response Example

```
{
  "status": "success",
  "data": [
    {
      "ic_no": "900101015555",
      "name": "John Doe",
      "email": "john.doe2@example.com",
      "mobile_no": "60123456788",
      "result": "REGISTERED_USER"
    }
  ]
}
```

```

    },
    {
      "ic_no": "880202025555",
      "name": null,
      "email": null,
      "mobile_no": null,
      "result": "USER_NOT_REGISTERED"
    }
  ]
}

```

6.11. Register User in Batch

This API is used to register multiple Gig Workers as PRIHATIN users.

Method	POST
Status Success	200
Pattern	{{base-url}}/api/v1/signup
Header	Authorization: Bearer <API Authentication Key>
Returns	<i>User Details</i> objects in the data attribute.

Parameters			
Name	Type	Required	Description
users	array	Y	Array of users objects.
Users Object			
ic_type	string	Y	IC Type Code. New IC value: "B", Old IC value: "L", Permanent Resident value: "PR".
ic_no	string	Y	IC Number



name	string	Y	Name
email	string	Y	Email
mobile_no	string	Y	Mobile Number. Must include country code "60". Example: "60XXXXXXXXXX"

Response Example

```
{
  "status": "success",
  "data": {
    "results": [
      {
        "status": "success",
        "user": {
          "ic_type": "B",
          "ic_no": "900101019999",
          "name": "John Doew",
          "email": "john.doew@example.com",
          "mobile_no": "60123450000",
          "gender": "M",
          "race": "O",
          "person_status": "P",
          "nationality": "MY",
          "plan_id": 1,
          "updated_at": "2026-02-05T18:57:03.000000Z",
          "created_at": "2026-02-05T18:57:03.000000Z",
          "id": 5224,
          "plan": {
            "id": 1,
            "name": "Plan 1",
            "yearly_amount": "157.20",
            "monthly_amount": "13.10",
```

```
        "created_at": "2026-01-28T03:20:43.000000Z",
        "updated_at": "2026-01-28T03:20:43.000000Z"
    }
}
},
{
    "status": "success",
    "user": {
        "ic_type": "B",
        "ic_no": "900101019998",
        "name": "John Dow",
        "email": "john.dow@example.com",
        "mobile_no": "60123450001",
        "gender": "F",
        "race": "O",
        "person_status": "P",
        "nationality": "MY",
        "plan_id": 1,
        "updated_at": "2026-02-05T18:57:03.000000Z",
        "created_at": "2026-02-05T18:57:03.000000Z",
        "id": 5225,
        "plan": {
            "id": 1,
            "name": "Plan 1",
            "yearly_amount": "157.20",
            "monthly_amount": "13.10",
            "created_at": "2026-01-28T03:20:43.000000Z",
            "updated_at": "2026-01-28T03:20:43.000000Z"
        }
    }
}
]
}
```



6.12. Update Users' Details in Batch

This API will enable Platform Providers to update multiple Gig Workers' details.

Method	PATCH
Status Success	200
Pattern	{{base-url}}/api/v1/user-details
Header	Authorization: Bearer <API Authentication Key>
Returns	Update User Details objects in <i>data</i> attribute.

Parameters			
Name	Type	Required	Description
users	array	Y	Array of users objects.
Users Object			
ic_no	string	Y	IC number.
house_phone_no	string	N	House phone number.
gender	string	Y	The gender of the user. Gender options: M = Male F = Female
race	string	Y	The race of the user. Race options: M = Malay C = Chinese I = Indian P = Native Peninsular H = Native Sabah K = Native Sarawak O = Others

person_status	string	Y	The person status of the user. Person status options: Public = "P" Retired Police = "RP" Retired Military = "RM" Others = "O"
nationality	string	Y	The nationality of the user. Options: Malaysian = "M" Permanent Resident = "PR"
address_line_1	string	Y	Address line 1. Must not be greater than 255 characters.
address_line_2	string	N	Address line 2. Must not be greater than 255 characters.
state_id	integer	Y	State ID. Use API-Endpoint Get States and Cities.
city_id	integer	Y	City ID. Use API-Endpoint Get States and Cities.
post_code	string	Y	Postcode. Must be between 4 and 5 digits.
next_of_kin_name	string	Y	The name of the user's next of kin. Must not be greater than 255 characters.
next_of_kin_mobile_no	string	Y	The mobile number of the user's next of kin.
next_of_kin_relation	string	Y	The relation of the user's next of kin. Options:

			Wife = "W" Husband = "H" Children = "C" Mother = "M" Father = "F" Sibling = "S" Others = "O"
--	--	--	--

Response Example

```
{
  "status": "success",
  "data": {
    "results": [
      {
        "ic_no": "900101019999",
        "name": "John Doew",
        "email": "john.doew@example.com",
        "mobile_no": "60123450000",
        "house_phone_no": "60123450020",
        "gender": "M",
        "race": "M",
        "person_status": "P",
        "nationality": "M",
        "address_line_1": "123, Jalan Ampang",
        "address_line_2": "Taman U Thant",
        "state_id": 1,
        "city_id": 366,
        "postcode": "55000",
        "next_of_kin_name": "Ahmad Bin Ali",
        "next_of_kin_mobile_no": "60123456789",
        "next_of_kin_relation": "S"
      },
      {
        "ic_no": "900101019998",
        "error": "USER_NOT_FOUND",
      }
    ]
  }
}
```

```

    ]
  }
}

```

6.13. Generate Token

Generate a new access token to API access.

Method	POST
Status Success	200
Pattern	{{base-url}}/oauth/token
Returns	Details of the new access token.

Parameters			
Name	Type	Required	Description
grant_type	string	Y	Grant type. Fixed value: "client_credentials"
client_id	string	Y	Client ID.
client_secret	string	Y	Client secret.

Response Example
<pre> { "token_type": "Bearer", "expires_in": 31536000, "access_token": "eyJ0eXAiOiJKV1QiLCJhbGciOiJSUzI1NiJ9.eyJhdWQiOiIwMTl..." } </pre>