

DevOps CLI Cheat Sheet for EKS & Linux Systems

mkdir create directories

```
mkdir -p /path/to/dir
```

-p : Create parent directories as needed (no error if exists)

mkfs format a block device

```
mkfs -t xfs /dev/xvdb
```

-t : Specify filesystem type (xfs, ext4, etc.)

mount mount filesystem

```
mount /dev/xvdb /mnt/data
```

-t : Filesystem type (optional)

-o : Mount options (e.g., ro, defaults, nofail)

tar compress/extract archives

```
tar -czvf archive.tar.gz mydir/
```

-c : Create

-x : Extract

-z : Gzip

-v : Verbose

-f : File name

rsync sync files/directories

```
rsync -avz src/ dest/
```

-a : Archive mode

-v : Verbose

-z : Compress

--delete : Delete extraneous files

cp, mv, rm copy, move, delete

```
cp -r src/ dest/
```

cp -r : Copy recursively

mv -f : Force overwrite

rm -rf : Recursive force delete

curl HTTP requests

curl -sSL https://site.com/file.sh | bash

-s : Silent

-S : Show errors

-L : Follow redirects

systemctl manage services

sudo systemctl restart kubelet

start/stop/restart/status/enable : Control service lifecycle

df and du check disk usage

df -h

df -h : Human-readable

du -sh /path : Summary, human-readable

chmod, chown file permissions

chmod -R 755 mydir

chown ubuntu:ubuntu mydir

chmod -R : Recursive permission change

chown : Set ownership

Bonus: Common EKS utilities

journalctl -u kubelet -f : Live kubelet logs

mount | grep containerd : Show mounts

lsblk : Block devices

blkid : Filesystem info