




Machine Learning Cheat Sheet

Types of Machine Learning

SUPERVISED LEARNING



Regression

- Linear
- Polynomial
- Ridge ,
- Lasso ,
- Decision Tree,
- Random Forest,
- SVR
- XGBoost

Classification

- Logistic
- Decision Tree
- Random Forest
- SVM
- k-NN
- Naïve Bayes
- XGBoost
- Neural Networks

UNSUPERVISED LEARNING



Clustering

- k-Means,
- Hierarchical
- DBSCAN,
- GMM
- Mean Shift

Dimensionality

- k-Means,
- Hierarchical
- DBSCAN,
- GMM
- Mean Shift

REINFORCEMENT LEARNING



Reward-based learning

- Q-Learning
- Deep Q-Networks (DQN)
- SARSA (State-Action-Reward-State-Action)
- Policy Gradient Methods
- Actor-Critic Methods
- Proximal Policy Optimization (PPO)
- Trust Region Policy Optimization (TRPO)
- Monte Carlo Methods

Data Preprocessing

df.isnull().sum(): Check missing values

df.dropna(): Remove missing values

df.fillna(value): Fill missing values

StandardScaler(): Standardization (mean=0, std=1)

MinMaxScaler(): Normalization (range [0,1])

LabelEncoder(): Convert categorical labels to numbers

OneHotEncoder(): Convert categorical features into dummy variables

Train Test Split



```
from sklearn.model_selection  
import train_test_split
```

```
X_train, X_test, y_train,  
y_test = train_test_split(X,  
y, test_size=0.2,  
random_state=42)
```


Regression Models

- Linear Regression
- Polynomial Regression
- Ridge & Lasso Regression
- Decision Tree Regression
- Random Forest Regression
- Support Vector Regression (SVR)



```
from sklearn.linear_model import  
LinearRegression  
model = LinearRegression()  
model.fit(X_train, y_train)  
y_pred = model.predict(X_test)
```

Classification Models

- Logistic Regression
- K-Nearest Neighbors (KNN)
- Decision Trees
- Random Forest
- Support Vector Machines (SVM)
- Naive Bayes
- Neural Networks (MLP)



```
from sklearn.ensemble import  
RandomForestClassifier  
model =  
RandomForestClassifier(n_estimators=100)  
model.fit(X_train, y_train)  
y_pred = model.predict(X_test)
```

Evaluation Metrics

Regression

- **MAE (Mean Absolute Error):**
Measures avg absolute error
- **MSE (Mean Squared Error):**
Penalizes large errors
- **RMSE (Root Mean Squared Error):** Square root of MSE
- **R² Score:** Explains variance captured by model

Classification

- **Accuracy:** $(TP + TN) / (TP + FP + TN + FN)$
- **Precision:** $TP / (TP + FP)$
- **Recall:** $TP / (TP + FN)$
- **F1-Score:** $2 * (Precision * Recall) / (Precision + Recall)$
- **ROC Curve:** Trade-off between TPR & FPR

Feature Selection & Engineering

Feature Importance: Use models like RandomForest

PCA (Principal Component Analysis): Reduce dimensionality

Correlation Matrix: Find highly correlated features



```
from sklearn.decomposition import PCA  
pca = PCA(n_components=2)  
X_pca = pca.fit_transform(X)
```

Hyperparameter Tuning

GridSearchCV – Tries all combinations

RandomizedSearchCV – Randomized search



```
from sklearn.model_selection import
GridSearchCV
params = {'n_estimators': [50, 100,
150]}
grid =
GridSearchCV(RandomForestClassifier()
, params, cv=5)
grid.fit(X_train, y_train)
```

Clustering Algorithms

- K-Means Clustering
- Hierarchical Clustering
- DBSCAN (Density-Based Spatial Clustering)



```
from sklearn.cluster import  
KMeans  
  
kmeans = KMeans(n_clusters=3)  
kmeans.fit(X)  
labels = kmeans.predict(X)
```


Deep Learning Basics

- Neural Networks
- Convolutional Neural Networks (CNNs)
- Recurrent Neural Networks (RNNs)
- Transformers (BERT, GPT)



```
import tensorflow as tf
model = tf.keras.Sequential([
    tf.keras.layers.Dense(128, activation='relu'),
    tf.keras.layers.Dense(1, activation='sigmoid')
])
model.compile(optimizer='adam',
loss='binary_crossentropy', metrics=['accuracy'])
```

Found Helpful?

Repost



Follow for more!

