



Kahoot

Quiz 16 - Cementing Operation

Test your knowledge of primary cementing objectives, well data for job design, slurries and additives, casing accessories, sequence of single-stage jobs, two-stage methods, thickening and gel strength... [Show more](#)

Questions (20)

1 - Quiz

What are the **objectives** of cementing in drilling operations?



▲ Provide Zonal Isolation ✓	◆ Support Torsional Load of Casing Strings ✓
● Provide Casing Support and Protection ✓	■ Support the Borehole ✓

2 - Quiz

Which **well data** are required for **designing** a cementing job?



▲ Survey Data ✓	◆ Caliper Data ✓
● Well Temperature and Formation Pressure ✓	■ Mud Properties ✓

3 - True or false

Inaccurate well temperature and formation pressure can cause excessive WOC, premature setting, and well security issues.



◆ True ✓	▲ False
----------	---------

4 - Quiz


In which **casing** section is the **stab-in** cementing method commonly used?



▲ Conductor Casing ✓	◆ Surface Casing
● Intermediate Casing	■ Production Casing

5 - True or false


Surface casing cementing jobs face significant challenges due to low temperatures.



◆ True ✓	▲ False
----------	---------

6 - Quiz

Why is a **two-stage cementing** job used in drilling operations?



▲ To Manage Hydrostatic Pressure ✓	◆ Increase Speed of Drilling Operations
● Reduce Risk of Cement Loss ✓	■ Improve Cement Placement Above Loss Zones ✓

7 - Quiz

What **casing accessories** are used to **control flow** and ensure **proper placement** during **cementing**?



☒ Centralizer
 ☒ Stop Collar
 ☒ Float Collar
 ☒ Float Shoe

8 - True or false

A **wiper plug** is used to separate **cement slurry** from **drilling** and **displacement fluids**.

☒ True
 ☒ False

9 - Puzzle

Arrange the Sequence for Single-Stage Cementing Job

☒ Drop Bottom Plug
 ☒ Pump Slurry
 ☒ Drop Top Plug
 ☒ Pump Displacement Fluid

10 - Quiz

What **fluids** are used to **separate cement slurry** from **drilling fluid** during **cementing** operations?

☒ Washer Fluid
 ☒ Spacer
 ☐ Lead Slurry
 ☐ Tail Slurry

11 - True or false

Tail slurry is the last **cement slurry** pumped during **primary cementing**.

☒ True
 ☒ False

12 - True or false

Lead slurry is often **lighter** in **density** and **strength** than the **tail slurry**.

☒ True
 ☒ False

13 - Quiz

Based on **API** classification, which of the following are the **classes** of **Portland cement**?

☒ Class G
 ☒ Class H
 ☐ Class I
 ☐ Class J

14 - Quiz

Which **cementing additive** is used to **delay** the **setting** time, providing more time for cement to be placed and adjusted?

☒ Retarders
 ☒ Accelerators
 ☐ Dispersants
 ☐ Extenders

15 - True or false

A shorter thickening time prevented cement slurry from reaching the designed annulus, resulting in cement inside casing.

◆ True ✓ ▲ False

16 - Quiz

What additives are required to improve mud removal, reduce friction pressure, and enhance pumpability of cement slurry?

▲ Dispersants ✓ ◆ Gelling Agents ✓
● Expanding Agents ■ Gas Control

17 - Quiz

Why is it necessary to use excess cement slurry during cementing operations in drilling wells?

▲ Ensure Complete Coverage of Hole Irregularity and Enlargement ✓ ◆ Enhance Pumpability of Slurry
● Ensure Cementer Gets a Good Workout and Stays in Shape ■ Give More Money to Cementing Contractor

18 - Quiz

The following is cementing additive to reduce filtration

▲ Fluid loss control agents ✓ ◆ Retarders
● Dispersant ■ Gas control agents

19 - Puzzle

Please select the correct of sequence in a Cementing working fluid

▲ Wash Fluid ✓
◆ Spacer ✓
● Lead Cement ✓
■ Tail Cement ✓

20 - True or false

BONUS!!! Choose the True option.

◆ True ✓ ▲ False

Details

Max. 200 participants. [Upgrade for more](#)

Updated 2 days ago • Visibility: Public

Media credits

1. Mekdet/Moment/Getty Images

7. Sadagus/iStock/Getty Images