1. #include <stdio.h>

#include <sys/types.h>

#include <sys/stat.h>

int main()

{

  if (mkfifo("myfifo", 0666) == -1)

  {

    perror("mkfifo");

    return 1;

  }

  printf("FIFO created\n");

  return 0;

}

```
hamsini@HamsiniVanam:~$ gcc fifo_create.c -o fifo_create
hamsini@HamsiniVanam:~$ ./fifo_create
FIFO created
hamsini@HamsiniVanam:~$ ls -l myfifo
prw-r--r-- 1 root root 0 Sep 29 02:50 myfifo
hamsini@HamsiniVanam:~$ ./fifo_create
mkfifo: File exists
hamsini@HamsiniVanam:~$
```

2. #include <stdio.h>

#include <fcntl.h>

#include <unistd.h>

int main()

{

  int fd;

  char buffer[100];

  fd = open("myfifo", O_RDONLY);

  read(fd, buffer, sizeof(buffer));

  printf("Received: %s\n", buffer);

```
    close(fd);
    return 0;
}
```

```
hamsini@HamsiniVanam:~$ gcc fifo_read.c -o fifo_read
hamsini@HamsiniVanam:~$ ./fifo_read
Received: Hello from Writer
hamsini@HamsiniVanam:~$
```

3.

```
#include <stdio.h>
#include <fcntl.h>
#include <unistd.h>
#include <string.h>

int main()
{
    int fd;
    char message[] = "Hello from Writer";

    fd = open("myfifo", O_WRONLY);
    write(fd, message, strlen(message) + 1);
    close(fd);
    printf("Message sent\n");
    return 0;
}
```

```
hamsini@HamsiniVanam:~$ gcc fifo_write.c -o fifo_write
hamsini@HamsiniVanam:~$ ./fifo_write
Message sent
hamsini@HamsiniVanam:~$
```