

FOUNDATION PLAN

SCALE: 1:100

1

2

26'-0"

F10

F12

8'-6"

12'-0"

AUTOCONST STRUCTURAL

FOUNDATION PLAN

SHEET S-01

REV D

FOOTING SCHEDULE

MARK	SIZE	DEPTH	REINFORCEMENT	CONCRETE
F10	750x750	500	8-T16 E/W	32 MPa
F12	900x900	600	10-T20 E/W	32 MPa
F15	1200x1200	700	12-T25 E/W	40 MPa

AUTOCONST STRUCTURAL

FOOTING SCHEDULE

SHEET S-02

REV D

OPENING SCHEDULE

MARK	SIZE	TYPE	REMARKS
D-01	0.9x2.1	STEEL	EXTERNAL
D-02	0.9x2.1	TIMBER	INTERNAL
D-03	1.2x2.1	STEEL	FIRE RATED 60MIN

GENERAL NOTES

- 1. ALL CONCRETE TO BE 32 MPa UNLESS NOTED OTHERWISE.
- 2. COVER TO REINFORCEMENT 40mm TO EARTH FACES.
- 3. DO NOT SCALE FROM DRAWINGS.
- 4. FOUNDATIONS DESIGNED FOR BEARING CAPACITY 200 kPa.

AUTOCONST STRUCTURAL

OPENING SCHEDULE & NOTES

SHEET S-03

REV D