
INTERACTIVE END-OF-CHAPTER EXERCISES

TCP IN ACTION: SLOW START, CONGESTION AVOIDANCE, AND FAST RETRANSMIT

Consider the figure below, which plots the evolution of TCP's congestion window at the beginning of each time unit (where the unit of time is equal to the RTT); see Figure 3.53 in the text. In the abstract model for this problem, TCP sends a "flight" of packets of size *cwnd* at the beginning of each time unit. The result of sending that flight of packets is that either *(i)* all packets are ACKed at the end of the time unit, *(ii)* there is a timeout for the first packet, or *(iii)* there is a triple duplicate ACK for the first packet. In this problem, you are asked to reconstruct the sequence of events (ACKs, losses) that resulted in the evolution of TCP's *cwnd* shown below.



Consider the evolution of TCP's congestion window in the example above and answer the following questions. The initial value of *cwnd* is 1 and the initial value of *ssthresh* (shown as a red +) is 8.

QUESTION LIST

1. Give the times at which TCP is in slow start. Format your answer like: 1,3,5,9 (If none submit blank)

2. Give the times at which TCP is in congestion avoidance. Format your answer like: 1,3,5,9 (If none submit blank)

3. Give the times at which TCP is in fast recovery. Format your answer like: 1,3,5,9 (If none submit blank)

4. Give the times at which packets are lost via timeout. Format your answer like: 1,3,5,9 (If none submit blank)

5. Give the times at which packets are lost via *triple ACK*. Format your answer like: 1,3,5,9 (If none submit blank)

6. Give the times at which the value of *ssthresh* changes (if it changes between t=3 and t=4, use t=4 in your answer)

SOLUTION

1. The times where TCP is in slow start are: 1,2,3,10,11,12,21,22,23,29,30,31,34,35,36

2. The times where TCP is in congestion avoidance are: 4,5,6,7,8,9,13,14,15,16,17,18,20,24,26,27,28,32,33,37,38,39,40

3. The times where TCP is in fast recovery are: 19,25


4. The times where TCP has a loss by timeout are: 9,20,28,33

5. The times where TCP has a loss by triple duplicate ACK are: 18,24

6. The times where the *ssthresh* changes are: 10,21,25,29,34

The complete solution is shown in the figure below:

- For intervals of time when TCP is in slow start, the plotted value of *cwnd* is shown as a green square
- For intervals of time when TCP is in congestion avoidance, the plotted value of *cwnd* is shown as a yellow square
- For intervals of time when TCP is in fast reccovery, the plotted value of *cwnd* is shown as an orange square
- The values for *ssthresh* are shown following a change as a red plus sign
- A flight of packets experiencing a loss has the loss type (which determines the next value of *cwnd*) labeled above



QUESTION 1 OF 6

Give the times at which TCP is in slow start. Format your answer like: 1,3,5,9 (If none submit blank)

Answer

CHECK | HINT | SKIP

We greatly appreciate the work of John Broderick (UMass '21) in helping to develop these interactive problems.

Copyright © 2010-2025 J.F. Kurose, K.W. Ross
Comments welcome and appreciated: kurose@cs.umass.edu