LAB1 2025 - - > to be presented in the lab hour on 13th March

We have two memory locations:

< Loc1 is for data and Loc2 is for result. >

```
Loc1    equ     0x20002000
Loc2    equ     0x30003000
```

We have 16 values F0, F1, F2, F3, F4, F5, F6, F7, F8, F9, FA, FB, FC, FD, FE, FF

Now we can fill our specified memory location with these values using,

```
memPrep LDR     R0, =Loc1
        ldr     R1, =0xF0F1F2F3
        mov     r2, #4; index
        LDR     r3, =0x04040404; cnstant

        ;       now fill the memdry with data

filling str     R1, [R0]
        sub     r2, r2, #1
        add     r0, r0, #4
        ADD     r1, r1, r3
        cmp     R2, #0
        BGT     filling
```

Then the memory appears like,

Symbol	Address	Value
	0×20002000	0×F0F1F2F3
	0×20002004	0×F4F5F6F7
	0×20002008	0×F8F9FAFB
	0×2000200C	0×FCFDFEFF

Here our task comes, WE NEED TO DETERMINE THE AVERAGE VALUE OF ODD NUMBERS.

HINTS:

- To pick values from memory, we can either use LDR and Logical Shift Operators or we can utilize LDRB instruction.
- To understand a number is odd or not, we can compare the number with 0x1.