
Introduction to Java Programming and Data Structures

Thirteenth Edition



Chapter 7

Single-Dimensional Arrays

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Opening Problem

Read one hundred numbers, compute their average, and find out how many numbers are above the average.

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Objectives (1 of 3)

7.1 To describe why arrays are necessary in programming (§7.1).

7.2 To declare array reference variables and create arrays (§§7.2.1–7.2.2).

7.3 To obtain array size using **`arrayRefVar.length`** and know default values in an array (§7.2.3).

7.4 To access array elements using indexes (§7.2.4).

7.5 To declare, create, and initialize an array using an array initializer (§7.2.5).

7.6 To program common array operations (displaying arrays, summing all elements, finding the minimum and maximum elements, random shuffling, and shifting elements) (§7.2.6).

7.7 To simplify programming using the foreach loops (§7.2.7).

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Objectives (2 of 3)

7.8 To apply arrays in application development (**`AnalyzeNumbers, DeckOfCards`**) (§§7.3–7.4).

7.9 To copy contents from one array to another (§7.5).

7.10 To develop and invoke methods with array arguments and return values (§§7.6–7.8).

7.11 To define a method with a variable-length argument list (§7.9).

7.12 To search elements using the linear (§7.10.1) or binary (§7.10.2) search algorithm.

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Objectives (3 of 3)

7.13 To sort an array using the selection sort approach (§7.11).

7.14 To use the methods in the **`java.util.Arrays`** class (§7.12).


7.15 To pass arguments to the main method from the command line (§7.13).

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Introducing Arrays

Array is a data structure that represents a collection of the same types of data.



Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Declaring Array Variables

- `datatype[] arrayRefVar;`

  Example:

  ```
  double[] myList;
  ```

- `datatype arrayRefVar[];` **// This style is allowed, but not preferred**

  Example:

  ```
  double myList[];
  ```

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Creating Arrays

```
arrayRefVar = new datatype[arraySize];
```

Example:

```
myList = new double[10];
```

`myList[0]` references the first element in the array.

`myList[9]` references the last element in the array.

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Declaring and Creating in One Step

- ```
  datatype[] arrayRefVar = new
  datatype[arraySize];

  double[] myList = new double[10];
  ```

- ```
  datatype arrayRefVar[] = new
  datatype[arraySize];

  double myList[] = new double[10];
  ```

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

The Length of an Array

Once an array is created, its size is fixed. It cannot be changed. You can find its size using

```
arrayRefVar.length
```

For example,

```
myList.length returns 10
```


Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Default Values

When an array is created, its elements are assigned the default value of

- **0** for the numeric primitive data types,
- `'\u0000'` for **`char`** types, and
- **`false`** for **`boolean`** types.

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Indexed Variables

The array elements are accessed through the index. The array indices are **0-based**, i.e., it starts from 0 to `arrayRefVar.length-1`. In the example in Figure 6.1, `myList` holds ten double values and the indices are from 0 to 9.

Each element in the array is represented using the following syntax, known as an **indexed variable**:

```
arrayRefVar[index];
```

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Using Indexed Variables

After an array is created, an indexed variable can be used in the same way as a regular variable. For example, the following code adds the value in `myList[0]` and `myList[1]` to `myList[2]`.

```
myList[2] = myList[0] + myList[1];
```

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Array Initializers

- Declaring, creating, initializing in one step:

```
double[] myList = {1.9, 2.9, 3.4, 3.5};
```

This shorthand syntax must be in one statement.

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Declaring, Creating, Initializing Using the Shorthand Notation

```
double[] myList = {1.9, 2.9, 3.4, 3.5};
```

This shorthand notation is equivalent to the following statements:

```
double[] myList = new double[4];

myList[0] = 1.9;

myList[1] = 2.9;

myList[2] = 3.4;

myList[3] = 3.5;
```

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Caution

Using the shorthand notation, you have to declare, create, and initialize the array all in one statement. Splitting it would cause a syntax error. For example, the following is wrong:

```
double[] myList;

myList = {1.9, 2.9, 3.4, 3.5};
```

Pearson


Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Trace Program With Arrays (1 of 16)

Declare array variable values, create an array, and assign its reference to values

```
public class Test {
  public static void main(S ng[] args) {
    int[] values = new int[5];
    for (int i = 1; i < 5; i++) {
      values[i] = i + values[i-1];
    }
    values[0] = values[1] + values[4];
  }
}
```


After the array is created



Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Trace Program With Arrays (2 of 16)



After the array is created

0	0
1	0
2	0
3	0
4	0

Pearson


Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Trace Program With Arrays (3 of 16)

i (=1) is less than 5

```
public class Test {
  public static void main(String[] args) {
    int[] values = new int[5];
    for (int i = 1; i < 5; i++) {
      values[i] = i + values[i-1];
    }
    values[0] = values[1] + values[4];
  }
}
```


After the array is created



Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Trace Program With Arrays (4 of 16)



Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Trace Program With Arrays (5 of 16)

After i++, i becomes 2

```
public class Test {
  public static void main(Stri[] args) {
    int[] values = new int[5];
    for (int i = 1; i < 5; i++) {
      values[i] = i + values[i-1];
    }
    values[0] = values[1] + values[4];
  }
}
```

After the first iteration

0	0
1	1
2	0
3	0
4	0

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Trace Program With Arrays (6 of 16)

```
public class Test {
  public static void main(String[]
      args) {
    int[] values = new int[5];
    for (int i = 1; i < 5; i++) {
      values[i] = i + values[i-1];
    }
    values[0] = values[1] +
      values[4];
  }
}
```

i (= 2) is less than 5


After the first iteration

0	0
1	1
2	0
3	0
4	0

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Trace Program With Arrays (7 of 16)



Pearson


Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Trace Program With Arrays (8 of 16)

After this, i becomes 3.

```
public class Test {
  public static void main(String[] args) {
    int[] values = new int[5];
    for (int i = 1; i < 5; i++) {
      values[i] = i + values[i-1];
    }
    values[0] = values[1] + values[4];
  }
}
```

After the second iteration



Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Trace Program With Arrays (9 of 16)

i (=3) is still less than 5.

```
public class Test {
  public static void main(St[]g[] args) {
    int[] values = new int[5];
    for (int i = 1; i < 5; i++) {
      values[i] = i + values[i-1];
    }
    values[0] = values[1] + values[4];
  }
}
```

After the second iteration

0	0
1	1
2	3
3	0
4	0

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Trace Program With Arrays (10 of 16)

After this line, values[3] becomes 6 (3 + 3)

```
public class Test {
  public static void main(String[] a
    int[] values = new int[5];
    for (int i = 1; i < 5; i++) {
      values[i] = i + values[i-1];
    }
    values[0] = values[1] + values[4];
  }
}
```

After the third iteration

0	0
1	1
2	3
3	6
4	0

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Trace Program With Arrays (11 of 16)

After this, i becomes 4

```
public class Test {
  public static void main(String[] args) {
    int[] values = new int[5];
    for (int i = 1; i < 5; i++) {
      values[i] = i + values[i-1];
    }
    values[0] = values[1] + values[4];
  }
}
```

After the third iteration

0	0
1	1
2	3
3	6
4	0

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Trace Program With Arrays (12 of 16)

i (=4) is still less than 5

```
public class Test {
  public static void main(String[] args) {
    int[] values = new int[5];
    for (int i = 1; i < 5; i++) {
      values[i] = i + values[i-1];
    }
    values[0] = values[1] + values[4];
  }
}
```

After the third iteration

0	0
1	1
2	3
3	6
4	0

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Trace Program With Arrays (13 of 16)

After this, values[4] becomes 10 (4 + 6)

```
public class Test {
  public static void main(St      [] args) {
    int[] values = new int[5];
    for (int i = 1; i < 5; i++) {
      values[i] = i + values[i-1];
    }
    values[0] = values[1] + values[4];
  }
}
```


After the fourth iteration

0	0
1	1
2	3
3	6
4	10

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Trace Program With Arrays (14 of 16)



Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Trace Program With Arrays (15 of 16)

i (=5) < 5 is false. Exit the loop

```
public class Test {
  public static void m   (String[] args) {
    int[] values = ne  int[5];
    for (int i = 1; i < 5; i++) {
      values[i] = i + values[i-1];
    }
    values[0] = values[1] + values[4];
  }
}
```


After the fourth iteration

0	0
1	1
2	3
3	6
4	10

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Trace Program With Arrays (16 of 16)



Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Processing Arrays

See the examples in the text.

1. (Initializing arrays with input values)
2. (Initializing arrays with random values)
3. (Printing arrays)
4. (Summing all elements)
5. (Finding the largest element)
6. (Finding the smallest index of the largest element)
7. (**Random shuffling**)
8. (**Shifting elements**)

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Initializing Arrays With Input Values

```
java.util.Scanner input = new java.util.Scanner(System.in);

System.out.print("Enter " + myList.length + " values: ");

for (int i = 0; i < myList.length; i++)

  myList[i] = input.nextDouble();
```

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Initializing Arrays With Random Values

```
for (int i = 0; i < myList.length; i++) {
 myList[i] = Math.random() * 100;
}
```

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Printing Arrays

```
for (int i = 0; i < myList.length; i++) {
 System.out.print(myList[i] + " ");
}
```

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Summing All Elements

```
double total = 0;

for (int i = 0; i < myList.length; i++) {

 total += myList[i];

}
```

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Finding the Largest Element

```
double max = myList[0];

for (int i = 1; i < myList.length; i++) {

 if (myList[i] > max) max = myList[i];

}
```


Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Random Shuffling

```
for (int i = 0; i < myList.length - 1; i++) {
  // Generate an index j randomly
  int j = (int)(Math.random()
    * myList.length);

  // Swap myList[i] with myList[j]
  double temp = myList[i];
  myList[i] = myList[j];
  myList[j] = temp;
}
```



Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Shifting Elements

```
double temp = myList[0]; // Retain the first element

// Shift elements left
for (int i = 1; i < myList.length; i++) {
  myList[i - 1] = myList[i];
}

// Move the first element to fill in the last position
myList[myList.length - 1] = temp;
```



Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Enhanced `for` Loop (for-each loop)

JDK 1.5 introduced a new for loop that enables you to traverse the complete array sequentially without using an index variable. For example, the following code displays all elements in the array `myList`:

```
for (double value: myList)
  System.out.println(value);
```

In general, the syntax is

```
for (elementType value: arrayRefVar) {
  // Process the value
}
```

You still have to use an index variable if you wish to traverse the array in a different order or change the elements in the array.

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Analyze Numbers

Read one hundred numbers, compute their average, and find out how many numbers are above the average.

AnalyzeNumbers

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Problem: Deck of Cards (1 of 4)

The problem is to write a program that picks four cards randomly from a deck of 52 cards. All the cards can be represented using an array named deck, filled with initial values 0 to 51, as follows:

```
int[] deck = new int[52];

// Initialize cards

for (int i = 0; i < deck.length; i++)


  deck[i] = i;
```

DeckOfCards

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved


Problem: Deck of Cards (2 of 4)



Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Problem: Deck of Cards (3 of 4)



DeckOfCards


Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Problem: Deck of Cards (4 of 4)

This problem builds a foundation for future more interesting and realistic applications:

See Exercise 20.15.



https://liveexample.pearsoncmg.com/dsanimation/24Point.html


Pearson


Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Copying Arrays (1 of 2)

Often, in a program, you need to duplicate an array or a part of an array. In such cases you could attempt to use the assignment statement (=), as follows:

```
list2 = list1;
```





Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Copying Arrays (2 of 2)

Using a loop:

```
int[] sourceArray = {2, 3, 1, 5, 10};

int[] targetArray = new
  int[sourceArray.length];


for (int i = 0; i < sourceArrays.length;
i++)

    targetArray[i] = sourceArray[i];
```

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

The `arraycopy` Utility

```
arraycopy(sourceArray, src_pos, targetArray,
  tar_pos, length);
```

Example:

```
System.arraycopy(sourceArray, 0,
  targetArray, 0, sourceArray.length);
```

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Passing Arrays to Methods

```
public static void printArray(int[] array) {
  for (int i = 0; i < array.length; i++) {
    System.out.print(array[i] + " ");
  }
}
```

```
Invoke the method

int[] list = {3, 1, 2, 6, 4, 2};
printArray(list);
```

```
Invoke the method
printArray(new int[]{3, 1, 2, 6, 4, 2});
```

Anonymous array

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Anonymous Array

The statement

```
printArray(new int[]{3, 1, 2, 6, 4, 2});
```

creates an array using the following syntax:

```
new dataType[]{literal0, literal1, ..., literalk};
```

There is no explicit reference variable for the array. Such array is called an **anonymous array**.

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Pass by Value

Java uses **pass by value** to pass arguments to a method. There are important differences between passing a value of variables of primitive data types and passing arrays.

- For a parameter of a primitive type value, the actual value is passed. Changing the value of the local parameter inside the method does not affect the value of the variable outside the method.
- For a parameter of an array type, the value of the parameter contains a reference to an array; this reference is passed to the method. Any changes to the array that occur inside the method body will affect the original array that was passed as the argument.

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved


Simple Example

```
public class Test {
  public static void main(String[] args) {
    int x = 1; // x represents an int value
    int[] y = new int[10]; // y represents an array of int values

    m(x, y); // Invoke m with arguments x and y

    System.out.println("x is " + x);
    System.out.println("y[0] is " + y[0]);
  }


  public static void m(int number, int[] numbers) {
    number = 1001; // Assign a new value to number
    numbers[0] = 5555; // Assign a new value to numbers[0]
  }
}
```



Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved


Call Stack (1 of 2)



When invoking `m(x, y)`, the values of `x` and `y` are passed to number and numbers. Since y contains the reference value to the array, numbers now contains the same reference value to the same array.

Pearson
Copyright © 2024 Pearson Education, Inc. All Rights Reserved


Call Stack (2 of 2)



When invoking `m(x, y)`, the values of `x` and `y` are passed to number and numbers. Since y contains the reference value to the array, numbers now contains the same reference value to the same array.

Pearson
Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Heap



The JVM stores the array in an area of memory, called **heap**, which is used for dynamic memory allocation where blocks of memory are allocated and freed in an arbitrary order.

Pearson
Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Passing Arrays as Arguments


- Objective: Demonstrate differences of passing primitive data type variables and array variables.

TestPassArray

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Example



Pearson


Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Returning an Array From a Method

```
public static int[] reverse(int[] list) {
  int[] result = new int[list.length];

  for (int i = 0, j = result.length - 1;
       i < list.length; i++, j--) {
    result[j] = list[i];
  }

  return result;
}
```




```
int[] list1 = {1, 2, 3, 4, 5, 6};
int[] list2 = reverse(list1);
```

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Trace the Reverse Method (1 of 22)


```
int[] list1 = {1, 2, 3, 4, 5, 6};
int[] list2 = reverse(list1);

public static int[] reverse(int[] list) {
  int[] result = new int[list.length];

  for (int i = 0, j = result.length - 1;
       i < list.length; i++, j--) {
    result[j] = list[i];
  }

  return result;
}
```

Declare result and create array



Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Trace the Reverse Method (2 of 22)


```
int[] list1 = {1, 2, 3, 4, 5, 6};
int[] list2 = reverse(list1);


  public static int[] reverse(int[] list) {
    int[] result = new int[list.length];

    for (int i = 0, j = result.length - 1;
         i < list.length; i++, j--) {
      result[j] = list[i];
    }

    return result;
  }
```

i = 0 and j = 5



Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Trace the Reverse Method (3 of 22)


```
int[] list1 = {1, 2, 3, 4, 5, 6};
int[] list2 = reverse(list1);

public static int[] reverse(int[] list) {
  int[] result = new int[list.length];

  for (int i = 0, j = result.length - 1;
       i < list.length; i++, j--) {
    result[j] = list[i];
  }

  return result;
}
```

i (= 0) is less than 6



Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Trace the Reverse Method (4 of 22)


```
int[] list1 = {1, 2, 3, 4, 5, 6};
int[] list2 = reverse(list1);


  public static int[] reverse(int[] list) {
    int[] result = new int[list.length];

    for (int i = 0, j = result.length - 1;
         i < list.length; i++, j--) {
      result[j] = list[i];
    }

    return result;
  }
```

i = 0 and j = 0
Assign list[0] to result[5]



Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Trace the Reverse Method (5 of 22)


```
int[] list1 = {1, 2, 3, 4, 5, 6};
int[] list2 = reverse(list1);


  public static int[] reverse(int[] list) {
    int[] result = new int[list.length];

    for (int i = 0, j = result.length - 1;
         i < list.length; i++, j--) {
      result[j] = list[i];
    }

    return result;
  }
```

After this, i becomes 1 and j becomes 4



Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Trace the Reverse Method (6 of 22)


```
int[] list1 = {1, 2, 3, 4, 5, 6};
int[] list2 = reverse(list1);


  public static int[] reverse(int[] list) {
    int[] result = new int[list.length];

    for (int i = 0, j = result.length - 1;
         i < list.length; i++, j--) {
      result[j] = list[i];
    }

    return result;
  }
```

i (=1) is less than 6



Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Trace the Reverse Method (7 of 22)


```
int[] list1 = {1, 2, 3, 4, 5, 6};
int[] list2 = reverse(list1);


  public static int[] reverse(int[] list) {
    int[] result = new int[list.length];

    for (int i = 0, j = result.length - 1;
         i < list.length; i++, j--) {
      result[j] = list[i];
    }

    return result;
  }
```

i = 1 and j = 4
Assign list[1] to result[4]



Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Trace the Reverse Method (8 of 22)


```
int[] list1 = {1, 2, 3, 4, 5, 6};
int[] list2 = reverse(list1);


  public static int[] reverse(int[] list) {
    int[] result = new int[list.length];

    for (int i = 0, j = result.length - 1;
         i < list.length; i++, j--) {
      result[j] = list[i];
    }

    return result;
  }
```

After this, i becomes 2 and j becomes 3



Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Trace the Reverse Method (9 of 22)


```
int[] list1 = {1, 2, 3, 4, 5, 6};
int[] list2 = reverse(list1);


  public static int[] reverse(int[] list) {
    int[] result = new int[list.length];

    for (int i = 0, j = result.length - 1;
         i < list.length; i++, j--) {
      result[j] = list[i];
    }

    return result;
  }
```

i (=2) is still less than 6



Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Trace the Reverse Method (10 of 22)


```
int[] list1 = {1, 2, 3, 4, 5, 6};
int[] list2 = reverse(list1);


  public static int[] reverse(int[] list) {
    int[] result = new int[list.length];

    for (int i = 0, j = result.length - 1;
         i < list.length; i++, j--) {
      result[j] = list[i];
    }

    return result;
  }
```

i = 2 and j = 3
Assign list[i] to result[j]



Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Trace the Reverse Method (11 of 22)


```
int[] list1 = {1, 2, 3, 4, 5, 6};
int[] list2 = reverse(list1);


  public static int[] reverse(int[] list) {
    int[] result = new int[list.length];

    for (int i = 0, j = result.length - 1;
         i < list.length; i++, j--) {
      result[j] = list[i];
    }

    return result;
  }
```

After this, i becomes 3 and j becomes 2



Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Trace the Reverse Method (12 of 22)


```
int[] list1 = {1, 2, 3, 4, 5, 6};
int[] list2 = reverse(list1);


  public static int[] reverse(int[] list) {
    int[] result = new int[list.length];

    for (int i = 0, j = result.length - 1;
         i < list.length; i++, j--) {
      result[j] = list[i];
    }

    return result;
  }
```

i (=3) is still less than 6



Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Trace the Reverse Method (13 of 22)


```
int[] list1 = {1, 2, 3, 4, 5, 6};
int[] list2 = reverse(list1);


  public static int[] reverse(int[] list) {
    int[] result = new int[list.length];

    for (int i = 0, j = result.length - 1;
         i < list.length; i++, j--) {
      result[j] = list[i];
    }

    return result;
  }
```

i = 3 and j = 2
Assign list[i] to result[j]



Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Trace the Reverse Method (14 of 22)


```
int[] list1 = {1, 2, 3, 4, 5, 6};
int[] list2 = reverse(list1);


  public static int[] reverse(int[] list) {
    int[] result = new int[list.length];

    for (int i = 0, j = result.length - 1;
         i < list.length; i++, j--) {
      result[j] = list[i];
    }

    return result;
  }
```

After this, i becomes 4 and j becomes 1



Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Trace the Reverse Method (15 of 22)


```
int[] list1 = {1, 2, 3, 4, 5, 6};
int[] list2 = reverse(list1);


  public static int[] reverse(int[] list) {
    int[] result = new int[list.length];

    for (int i = 0, j = result.length - 1;
         i < list.length; i++, j--) {
      result[j] = list[i];
    }

    return result;
  }
```

i (=4) is still less than 6



Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Trace the Reverse Method (16 of 22)


```
int[] list1 = {1, 2, 3, 4, 5, 6};
int[] list2 = reverse(list1);


  public static int[] reverse(int[] list) {
    int[] result = new int[list.length];

    for (int i = 0, j = result.length - 1;
         i < list.length; i++, j--) {
      result[j] = list[i];
    }

    return result;
  }
```

i = 4 and j = 1
Assign list[i] to result[j]



Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Trace the Reverse Method (17 of 22)


```
int[] list1 = {1, 2, 3, 4, 5, 6};
int[] list2 = reverse(list1);


  public static int[] reverse(int[] list) {
    int[] result = new int[list.length];

    for (int i = 0, j = result.length - 1;
         i < list.length; i++, j--) {
      result[j] = list[i];
    }

    return result;
  }
```

After this, i becomes 5 and j becomes 0



Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Trace the Reverse Method (18 of 22)


```
int[] list1 = {1, 2, 3, 4, 5, 6};
int[] list2 = reverse(list1);


  public static int[] reverse(int[] list) {
    int[] result = new int[list.length];

    for (int i = 0, j = result.length - 1;
         i < list.length; i++, j--) {
      result[j] = list[i];
    }

    return result;
  }
```

i (=5) is still less than 6



Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Trace the Reverse Method (19 of 22)


```
int[] list1 = {1, 2, 3, 4, 5, 6};
int[] list2 = reverse(list1);


  public static int[] reverse(int[] list) {
    int[] result = new int[list.length];

    for (int i = 0, j = result.length - 1;
         i < list.length; i++, j--) {
      result[j] = list[i];
    }

    return result;
  }
```

i = 5 and j = 0
Assign list[i] to result[j]



Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Trace the Reverse Method (20 of 22)


```
int[] list1 = {1, 2, 3, 4, 5, 6};
int[] list2 = reverse(list1);


  public static int[] reverse(int[] list) {
    int[] result = new int[list.length];

    for (int i = 0, j = result.length - 1;
         i < list.length; i++, j--) {
      result[j] = list[i];
    }

    return result;
  }
```

After this, i becomes 6 and j becomes -1



Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Trace the Reverse Method (21 of 22)


```
int[] list1 = {1, 2, 3, 4, 5, 6};
int[] list2 = reverse(list1);


  public static int[] reverse(int[] list) {
    int[] result = new int[list.length];

    for (int i = 0, j = result.length - 1;
         i < list.length; i++, j--) {
      result[j] = list[i];
    }

    return result;
  }
```

i (=6) < 6 is false. So exit the loop.



Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Trace the Reverse Method (22 of 22)


```
int[] list1 = {1, 2, 3, 4, 5, 6};
int[] list2 = reverse(list1);

  public static int[] reverse(int[] list) {
    int[] result = new int[list.length];

    for (int i = 0, j = result.length - 1;
         i < list.length; i++, j--) {
      result[j] = list[i];
    }

    return result;
  }
```

Return result




Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Problem: Counting Occurrence of Each Letter

- Generate 100 lowercase letters randomly and assign to an array of characters.
- Count the occurrence of each letter in the array.



CountLettersInArray

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Variable-Length Arguments

You can pass a variable number of arguments of the same type to a method.

VarArgsDemo


Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Searching Arrays

Searching is the process of looking for a specific element in an array; for example, discovering whether a certain score is included in a list of scores. Searching is a common task in computer programming. There are many algorithms and data structures devoted to searching. In this section, two commonly used approaches are discussed, **`linear search`** and **binary search.**

```
public class LinearSearch {
  /** The method for finding a key in the list */
  public static int linearSearch(int[] list, int key) {
    for (int i = 0; i < list.length; i++)
      if (key == list[i])
        return i;
    return -1;
  }
}
```



Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Linear Search

The linear search approach compares the key element, **`key`, sequentially** with each element in the array **`list`**. The method continues to do so until the key matches an element in the list or the list is exhausted without a match being found. If a match is made, the linear search returns the index of the element in the array that matches the key.

If no match is found, the search returns **–1.**

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Linear Search Animation (1 of 2)



Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Linear Search Animation (2 of 2)

https://liveexample.pearsoncmg.com/dsanimation/LinearSearcheBook.html

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

From Idea to Solution (1 of 6)

```
/** The method for finding a key in the list */
public static int linearSearch(int[] list, int key) {
  for (int i = 0; i < list.length; i++)
    if (key == list[i])
      return i;
  return -1;
}
```

Trace the method

```
int[] list = {1, 4, 4, 2, 5, -3, 6, 2};
int i = linearSearch(list, 4);  // returns 1
int j = linearSearch(list, -4); // returns -1
int k = linearSearch(list, -3); // returns 5
```

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Binary Search (1 of 6)

For binary search to work, the elements in the array must already be ordered. Without loss of generality, assume that the array is in ascending order.

e.g., 2 4 7 10 11 45 50 59 60 66 69 70 79

The binary search first compares the key with the element in the middle of the array.

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Binary Search (2 of 6)


Consider the following three cases:

- If the key is less than the middle element, you only need to search the key in the first half of the array.
- If the key is equal to the middle element, the search ends with a match.
- If the key is greater than the middle element, you only need to search the key in the second half of the array.

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Binary Search (3 of 6)



Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved


Binary Search Animation

https://liveexample.pearsoncmg.com/dsanimation/BinarySearcheBook.html

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved


Binary Search (4 of 6)



Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Binary Search (5 of 6)



Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Binary Search (6 of 6)

The `binarySearch` method returns the index of the element in the list that matches the search key if it is contained in the list. Otherwise, it returns

-insertion point – 1.

The insertion point is the point at which the key would be inserted into the list.

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

From Idea to Solution (2 of 6)

```
/** Use binary search to find the key in the list */
public static int binarySearch(int[] list, int key) {
  int low = 0;
  int high = list.length - 1;

  while (high >= low) {
     int mid = (low + high) / 2;
     if (key < list[mid])
       high = mid - 1;
     else if (key == list[mid])
       return mid;
     else
       low = mid + 1;
  }

  return -1 - low;
}
```

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

The `Arrays.binarySearch` Method

Since binary search is frequently used in programming, Java provides several overloaded `binarySearch` methods for searching a key in an array of `int`, `double`, `char`, `short`, `long`, and `float` in the `java.util.Arrays` class. For example, the following code searches the keys in an array of numbers and an array of characters.

```
int[] list = {2, 4, 7, 10, 11, 45, 50, 59, 60, 66, 69, 70, 79};
System.out.println("Index is " +
  java.util.Arrays.binarySearch(list, 11));          Return is 4

char[] chars = {'a', 'c', 'g', 'x', 'y', 'z'};
System.out.println("Index is " +
  java.util.Arrays.binarySearch(chars, 't'));        Return is –4 (insertion point is
                                                     3, so return is -3-1)
```

For the `binarySearch` method to work, the array must be pre-sorted in increasing order.

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved


Sorting Arrays

Sorting, like searching, is also a common task in computer programming. Many different algorithms have been developed for sorting. This section introduces a simple, intuitive sorting algorithms: **selection sort**.

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Selection Sort

Selection sort finds the smallest number in the list and places it first. It then finds the smallest number remaining and places it second, and so on until the list contains only a single number.



Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Selection Sort Animation

https://liveexample.pearsoncmg.com/dsanimation/SelectionSortNew.html

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

From Idea to Solution (3 of 6)

```
for (int i = 0; i < list.length; i++) {
  select the smallest element in list[i..listSize-1];
  swap the smallest with list[i], if necessary;
  // list[i] is in its correct position.
  // The next iteration apply on list[i+1..listSize-1]
}
```

```
list [0] list [1] list [2] list [3] ... list [10]

list [0] list [1] list [2] list [3] ... list [10]

list [0] list [1] list [2] list [3] ... list [10]

list [0] list [1] list [2] list [3] ... list [10]

list [0] list [1] list [2] list [3] ... list [10]

                              ...

list [0] list [1] list [2] list [3] ... list [10]
```

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

From Idea to Solution (4 of 6)

```
for (int i = 0; i < listSize; i++) {
  select the smallest element in list[i..listSize-1];
  swap the smallest with list[i], if necessary;
  // list[i] is in its correct position.
  // The next iteration apply on list[i..listSize-1]
}
```

Expand

```
double currentMin = list[i];

for (int j = i+1; j < list.length; j++) {
  if (currentMin > list[j]) {
    currentMin = list[j];

  }
}
```

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

From Idea to Solution (5 of 6)

```
for (int i = 0; i < listSize; i++) {
  select the smallest element in list[i..listSize-1];
  swap the smallest with list[i], if necessary;
  // list[i] is in its correct position.
  // The next iteration apply on list[i..listSize-1]
}
```

Expand

```
double currentMin = list[i];
int currentMinIndex = i;
for (int j = i; j < list.length; j++) {
  if (currentMin > list[j]) {
    currentMin = list[j];
    currentMinIndex = j;
  }
}
```

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

From Idea to Solution (6 of 6)

```
for (int i = 0; i < listSize; i++) {
  select the smallest element in list[i..listSize-1];
  swap the smallest with list[i], if necessary;
  // list[i] is in its correct position.
  // The next iteration apply on list[i..listSize-1]
}
```

Expand

```
if (currentMinIndex != i) {
  list[currentMinIndex] = list[i];
  list[i] = currentMin;
}
```

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Wrap It in a Method

```
/** The method for sorting the numbers */
public static void selectionSort(double[] list) {
  for (int i = 0; i < list.length; i++) {
    // Find the minimum in the list[i..list.length-1]
    double currentMin = list[i];
    int currentMinIndex = i;
    for (int j = i + 1; j < list.length; j++) {
      if (currentMin > list[j]) {
        currentMin = list[j];
        currentMinIndex = j;
      }
    }

    // Swap list[i] with list[currentMinIndex] if necessary;
    if (currentMinIndex != i) {
      list[currentMinIndex] = list[i];
      list[i] = currentMin;
    }
  }
}
```

Invoke it

selectionSort(yourList)

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

The `Arrays.sort` Method

Since sorting is frequently used in programming, Java provides several overloaded sort methods for sorting an array of `int`, `double`, `char`, `short`, `long`, and `float` in the `java.util.Arrays` class. For example, the following code sorts an array of numbers and an array of characters.

```
double[] numbers = {6.0, 4.4, 1.9, 2.9, 3.4, 3.5};

java.util.Arrays.sort(numbers);

char[] chars = {'a', 'A', '4', 'F', 'D', 'P'};

java.util.Arrays.sort(chars);
```

Java 8 now provides `Arrays.parallelSort(list)` that utilizes the multicore for fast sorting.

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

The `Arrays.toString(list)` Method

The `Arrays.toString(list)` method can be used to return a string representation for the list.

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

`Main` Method Is Just a Regular Method

You can call a regular method by passing actual parameters. Can you pass arguments to **`main`**? Of course, yes. For example, the main method in class **`B`** is invoked by a method in **`A`**, as shown below:

```
public class A {
  public static void main(String[] args) {
    String[] strings = {"New York",
      "Boston", "Atlanta"};
    B.main(strings);
  }
}
```

```
class B {
  public static void main(String[] args) {
    for (int i = 0; i < args.length; i++)
      System.out.println(args[i]);
  }
}
```

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Command-Line Parameters

```
class TestMain {
 public static void main(String[] args) {
  ...
  }
}
```

```
java TestMain arg0 arg1 arg2 ... argn
```

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Processing Command-Line Parameters

In the main method, get the arguments from `args[0]`, `args[1]`, `...`, `args[n]`, which corresponds to `arg0`, `arg1`, `...`, `argn` in the command line.

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Problem: Calculator

- Objective: Write a program that will perform binary operations on integers. The program receives three parameters: an operator and two integers.

java Calculator 2 + 3

java Calculator 2 – 3

java Calculator 2 / 3

java Calculator 2.3

Calculator

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved

Copyright



This work is protected by United States copyright laws and is provided solely for the use of instructors in teaching their courses and assessing student learning. Dissemination or sale of any part of this work (including on the World Wide Web) will destroy the integrity of the work and is not permitted. The work and materials from it should never be made available to students except by instructors using the accompanying text in their classes. All recipients of this work are expected to abide by these restrictions and to honor the intended pedagogical purposes and the needs of other instructors who rely on these materials.

Pearson

Copyright © 2024 Pearson Education, Inc. All Rights Reserved