Back

Time left 1:29:42

Question 1

Not yet answered

Marked out of 5.00

Flag question

Which of the following statements about **classes and objects** in Java is **correct**?

a. Objects are used to define the structure and behavior of a class.

b. Only one object can be created from a class in Java.

c. A class is an instance of an object.

d. An object is created from a class using the new keyword.

Next page

Question 2

Not complete

Marked out of 30.00

Flag question

Write a Java program that defines a method to convert an array of temperature values from Celsius to Fahrenheit or vice versa.

The program should:

- Read **5** temperature values from the user.
- Ask the user for the conversion type as a String ("**CtoF**" or "**FtoC**"). Also sense the "Invalid conversion type."
- Use a separate method to perform the conversion and print the results (i.e. **convertAndPrint** method)

Hint: Use arrays, a `for` loop, and `if-else` statements.
Hint: Use Math.round() method to **round the converted values** to **one decimal place.**

Conversion Formulas:

- **CtoF:** Celsius to Fahrenheit: `F = C * 9/5 + 32`
- **FtoC:** Fahrenheit to Celsius: `C = (F - 32) * 5/9`

For example:

Input	Result
CtoF 0 25 30 10 15.5	Enter conversion type (CtoF or FtoC): CtoF Enter 5 temperature values: 0.0 25.0 30.0 10.0 15.5 Original: 0.0 : Converted: 32.0 Original: 25.0 : Converted: 77.0 Original: 30.0 : Converted: 86.0 Original: 10.0 : Converted: 50.0 Original: 15.5 : Converted: 59.9
FtoC 32 68 86 50 59	Enter conversion type (CtoF or FtoC): FtoC Enter 5 temperature values: 32.0 68.0 86.0 50.0 59.0 Original: 32.0 : Converted: 0.0 Original: 68.0 : Converted: 20.0 Original: 86.0 : Converted: 30.0 Original: 50.0 : Converted: 10.0 Original: 59.0 : Converted: 15.0
CF 10 20 30 40 50	Enter conversion type (CtoF or FtoC): CF Enter 5 temperature values: 10.0 20.0 30.0 40.0 50.0 Invalid conversion type.

Question 3

Not yet answered

Marked out of 5.00

Flag question

What is the default value of an instance variable of type `int` in a Java class?

- a. undefined
- b. 1
- c. null
- d. 0

Question 4

Not yet answered

Marked out of 5.00

Flag question

You can create multiple objects from the same class in Java.

- ○ True
- ○ False

Question 5

Not yet answered

Marked out of 5.00

Flag question

Which of the following correctly creates an object of a class `Car`?

- a. new Car obj = Car();
- b. Car obj = Car();
- c. class Car = new obj();
- d. Car obj = new Car();

Question 6

Not complete

Marked out of 30.00

Flag question

Create a Java class called `Student` that represents a university student. The class must follow these requirements:

✅ Properties:

- Private `String fullName`
- Private `String id`

✅ Constructor:

- A constructor that takes `String fullName` and `String id` as arguments and sets the fields.

✅ Methods:

- `public String getInitials()`
  Returns the **initials of the student** in uppercase.
  Example: `"mehmet yilmaz"` → `"MY"`
  Multiple names should use the **first letter** of each word.
- `public String getObfuscatedId()`
  Returns the student ID with all but the **last 3 characters replaced by asterisks**.
  Example: `"ABC1234567"` → `"*******567"`
- `public String getSummary()`
  Returns:

  "Name: <FULL NAME IN TITLE CASE>, Initials: <INITIALS>, ID: <OBFUSCATED ID>"

🔤 Title Case Note: Each word should start with an uppercase letter, rest lowercase.

Example: `"mehmET yilmaZ"` → `"Mehmet Yilmaz"`

Note: Do not provide any main method, just Student Class.

Hint-1: To have a clean input, and remove any number of unwanted spaces you can use the following code snippet while reading your input in your constructor:

```
String after = before.trim().replaceAll(" +", " ");
```

Hint-2: You can split any given string into individual words as follows:

```
String[] words = s.split("\\s+");
```

For example:

Test	Result

`Student s = new Student("mehmet yılmaz", "ABC1234567");`
`System.out.println(s.getInitials());`
`System.out.println(s.getObfuscatedId());`
`System.out.println(s.getSummary());`
	`MY`
	`*******567`
	`Name: Mehmet Yılmaz, Initials: MY, ID: *******567`

`Student s = new Student("fatiH sulTaN mEhmET", "QWERT89765");`
`System.out.println(s.getSummary());`
`System.out.println(s.getInitials());`
`System.out.println(s.getObfuscatedId());`
	`Name: Fatih Sultan Mehmet, Initials: FSM, ID: *******765`
	`FSM`
	`*******765`

Answer: (penalty regime: 0 %)

Reset answer

```
public class Student {
    // your code here - do NOT provie any main method!
}
```

Question 7

Not yet answered

Marked out of 10.00

Flag question

What will the following code print?

```
class Animal {
    String type;

    void setType(String t) {
        type = t;
    }

    void printType() {
        System.out.println("Type: " + type);
    }
}

public class Test {
    public static void main(String[] args) {
        Animal a = new Animal();
        a.setType("Dog");
        a.printType();
    }
}
```

- a. Compilation Error
- b. Type: Dog
- c. Dog
- d. Type: null

Question 8

Not yet answered

Marked out of 10.00

Flag question

Consider the following Java code:

```
public class Book {
    String title;
    int pages;

    // Constructor
    public Book(String t, int p) {
        title = t;
        pages = p;
    }

    public void display() {
        System.out.println("Title: " + title + ", Pages: " + pages);
    }

    public static void main(String[] args) {
        Book b1 = new Book("Java Basics", 250);
        b1.display();
    }
}
```

What will be the output of this program?

- a. Compilation Error: Constructor must be defined with return type
- b. Title: null, Pages: 0
- c. Java Basics
  250
- d. Title: Java Basics, Pages: 250