SYRIAN PRIVATE UNIVERSITY

Faculty of Dentistry

SPU Dental Clinic System

System Design Document

Prepared by Hamza Almawla, Zeannab Alhommsi

Date Oct 26, 2026

Status Draft for review

Table of Contents

1. Design overview and goals 1
2. System architecture 1
3. Technology stack 2
    Backend and dashboard 2
    Mobile app 2
    Infrastructure 3
4. Repository structure 3
5. Backend modules 4
6. Database design 5
    Tables 5
7. API design 8
    Conventions 8
    Endpoints 8
8. Security and permissions 11
9. Workflow engine 12
    Transition table 12
    Notifications 13
    Scheduled jobs (Celery beat) 13
10. Mobile app design 14
    App architecture 14
    Login and role routing 14
    Working on a weak network 14
    Screens 14
    Key widgets 15
11. Web dashboard design 15
    Sidebar 16
12. Deployment, environments and CI/CD 16
    Environments 16
    Production services (docker-compose.prod.yml) 17
    CI/CD with GitHub Actions 17
13. Development conventions for Claude Code 18
14. Traceability 18

This document describes how the system is built to meet the Software Requirements Specification: one Django backend with a REST API and an Unfold dashboard, one Flutter app with three role-based interfaces, deployed with Docker on a cloud server.

1. Design overview and goals

The design keeps the system small enough to build in one month: one backend, one database, one mobile codebase. Every clinic rule lives in configuration tables rather than in code.

Design goals, in priority order

1. **Correct clinical records.** Approved records are locked and versioned, every change is audited, and permissions are checked on the server.
2. **Configurable, not coded.** Clinics, chairs, sessions, courses, steps, grading and lists are data the super admin edits (SRS section 4).
3. **Fast at the chair.** Few taps to approve, photos that upload on a weak network, and drafts that survive closing the app.
4. **Buildable by two people with Claude Code.** Standard, well-documented libraries; one way of doing each thing; conventions written down in the repository.
5. **Cheap to run.** A single cloud server with Docker is enough for the expected load (SRS NFR-02).

Key design decisions

Decision	Choice	Why
Backend shape	One Django project (a modular monolith), split into apps by domain	Simple to deploy and test; clear module boundaries without microservices overhead
Dashboard	Django Unfold on the Django admin	No separate frontend or API for admin screens; saves about two weeks
Mobile	One Flutter app; the role chooses the interface after login	One store listing, one codebase, shared widgets
Workflow	Explicit state machines in a service layer (section 9)	Rules are tested in one place and cannot be bypassed from the API or the dashboard
Configuration	Template tables (courses, steps, lists) instead of hard-coded enums	Meets the "everything dynamic" requirement
Background work	Celery workers with Redis	Push notifications, thumbnails, Excel imports and PDF exports run without blocking requests
Files	S3-compatible object storage behind signed URLs	Patient photos are never public; storage can grow without changing the server

2. System architecture

Two kinds of client reach one server. The Flutter app talks to the REST API, and the browser opens the Unfold dashboard. Both are served by the same Django process and follow the same service layer.

[embedded content: system architecture · clients, server, data, external services\]

Django handles each request and hands slow work (push messages, thumbnails, imports, PDF exports) to the Celery worker through Redis. Photos go to private object storage; the database and storage are backed up off the server every night.

3. Technology stack

All choices are mature open-source tools with good documentation, which matters when Claude Code writes most of the code. Pin exact versions in the repository when the project starts.

Backend and dashboard

Purpose	Library or tool
Language and framework	Python 3.12, Django 5.2 (LTS)
REST API	Django REST Framework
Authentication	djangorestframework-simplejwt (access and refresh tokens)
API documentation	drf-spectacular (OpenAPI schema and Swagger UI)
Filtering and search	django-filter
Dashboard	django-unfold (on the Django admin)
Excel import and export	django-import-export, openpyxl
Change history and versions	django-simple-history
File storage	django-storages with boto3 (S3-compatible), Pillow for thumbnails
Background jobs	Celery with Redis as the broker; django-celery-beat for scheduled jobs (round reminders, backups)
PDF generation	WeasyPrint (HTML templates to PDF, supports Arabic right to left)
Push notifications	firebase-admin (FCM for Android, and APNs for iOS through FCM)
Database	PostgreSQL 16
Tests	pytest, pytest-django, factory-boy
Code quality	ruff (lint and format), mypy (optional)
Error tracking	Sentry (free tier)

Mobile app

Purpose	Package
Framework	Flutter (stable channel), Dart 3
State management	flutter_riverpod
Navigation	go_router (routes guarded by role)
HTTP	dio, with an interceptor that refreshes tokens
Models	freezed, json_serializable
Secure token storage	flutter_secure_storage
Local storage (drafts, upload queue)	drift (SQLite)

Purpose	Package
Photos	image_picker, flutter_image_compress
Push	firebase_messaging, flutter_local_notifications
Arabic and English	flutter_localizations, intl (ARB files)
Connectivity	connectivity_plus
Tests	flutter_test, mocktail

Infrastructure

Purpose	Tool
Containers	Docker, Docker Compose
Web server and TLS	Nginx with Let's Encrypt certificates
App server	Gunicorn
Object storage	MinIO on the same server, or the cloud provider's S3-compatible storage
Code hosting and CI/CD	GitHub, GitHub Actions
App builds	Flutter build in CI; uploaded to TestFlight and the Google Play internal track

4. Repository structure

One Git repository holds the backend, the mobile app, the deployment files and the documents, so one Claude Code session can see the whole system.

```
spu-dental/
├── CLAUDE.md                 # conventions for Claude Code (section 13)
├── README.md
├── docs/                     # SRS, this design, API notes, decisions log
├── backend/
│   ├── manage.py
│   ├── pyproject.toml
│   ├── config/               # settings (base, dev, staging, prod), urls, celery, wsgi
│   ├── apps/
│   │   ├── core/             # base models, audit, permissions, utils
│   │   ├── accounts/
│   │   ├── setup/            # terms, departments, clinics, chairs, sessions, lookup lists
│   │   ├── academics/        # courses, templates, enrollments, supervisor scope
│   │   ├── patients/
│   │   ├── diagnosis/
│   │   ├── referrals/
│   │   ├── workcards/        # work cards, cases, steps, grading
│   │   ├── media/            # photos and X-rays
│   │   ├── scheduling/       # chair distribution, attendance
│   │   ├── maintenance/      # rounds, tickets
│   │   ├── notifications/
│   │   └── reports/
│   ├── templates/            # PDF and dashboard templates
│   ├── locale/ar/            # Arabic translations
│   └── tests/
├── mobile/
│   ├── pubspec.yaml
│   ├── lib/
│   │   ├── main.dart
```

```
│   │   ├── core/              # api client, auth, router, theme, l10n, offline queue
│   │   ├── shared/            # widgets, models used by all roles
│   │   └── features/
│   │       ├── auth/
│   │       ├── student/       # home, patients, diagnosis, work cards, logbook
│   │       ├── supervisor/    # approvals, referrals, assignment, clinic today
│   │       ├── maintenance/   # rounds, tickets, chairs
│   │       └── notifications/
│   ├── l10n/                  # app_ar.arb, app_en.arb
│   └── test/
├── deploy/
│   ├── docker-compose.yml
│   ├── docker-compose.prod.yml
│   ├── nginx/
│   └── backup/
└── .github/workflows/         # backend tests, mobile build, deploy
```

5. Backend modules

The backend is split into 13 Django apps. Each app owns its models, and other apps change those models only by calling the app's service functions, never by editing them directly.

App	Owns (models)	Main services	SRS
core	BaseModel (id, created/updated by and at, is_active), AuditLog	Audit logging, soft delete, shared permission classes, error format	SYS-02, SYS-04, SYS-10
accounts	User, Role, UserRole, DeviceToken	Login, token refresh, account lock, password change, role switch	DB-01, DB-02, ST-01, SYS-01
setup	Term, Department, Clinic, Chair, Session, CaseType, ToothCode, MedicalHistoryItem, SoftTissueSite, IndexDefinition, TreatmentType, ChecklistItem, FaultCategory, SystemSetting	Configuration CRUD, default data loaded on install	DB-04, DB-06, DB-18
academics	Course, CourseClinic, CaseRequirement, StepTemplate, GradingScheme, Enrollment, SupervisorScope	Excel import of students and enrollments, eligibility checks, supervisor scope lookup	DB-03, DB-05, DB-07
patients	Patient, PatientAssignment, PatientTransfer, DiagnosisQueueEntry	Registration with duplicate check, file number generation, assignment, transfer	DB-08–DB-11, SV-03, SV-09
diagnosis	Diagnosis, MedicalHistoryAnswer, ToothFinding, SoftTissueFinding, IndexScore, PlanItem	Draft, submit, approve, return, version	ST-05, ST-06, SV-04
referrals	Referral, ReferralItem	Create, accept, reject, assign, complete	SV-05, SV-06, SV-08, DB-13
workcards	WorkCard, Case, StepRecord	Card creation on enrollment, case creation (from referral or lab), step submit, approve, return, progress	ST-07–ST-10, SV-07

App	Owns (models)	Main services	SRS
media	MediaFile	Upload, thumbnail, signed URLs	ST-11, SYS-06
scheduling	ChairAssignment, Attendance	Auto-suggest distribution, attendance	DB-12, SV-11, ST-12
maintenance	Round, ChairCheck, Ticket, TicketEvent	Round submission, ticket workflow, chair status	MT-02–MT-08
notifications	Notification	Create in-app notification, send push, mark read	SYS-03
reports	(no tables; read-only queries)	Daily reports F6/F8/F9/F18, logbook, statistics, Excel and PDF export	DB-15, DB-16, ST-13

Layers inside each app: `models.py` holds the data, `services.py` holds the business rules and state changes, `selectors.py` holds read queries that apply permission scoping, `api/` holds the serializers, views and URLs, and `admin.py` holds the Unfold dashboard screens. Views and admin actions call services and never change models directly, so the API and the dashboard follow the same rules.

6. Database design

The database is PostgreSQL with about 50 tables. Every table inherits the common fields `id`, `created_at`, `created_by`, `updated_at`, `updated_by` and `is_active`. Clinical tables also keep a full history table via django-simple-history.

[embedded content: core ERD · 15 entities, read labels left to right or top to bottom\]

A referral becomes exactly one case on the work card of the student it is assigned to, so the patient record and the student's grades stay linked.

Tables

App	Table	Key fields	Constraints and indexes
core	AuditLog	user, action, model, object_id, changes (JSON), ip, at	Index on (model, object_id) and on at
accounts	User	username, full_name_ar, full_name_en, phone, university_id, must_change_password, failed_logins, locked_until	username unique; university_id unique when set
accounts	Role · UserRole	code (super_admin, management, supervisor, student, technician) · user, role	(user, role) unique
accounts	DeviceToken	user, platform, token, last_seen	token unique
setup	Term	name, start_date, end_date, is_current	One current term
setup	Department	name_ar, name_en, head (User)	—

App	Table	Key fields	Constraints and indexes
setup	Clinic · Chair	number, name, building, floor, type (diagnosis, treatment, lab), department · clinic, number, status (in_service, out_of_service)	Clinic number unique; (clinic, number) unique
setup	Session	clinic_type or clinic, name, start_time, end_time, order	—
setup	CaseType	name_ar, name_en, kind (clinical, lab)	—
setup	ToothCode	letter, meaning_ar, meaning_en, color, order	letter unique
setup	MedicalHistoryItem	question_ar, question_en, answer_type (yes_no, yes_no_details, text), is_alert, order	—
setup	SoftTissueSite · IndexDefinition	name, order · kind (calculus, plaque), tooth, surface (buccal, lingual), min_score, max_score	—
setup	TreatmentType	name_ar, name_en, department, case_type	—
setup	ChecklistItem · FaultCategory	name, order · name, blocks_chair	—
setup	SystemSetting	key, value (JSON)	key unique
academics	Course	code, name_ar, name_en, type (clinical, lab), department, term, students_per_chair (1–3), any_step_order	(code, term) unique
academics	CourseClinic	course, clinic	unique pair
academics	CaseRequirement	course, case_type, required_count	(course, case_type) unique
academics	GradingScheme	type (numeric, code, pass_fail), min, max, codes (JSON)	—
academics	StepTemplate	course, case_type (optional), order, name, grading_scheme, photo_required	(course, case_type, order) unique
academics	Enrollment	student, course, term	(student, course, term) unique
academics	SupervisorScope	supervisor, course (optional), clinic (optional)	At least one of course or clinic
patients	Patient	file_no, national_id, full_name, dob, sex, job, phone, address	file_no unique (generated); national_id unique when set; index on phone and name
patients	DiagnosisQueueEntry	patient, clinic, status (waiting, assigned, done), assigned_student	One waiting entry per patient
patients	PatientAssignment	patient, student, purpose (diagnosis, treatment), case (optional), active, started_at, ended_at	Index on (student, active)

App	Table	Key fields	Constraints and indexes
patients	PatientTransfer	patient, from_student, to_student, reason, by, at	—
diagnosis	Diagnosis	patient, student, supervisor, clinic, status, chief_complaint, soft_tissue_notes, xray_findings, diagnosis_text, version, submitted_at, approved_at	One diagnosis in progress per patient (partial unique index)
diagnosis	MedicalHistoryAnswer	diagnosis, item, answer, details	(diagnosis, item) unique
diagnosis	ToothFinding	diagnosis, tooth (FDI, permanent and primary), code	(diagnosis, tooth, code) unique
diagnosis	SoftTissueFinding · IndexScore	diagnosis, site, is_normal, note · diagnosis, index_definition, score	Score within the definition's range
diagnosis	PlanItem	diagnosis, treatment_type, teeth (array), department, status (planned, referred, done, cancelled), note	Index on (status, treatment_type) for the case finder
referrals	Referral	from_clinic, to_clinic, referred_by, procedure, note, status, accepted_by, assigned_student, reject_reason, sent_at, accepted_at, completed_at	Index on (to_clinic, status)
referrals	ReferralItem	referral, plan_item	A plan item in only one open referral (BR-04)
workcards	WorkCard	enrollment, card_no	enrollment unique; card_no unique per term
workcards	Case	work_card, case_type, patient, tooth, referral, exercise_no, status (open, completed, cancelled), completed_by, completed_at	referral unique when set
workcards	StepRecord	case, template, order, status, student, note, submitted_at, supervisor, grade_value, grade_code, comment, approved_at	(case, order) unique
media	MediaFile	file, thumbnail, kind (photo, xray), uploaded_by, patient, diagnosis, case, step, ticket, taken_at, is_teaching, idempotency_key	idempotency_key unique
scheduling	ChairAssignment	date, session, chair, course, student	(date, session, chair, student) unique
scheduling	Attendance	chair_assignment, present, marked_by, marked_at	chair_assignment unique
maintenance	Round · ChairCheck	clinic, date, kind (morning, afternoon), by, submitted_at · round, chair, item, ok, note	(clinic, date, kind) unique (BR-11)

App	Table	Key fields	Constraints and indexes
maintenance	Ticket	chair, category, status, is_external, description, opened_by, chair_check, resolved_by, resolution, opened_at, resolved_at	Index on (status, chair)
maintenance	TicketEvent	ticket, from_status, to_status, by, note, at	—
notifications	Notification	recipient, type, title, body, target, read_at	Index on (recipient, read_at)

7. API design

The mobile app uses one REST API under `/api/v1/`. The dashboard does not use the API; it runs inside Django. Workflow changes are explicit action endpoints (for example `/approve/`), never a free edit of a `status` field.

Conventions

- **Format:** JSON, snake_case field names, ISO 8601 dates in UTC (shown to users in Damascus time).
- **Authentication:** `Authorization: Bearer <access token>`. The access token lasts 15 minutes and the refresh token 30 days, rotated on each use.
- **Language:** `Accept-Language: ar` or `en` selects the language of error messages and lookup names.
- **Lists:** paginated with `?page=` and `?page_size=` (default 20, maximum 100), filtered with query parameters, and ordered with `?ordering=`.
- **Errors:** HTTP status plus `{"code": "step_out_of_order", "message": "…", "details": {…}}`. The codes are stable so the app can react to them.
- **Actions:** `POST /<resource>/{id}/<action>/` with a small body (for example a grade or a comment). They return the updated object.
- **Idempotency:** uploads and submissions send an `Idempotency-Key` header, so a retry from the offline queue does not create duplicates.
- **Versioning:** `/api/v1/`; breaking changes go to `/api/v2/`.

Endpoints

Area	Method and path	Who	Purpose
Auth	`POST /auth/login/`	All	Username and password → tokens, roles
Auth	`POST /auth/refresh/` · `POST /auth/logout/`	All	Refresh token; log out and revoke the token

Area	Method and path	Who	Purpose
Auth	`GET /me/` · `POST /me/password/` · `POST /me/devices/`	All	Profile and roles; change password; register a push token
Lookups	`GET /lookups/`	All	Every lookup list in one call, cached by the app (tooth codes, history items, sites, treatment types, checklist, fault categories, sessions)
Patients	`GET /patients/` · `GET /patients/{id}/`	Student (own), Supervisor (scope)	My patients; full record with alerts
Diagnosis queue	`GET /diagnosis-queue/` · `POST /diagnosis-queue/{id}/assign/`	Supervisor	Waiting patients; assign one to a student
Diagnosis	`POST /diagnoses/` · `GET` · `PATCH /diagnoses/{id}/`	Student	Create, read and edit a draft (all F1 sections in one nested body)
Diagnosis	`POST /diagnoses/{id}/submit/`	Student	Send to a supervisor
Diagnosis	`POST /diagnoses/{id}/approve/` · `/return/`	Supervisor	Approve, or return with a comment
Referrals	`POST /referrals/`	Supervisor	Refer plan items to a clinic
Referrals	`GET /referrals/?direction=in|out&status=`	Supervisor	Inbox and sent list
Referrals	`POST /referrals/{id}/accept/` · `/reject/` · `/assign/`	Supervisor	Accept, reject with a reason, assign to a student
Referrals	`GET /referrals/{id}/eligible-students/`	Supervisor	Students allowed for this referral, with their progress
Work cards	`GET /workcards/` · `GET /workcards/{id}/`	Student (own), Supervisor (scope)	Cards with progress; card detail with cases
Cases	`POST /cases/` (lab) · `GET /cases/{id}/`	Student	Create a lab case; case detail with steps

Area	Method and path	Who	Purpose
Cases	`POST /cases/{id}/complete/`	Supervisor	Confirm the case is complete (closes the referral)
Steps	`POST /steps/{id}/submit/`	Student	Mark done with a note and photo ids
Steps	`POST /steps/{id}/approve/` · `/return/`	Supervisor	Grade and approve, or return with a comment
Approvals	`GET /approvals/`	Supervisor	One queue of waiting diagnoses and steps
Transfers	`POST /patients/{id}/transfer/`	Supervisor	Move a patient and open cases to another student
Case finder	`GET /case-finder/?treatment_type=&department=`	Supervisor	Patients with approved, not yet referred plan items
Media	`POST /media/` (multipart) · `GET /media/{id}/`	Student, Supervisor, Technician	Upload a photo; get a signed link
Scheduling	`GET /schedule/?date=` · `GET /clinics/{id}/today/`	Student, Supervisor	My chairs; the clinic's chair × session grid
Scheduling	`POST /attendance/`	Supervisor	Mark attendance in bulk
Maintenance	`GET /clinics/?with=chair_status`	Technician	Clinics with chair counts
Maintenance	`POST /rounds/`	Technician	Submit a round with all chair checks
Maintenance	`POST /tickets/` · `GET /tickets/`	Technician, Supervisor	Report a fault; list tickets
Maintenance	`POST /tickets/{id}/start/` · `/external/` · `/resolve/`	Technician	Move the ticket through its states
Maintenance	`POST /chairs/{id}/status/`	Technician	Set a chair in or out of service, with a reason
Notifications	`GET /notifications/` · `POST /notifications/read/`	All	List; mark as read
Logbook	`GET /logbook/`	Student	All my cases with grades

The full request and response schemas are generated by drf-spectacular at `/api/v1/schema/` and browsable at `/api/v1/docs/`. That schema, not this table, is the contract between the backend and the app.

8. Security and permissions

Permissions are enforced in three layers on the server: the role allows the action, the scope limits the rows, and the record's state allows the change. The app only hides buttons; it is never trusted.

1. Role check (per endpoint). Each view declares the roles allowed, using DRF permission classes such as `IsStudent`, `IsSupervisor`, `IsTechnician`, `IsSuperAdmin` and `IsManagement`. Roles come from the `UserRole` table. A user with several roles sends `X-Active-Role` to pick the interface; the server checks that the user holds that role.

2. Scope check (per row). Every list and detail view reads through a selector that filters the queryset:

- **Student:** patients with an active assignment to them; their own work cards, cases and steps.
- **Supervisor:** clinics and courses in their `SupervisorScope`; diagnoses and steps submitted to those; referrals to and from those clinics.
- **Technician:** clinics, chairs, rounds and tickets; no patient data.
- **Management:** read-only, all data, dashboard only.

A record outside the user's scope returns 404, not 403, so its existence is not revealed.

3. State check (per action). The service layer refuses transitions that are not allowed from the current state (section 9). The service also enforces business rules BR-01 to BR-14, for example "a supervisor cannot approve their own work".

Authentication details

- JWT access tokens last 15 minutes and refresh tokens 30 days, rotated on each refresh. Logout blacklists the refresh token.
- 5 failed logins lock the account for 15 minutes (SYS-01). The super admin can unlock it from the dashboard.
- New accounts get a temporary password, which must be changed on first login.
- Dashboard sessions use Django's session login with CSRF protection, a 2-hour idle timeout, and access for the super admin and management roles only.

Data protection

- HTTPS only, with HSTS enabled.
- Photos are stored in a private bucket and served through signed links that expire after 10 minutes.
- The app keeps photos in its own storage until they are uploaded, then deletes them; nothing goes to the phone's gallery.
- Database and storage backups are encrypted.
- Secrets (database password, JWT key, storage keys, Firebase key) live in environment variables, never in the repository.
- Every create, change, approval, login and failed login goes to `AuditLog`. django-simple-history keeps a full copy of each version of clinical records.

- Rate limiting: login at 10 requests a minute per IP; other endpoints at 120 requests a minute per user.

9. Workflow engine

Each workflow record has a `status` field changed only by one service function per action. That function checks the guard, writes the change and its side effects in one database transaction, and queues notifications after the commit. The lifecycles are drawn in the SRS (section 6).

Pattern used by every action

1. Lock the row (`select_for_update`) and check the current status against the allowed "from" states.
2. Check the guards: role, scope and business rules. If one fails, raise a `DomainError` with a stable code.
3. Update the status and the fields, and write the history record and the audit log entry.
4. Run the side effects, such as updating the plan item, closing the referral or changing the chair status.
5. Call `transaction.on_commit` to queue notifications and push messages in Celery.

Transition table

Record	Action	From → to	Who	Guard	Side effects
Diagnosis	submit	draft, returned → submitted	Student (owner)	Required sections filled; patient assigned to the student	Notify the chosen supervisor
Diagnosis	approve	submitted → approved	Supervisor (scope, not owner)	—	Lock the record; plan items become "planned"; notify the student
Diagnosis	return	submitted → returned	Supervisor	Comment required	Notify the student
Referral	create	→ sent	Supervisor	Plan items approved and not in another open referral (BR-04)	Plan items → referred; notify the receiving clinic's supervisors
Referral	accept	sent → accepted	Supervisor of receiving clinic	—	Notify the referring supervisor
Referral	reject	sent → rejected	Supervisor of receiving clinic	Reason required	Plan items → planned again; notify the referrer
Referral	assign	accepted → assigned	Supervisor of receiving clinic	Student eligible (BR-05)	Create the Case on the student's work card with steps from the template; create the PatientAssignment; notify the student
Referral	(automatic)	assigned → in treatment	System	First step submitted	—

Record	Action	From → to	Who	Guard	Side effects
Step	submit	pending, returned → submitted	Student (case owner)	Previous step approved, unless the course allows any order (BR-06); photo present if the template requires one	Notify the supervisors in scope
Step	approve	submitted → approved	Supervisor (scope, not owner)	Grade valid for the course's grading scheme	Lock the step; notify the student
Step	return	submitted → returned	Supervisor	Comment required	Notify the student
Case	complete	open → completed	Supervisor	All steps approved	Referral → completed; plan item → done; work card progress +1; notify the referring clinic (BR-08)
Ticket	open	→ open	Technician, Supervisor, System (failed check)	—	If the category blocks the chair: chair → out of service; notify the technicians
Ticket	start	open → in progress	Technician	—	—
Ticket	external	in progress → external repair	Technician	Note required	—
Ticket	resolve	in progress, external repair → resolved	Technician	Repair note required	Chair → in service if no other blocking ticket; notify whoever reported it

Notifications

One `Notification` row per recipient and event holds the type, a title and body in the recipient's language, a link to the target (for example `case:123`), and a read time. A Celery task sends the push message. If push fails, the row stays and the app shows it in the list (SYS-03).

Scheduled jobs (Celery beat)

Job	When	What
Round reminder	9:30 and 15:00	Notify technicians of clinics with no round submitted (MT-09)
Stale referral alert	Daily 8:00	Notify the receiving supervisors of referrals waiting more than 3 days (configurable)
Clean expired tokens	Nightly	Remove blacklisted tokens
Backup	Nightly 2:00	Dump the database and copy storage to the backup location

10. Mobile app design

One Flutter app opens one of three interfaces after login. Each interface is a separate feature folder with its own bottom navigation, and all three share the API client, the offline queue, the theme and the common widgets.

App architecture

- **Presentation:** screens and widgets. They read state from Riverpod providers and never call the API directly.
- **State:** Riverpod providers and notifiers, one per screen or feature, which expose loading, data and error states.
- **Data:** repositories per resource (for example `CaseRepository`). They call the API through dio and map JSON to freezed models.
- **Local:** a drift (SQLite) database with three tables: diagnosis drafts, the upload queue and the cached lookups.
- **Core:** the dio client with a token refresh interceptor, go_router with role guards, the theme (Arabic font, right-to-left), localization, error mapping from API codes to messages, and the connectivity watcher.

Login and role routing

1. Log in, and receive tokens and roles. Tokens are stored in secure storage.
2. A first login forces a password change.
3. A user with one role goes straight to its home. A user with several roles picks one, and can switch later from the profile.
4. go_router guards the role prefixes `/student/…`, `/supervisor/…` and `/maintenance/….` A wrong role is sent back to its own home.

Working on a weak network

- **Drafts:** the diagnosis form saves to local storage on every change and syncs to the server draft when online.
- **Uploads:** each photo is compressed to at most 2 MB and put in the upload queue with an idempotency key. A background worker sends it, and retries with back-off.
- **Submissions:** a step is sent for approval only after all its photos have uploaded. Until then the screen shows "waiting to upload".
- **Lookups:** cached and refreshed at most once a day, or when the server's version number changes.

Screens

Interface	Bottom tabs	Screens

Interface	Bottom tabs	Screens
Student	Home · Patients · Work cards · Notifications · Profile	Home (today's clinic, chair and sessions; returned items; waiting items) · My patients · Patient record (alerts banner, diagnoses, plan, referrals, photos) · Diagnosis wizard: 1 Complaint, 2 Medical history, 3 Dental chart, 4 Soft tissue, 5 Indices, 6 X-rays, 7 Diagnosis and plan, 8 Review and submit · Work cards list · Work card (progress per case type) · Case (steps) · Step submit (note, camera, gallery) · New lab case · My schedule · Logbook
Supervisor	Approvals · Referrals · Clinic today · Notifications · Profile	Home and approvals queue (diagnoses and steps, filter by clinic) · Diagnosis review (all sections read-only, approve or return) · Step review (photos full screen, grade input by scheme, approve or return) · Create referral (select plan items, clinic, note) · Referral inbox and sent list · Assign student (eligible list with progress) · Diagnosis queue · Transfer patient · Case finder · Clinic today (chair × session grid, attendance) · Student progress · Report fault
Maintenance	Clinics · Tickets · Notifications · Profile	Clinics list (chairs in and out of service) · Round (morning or afternoon; one row per chair; "all OK"; fault entry with photo) · Ticket list (open, by age) · Ticket detail (start, external, resolve, notes, photos) · Chair detail (status, history, set in or out of service)

Key widgets

- **Dental chart:** a 4 × 8 grid in FDI order (18→11 | 21→28 on top, 48→41 | 31→38 below). Tapping a tooth opens a sheet of code chips, multi-select. The colours and letters come from the lookup.
- **Soft tissue map:** a list of sites with a normal or finding toggle and a note field. The oral illustration from F1 is shown as a reference image.
- **Index entry:** the six configured teeth and surfaces, each with a 0–3 segmented control, and the computed index shown live.
- **Grade input:** built from the course's grading scheme as a number pad, a code chip list or a pass / fail toggle.
- **Patient alert banner:** a red banner listing the alert items, shown on every patient screen.

Detailed wireframes for these screens are a separate deliverable of the design phase.

11. Web dashboard design

The dashboard is the Django admin styled with Unfold, at `/dashboard/`. Standard admin pages cover the setup screens. A few custom Unfold pages cover the boards and reports, and all of them call the same services as the API.

Sidebar

Group	Items	Type
Home	Key figures: patients, open referrals, approvals waiting, chairs out of service	Custom page with Unfold cards and charts
Patients	Patients (register, search, edit, history) · Diagnosis queue	Admin with inlines; "Send to diagnosis clinic" action
Clinical	Referral board · Diagnoses (read-only) · Work cards and cases (read-only)	Custom board; read-only admin
Scheduling	Chair distribution planner · Attendance	Custom page: chair × session grid with auto-suggest
Maintenance	Chair status board · Tickets · Rounds	Custom board; admin with filters
Academic setup	Terms · Courses (inlines: case requirements, step templates, clinics, supervisors) · Grading schemes · Enrollments · Import students (Excel)	Admin with inlines; import-export
Facilities	Departments · Clinics (inline chairs) · Sessions	Admin with inlines
Lists	Tooth codes · Medical history items · Soft tissue sites · Index definitions · Treatment types · Checklist items · Fault categories	Admin with sortable order
Reports	Daily clinic (F8) · Daily lab (F9) · Chair status (F6/F18) · Student logbook · Course progress · Pending treatments · Referral and maintenance statistics	Custom pages with filters; Excel and PDF export
Users	Users · Roles · Audit log	Admin; audit log read-only
Settings	System settings	Single-record admin

Management role: the same sidebar without the setup, users and settings groups. Every admin is read-only for this role, enforced by `has_change_permission` returning false.

Arabic layout: Django's `LANGUAGES` setting with Arabic as the default, and `dir="rtl"` on the dashboard's base template. RTL support in Unfold is checked in week 1, and the fallback is Flutter Web (Project Plan, risks).

12. Deployment, environments and CI/CD

The whole backend runs as Docker Compose services on one cloud Linux server. A server with 4 vCPU, 8 GB RAM and about 200 GB of disk covers the expected load and several years of photos; storage can move to managed S3 later without code changes.

Environments

Environment	Where	Purpose	Data
Development	Each developer's laptop (Docker Compose)	Building and unit tests	Seed data from a fixture script

Environment	Where	Purpose	Data
Staging	Same cloud server, separate containers and database, `staging.<domain>`	Thursday demos, store review builds, user acceptance test	Realistic fake patients; never real data
Production	Cloud server, `dental.<spu domain>`	Live use	Real data, backed up nightly

Production services (docker-compose.prod.yml)

Service	Image	Role
nginx	nginx	HTTPS (Let's Encrypt), static files, upload size limit, proxy to the web container
web	backend image	Gunicorn running Django: the API and the dashboard
worker	backend image	Celery worker: push, thumbnails, imports, PDF and Excel exports
beat	backend image	Celery beat: scheduled jobs (section 9)
db	postgres:16	Database, on a persistent volume
redis	redis	Celery broker and cache
minio	minio	Photo storage, on a persistent volume (or the provider's S3)
backup	small cron image	Nightly encrypted database dump and storage copy to off-server storage, kept 30 days

CI/CD with GitHub Actions

Workflow	Trigger	Steps
backend-ci	Every pull request	Lint with ruff; run pytest against a PostgreSQL service; check that migrations are complete; check that the OpenAPI schema builds
mobile-ci	Every pull request touching `mobile/`	flutter analyze; flutter test
deploy-staging	Merge to `main`	Build and push the backend image; SSH to the server; `docker compose pull && up -d`; run migrations
deploy-production	Tag `v*`	Same as staging, against production, after manual approval
mobile-release	Tag `app-v*`	Build the Android App Bundle and the iOS archive; upload to the Google Play internal track and TestFlight

Monitoring: Sentry for backend and app errors, a free uptime check on `/health/`, and a disk-space alert at 80%.

Store publishing: developer accounts held outside Syria (Project Plan). Reviewers get demo logins for each role on staging data. A privacy policy page is served at `/privacy/`.

13. Development conventions for Claude Code

These rules go into `CLAUDE.md` at the root of the repository, so every Claude Code session follows the same structure. Each build prompt names the user stories (US-xx) and requirement IDs it implements.

Backend rules

- Every model inherits `core.BaseModel`. Records are never hard-deleted; use `is_active=False`.
- Business rules and status changes live only in `services.py`. Views, serializers and admin actions call services.
- Reads that depend on the user go through `selectors.py`, which applies the scope filter (section 8).
- Errors: raise `DomainError(code, message)`; one exception handler turns it into the API error format.
- Every user-facing string is wrapped in `gettext`, with Arabic in `locale/ar`.
- Every service function gets pytest tests for the allowed path, each guard failure, and the permission scope.
- Migrations are committed. Migrations are never edited after they are merged.

Mobile rules

- Feature-first folders (`features/<role>/<feature>/`), each with `data/`, `state/` and `ui/`.
- No API calls in widgets; widgets read Riverpod providers only.
- Every text comes from the ARB files in Arabic and English. No hard-coded strings.
- Use `EdgeInsetsDirectional` and `AlignmentDirectional` everywhere, so right-to-left layout works.
- API error codes are mapped to localized messages in one place.
- After changing the API, regenerate the models from the OpenAPI schema or update the freezed models to match it.

Process rules

- One branch and one pull request per user story. The pull request description lists the US and requirement IDs and how they were tested.
- Before merging, a developer reviews the diff, runs it on staging, and checks it in Arabic.
- `docs/decisions.md` records every decision that changes this design, with its date and reason.

Prompt template for a story

```
Implement US-07 (SV-07, SYS-03) from docs/SRS.md.
Scope: backend workcards app (approve/return step services + API) and
mobile supervisor feature (approval queue, step review screen).
Follow CLAUDE.md. Acceptance criteria: <paste from SRS>.
Add tests for each criterion. Do not change other apps' models.
```

14. Traceability

Every SRS requirement maps to at least one backend app and one interface. The user stories in the SRS link each sprint to these modules.

SRS requirements	Backend app(s)	Interface	Sprint

SRS requirements	Backend app(s)	Interface	Sprint
DB-01, DB-02, ST-01, SV-01, MT-01, SYS-01, SYS-02	accounts, core	All	S1
DB-03, DB-05, DB-07	academics	Dashboard	S1
DB-04, DB-06, DB-18, SYS-07, SYS-09, SYS-10	setup, core	Dashboard	S1
ST-07–ST-11, SV-07, SYS-06	workcards, media	Student, Supervisor	S2
DB-08–DB-11, ST-03, ST-04, SV-03	patients	Dashboard, Student, Supervisor	S3
ST-05, ST-06, SV-04, SYS-05	diagnosis	Student, Supervisor	S3
SV-05, SV-06, SV-08, DB-13	referrals, workcards	Supervisor, Dashboard	S3–S4
SV-09, SV-10	patients, diagnosis	Supervisor	S4
DB-12, SV-11, ST-12	scheduling	Dashboard, Supervisor, Student	S4
MT-02–MT-08, SV-13, DB-14	maintenance	Maintenance, Supervisor, Dashboard	S4
SYS-03, ST-14, SV-14, MT-09	notifications	All	S5
DB-15, DB-16, DB-17, ST-13, SV-12, SYS-08	reports, core	Dashboard, Student, Supervisor	S5
SYS-04	core (AuditLog, simple-history)	Dashboard	S1