

ACIP

Activity 2: Automatic CP extraction with Matlab feature functions

Anna, Kimia, Hamza

April 2024

Introduction

In this study, we explore the Scale-Invariant Feature Transform (SIFT) and Binary Robust Invariant Scalable Keypoints (BRISK) to determine their robustness against image transformations. SIFT [1] offers scale and rotation invariance. BRISK [2] provides a computationally efficient alternative with scale and rotation invariance capabilities. This report will demonstrate these feature detectors' suitability for real-world applications by comparing their performance on an original image and its transformation.

1 Methodology

1.1 Image Acquisition and Feature Extraction

The image of a coin with its rich textural features and distinct edges and contours provides a challenging, but interpretable set of keypoints for detection algorithms. SIFT begins by detecting keypoints through the Difference of Gaussians (DoG) approach, isolating potential points of interest that remain consistent across scales. It refines these points through localization, orientation assignment, and ultimately describes each keypoint using a 128-dimension descriptor, capturing local gradients across subregions. BRISK, a faster alternative, is efficient in binary descriptor computation and invariant to rotations.

1.2 Image Transformation

In the first activity, we applied horizontal shearing and rigid transformations to an image. With horizontal shearing, we tilt the image horizontally, without any vertical displacement or scaling. With rigid transformations, we perform a combination of rotation and translation but maintain the distances between points.

1.3 Feature Extraction from Transformed Images

Applying the same feature extraction methods to transformed images tests the hypothesis that the selected features are invariant to the applied transformations. A successful feature extraction method would detect a similar distribution of keypoints in both the original and transformed images, despite any distortion or movement.

1.4 SIFT

The Scale-Invariant Feature Transform (SIFT) is a technique introduced by David G. Lowe that detects and describes local features in images. The method is designed to be robust against changes in image scale, rotation, and illumination, as well as changes in 3D viewpoint.

SIFT starts by searching for the 3D scale-space extrema in the image using a Difference of Gaussians (DoG) function, which involves subtracting one blurred version of an original image from another, less blurred version of the image. This step identifies potential interest points that are invariant to scale. This scanning and detection process can be sensitive to noise; therefore, it is followed by an interpolation that refines the localization of the extrema, and by filtering to discard unreliable detections. At this point, each keypoint has x, y which are the position of the keypoint and a scale in which the keypoint was found.

Then, we have the orientation assignment. Apart from the scale for each keypoint, SIFT also calculates the main orientation; This is done by taking a square window around the detected feature in the corresponding scale, computing edge orientation or gradient direction for each pixel, creating a weighted direction histogram made of 36 bins (10 degrees per pixel, and the weights are the gradient magnitude), and taking the peak in the histogram as the dominant direction. In the end, each keypoint is made of x, y , scale, and orientation.

Apart from a detector, SIFT is also a descriptor which is considered as one of its strengths. For each keypoint (x, y , scale, orientation) a normalized patch will be used; after undoing the effect of rotation and scaling (orientation and scale invariance). The patch is divided into 16×16 regions (4×4 grid of cells). An 8-bin weighted orientation histogram is calculated for each cell, which will give us the final descriptor: $16 \text{ cells} \times 8 \text{ orientations}$: 128 dimension descriptor.

1.5 BRISK

BRISK, short for Binary Robust Invariant Scalable Keypoints, is a feature point detection and description algorithm with scale invariance and rotation invariance, developed in 2011. The BRISK algorithm is designed to be a fast and efficient alternative to other feature detectors and descriptors like SIFT and SURF, with particular emphasis on providing robust performance in real-time applications. BRISK is both a detector and a descriptor; it not only identifies points of interest in an image but also describes the regions around these points in a way that is useful for matching keypoints between different images. Compared with the traditional algorithms, the matching speed of BRISK is faster and the storage memory is lower.

Similar to SIFT, BRISK starts by generating a scale-space representation of the image. At each scale level, the algorithm performs a FAST (Features from Accelerated Segment Test) corner detection and uses the FAST detector score s . It checks for corners by examining a circle of 16 pixels around each candidate pixel and ensures that there are at least 9 contiguous pixels in the circle that are either all darker or all lighter than the central pixel by a certain intensity threshold. These corners are candidates for keypoints. After that, non-maxima suppression is performed on each octave and layers between in a way that the s score is maximal within 3×3 neighborhood.

Next, using the points obtained from the previous section, a 2D quadratic function is fit to the 3×3 neighbor of each point, and subpixel maxima are determined (through all the layers). These maxima are later interpolated across scale space, and the local maxima is chosen as the scale that the feature was found in. BRISK generates a descriptor based on a unique sampling pattern that consists of pairs of points at various distances around each keypoint, separating the pairs of pixels into subsets of short-distance and long-distance pairs. Each point in the sampling pattern is smoothed using a Gaussian filter. The standard deviation of the filter is proportional to the distance from the center to avoid aliasing effects in the sampled intensities. Then, for each pair of sampling points, the local gradient is calculated based on the smoothed intensity values. This involves determining the difference in intensities and normalizing by the distance between the points.

BRISK calculates an overall direction for the keypoint using long-distance pairs from the set of all point pairs. This direction is found by averaging the gradients from these pairs, effectively determining a dominant gradient direction which helps in achieving rotation invariance.

The keypoint's sampling pattern is also rotated by an angle, which is derived from the calculated gradient. This is crucial for ensuring that the descriptor is rotation invariant. Finally, a binary string is constructed by performing brightness comparisons between short-distance pairs in the rotated pattern. For each pair, the intensity comparison results in either 0 or 1; if the intensity at the first point of the pair is greater than the second, the result is 1; otherwise, it is 0. This binary string forms the descriptor. BRISK effectively generates invariant descriptors to scale and orientation while maintaining a high degree of distinctiveness and computational efficiency, making it suitable for real-time applications.

2 Results

2.1 Feature Detection in Original and Transformed Images with SIFT

Original image with CP extracted by Matlab implemented feature





Figure 1: Original image with CP extracted by SIFT feature


The SIFT features were analyzed for both the original and transformed images, with the results depicted in Figures 1 and 2. Upon examination, we observe that, following horizontal shearing, the CPs largely correspond between the two images, with only minor discrepancies. This suggests a robustness of the SIFT features to the applied shearing transformation. Contrastingly, the CPs from the image subjected to a rigid transformation demonstrate a significant deviation from those in the original image, indicating a reduced stability of the SIFT features under such conditions.

Transformed image with CP extracted by Matlab implemented feature



(a)

Transformed image with CP extracted by Matlab implemented feature




(b)

Figure 2: (a) Transformed image with CP extracted by SIFT feature; (b) Transformed image with CP by SIFT feature

2.2 Feature Detection in Original and Transformed Images with BRISK


In our experiment with the BRISK feature detection method, the results depicted in Figure 3 show significant differences between the CPs in the original image and those in the rigidly transformed image. We specifically utilized the BRISK method for rigid transformations, leveraging its design for handling scale and rotation changes. Notably, the method accurately detected keypoints around distinctive letters like E, C, and N, and on the intricate patterns of the coin in both the original and transformed images. However, it struggled with keypoints around the outer border of the coin, particularly in the transformed image. This discrepancy suggests that while BRISK effectively captures features in areas with high pattern density, it may be less reliable around less structured, peripheral regions. These observations indicate that further investigation is needed to determine when and how the BRISK method is most effective.

Original image with CP extracted by Matlab implemented feature



(a)

Transformed image with CP extracted by Matlab implemented feature



(b)

Figure 3: (a) Original image with CP extracted by BRISK feature; (b) Transformed image with CP by BRISK feature

3 Conclusions

3.1 Robustness of SIFT and BRISK

SIFT, with its robust design against scale changes and rotations, generally performed well under horizontal shearing. This performance aligns with its method of detecting keypoints through a scale-space extrema search, optimized for such invariance. However, under rigid transformations, SIFT showed some limitations, highlighting areas for potential enhancement.

At the same time, BRISK, known for its quick binary descriptor system and also designed to be invariant to scale and rotation, faced challenges under rigid transformations. Although it performed well in regions with dense patterns and distinct features, such as letters and intricate coin patterns, its reliability diminished around the outer edges of the coin. These findings underscore the need for further testing and potential refinement of BRISK's approach to ensure consistent performance across different image areas and transformation types.

3.2 Comparison of Feature Detection Methods

The analysis reveals that SIFT's detailed, though computationally demanding, approach provides robustness in scenarios where BRISK, with its emphasis on speed and efficiency, may not suffice. While SIFT is better suited for applications that demand high accuracy regardless of computational cost, BRISK could be preferred in scenarios where quick processing is crucial, albeit at the risk of inconsistencies in less structured areas.

References

- [1] Lowe D. G., "Distinctive image features from scale-invariant keypoints," in International journal of computer vision, 60, 91-110., 2004.
- [2] Leutenegger, S., Chli, M., Siegwart, R. Y., "BRISK: Binary robust invariant scalable keypoints," in International conference on computer vision, pp. 2548-2555, IEEE, 2011.