



F 200/300 Series

PRODUCT NAME

F 200/300 Series Four-Bolt Flange Bearing Unit

Purpose of Product

This unit is designed to support a rotating shaft while being mounted to a flat surface (such as a wall or machine frame). The four-bolt flange design provides stable positioning and is commonly used in applications where the shaft passes through a surface and requires secure, aligned support.

Key Features

- Four-bolt square flange for strong and stable mounting
- Self-aligning insert bearing to compensate for shaft misalignment
- Durable cast housing for high strength and long service life
- Pre-lubricated bearing with provision for re-greasing
- Integrated locking mechanism (set screws or eccentric collar)
- Sealed bearing to protect against dust, dirt, and moisture
- Easy installation and replacement

Detailed Specifications *(varies by exact size within the series)*

- **Series:** F 200 / F 300
- **Housing Material:** Cast iron or ductile iron
- **Bearing Type:** Insert ball bearing (self-aligning)
- **Mounting Type:** Four-bolt square flange
- **Shaft Diameter Range:** Typically ~20 mm to 60+ mm (depending on model)
- **Bolt Hole Configuration:** Four equally spaced mounting holes
- **Sealing:** Contact rubber seals and/or metal shields
- **Lubrication:** Grease lubricated with grease fitting (zerk)
- **Operating Temperature Range:** Approx. -20°C to +120°C
- **Locking Mechanism:** Set screw locking or eccentric locking collar
- **Surface Finish:** Corrosion-resistant coating (often painted or zinc-treated)
- **Applications:** Conveyors, agricultural machinery, fans, pumps, and general industrial equipment