



# FL 200/300 Series

## PRODUCT NAME

FL 200/300 Series Flange Bearing Unit (Two-Bolt Flange Unit)

## Purpose of Product

This bearing unit is designed to support rotating shafts where the mounting surface is perpendicular to the shaft axis. It is commonly used in applications requiring compact, face-mounted bearing support, such as conveyors, agricultural equipment, and light-to-medium industrial machinery.

## Key Features

- Oval-shaped, two-bolt flange design for secure face mounting
- Integrated insert bearing for easy installation and replacement
- Compact structure ideal for space-constrained setups
- Set screw locking or eccentric locking collar options
- Durable cast housing for strength and vibration resistance
- Pre-lubricated with provision for re-lubrication
- Good alignment capability and smooth operation

## Detailed Specifications

- **Series:** FL 200 / FL 300
- **Housing Material:** Cast iron (standard), optional ductile iron
- **Bearing Type:** UC series insert bearing
- **Mounting Type:** Two-bolt flange (oval)
- **Shaft Diameter Range:** Typically ~12 mm to ~100 mm (varies by model, e.g., FL204–FL320)
- **Locking Mechanism:** Set screw locking or eccentric collar
- **Lubrication:** Grease fitting (nipple) for maintenance
- **Sealing:** Rubber seals or metal shields depending on bearing insert
- **Operating Temperature:** Approx. -20°C to +120°C (depends on lubrication and bearing type)
- **Surface Finish:** Painted or anti-corrosion coated
- **Applications:** Conveyors, fans, food machinery, textile machines, and agricultural equipment