



PB 200/300 Series

PRODUCT NAME

PB 200/300 Series Pillow Block Bearing Unit

Purpose of Product

This product is used to **support rotating shafts** in machinery while allowing smooth and low-friction motion. It is typically mounted onto a flat surface and helps keep the shaft properly aligned, reducing wear and extending equipment life.

Key Features

- **Pre-assembled unit** (housing + bearing) for easy installation
- **Self-aligning bearing design** to compensate for minor misalignment
- **Durable cast housing** for strength and vibration resistance
- **Grease fitting (zerk)** for easy lubrication and maintenance
- **Set screw locking mechanism** to secure the shaft
- **Corrosion-resistant finish** for longer service life
- **Multiple mounting holes** for stable and secure installation

Detailed Specifications (*typical for PB 200/300 Series — may vary by model*)

- **Bearing Type:** Insert ball bearing
- **Housing Type:** Pillow block (2-bolt flange style base)
- **Material (Housing):** Cast iron or ductile iron
- **Material (Bearing):** High-carbon chromium steel
- **Shaft Diameter Range:** Typically 12 mm to 75 mm (varies by model)
- **Mounting Bolt Holes:** 2-hole configuration
- **Lubrication:** Grease lubricated with relubrication fitting
- **Sealing:** Double-sealed to prevent dust and contaminants
- **Operating Temperature Range:** Approx. -20°C to +120°C
- **Load Capacity:** Depends on specific bearing size (light to medium duty applications)
- **Locking Method:** Set screw locking or eccentric collar (depending on variant)