



## PH 200/300 Series

### PRODUCT NAME

PH 200/300 Series Hanger Bearing Unit

### Purpose of Product

This bearing unit is designed to support rotating shafts in **suspended (hanging) applications**, typically mounted from above. It is commonly used in conveyor systems, especially screw conveyors, where the shaft needs mid-span support without a base underneath.

### Key Features

- Hanger-style housing for overhead/suspended mounting
- Self-aligning insert bearing to handle shaft misalignment
- Strong cast housing for durability under continuous loads
- Compact design suitable for tight or enclosed spaces
- Pre-lubricated bearing with provision for relubrication
- Sealed unit to protect from dust and contaminants
- Easy installation and maintenance

**Detailed Specifications** (*varies by model within the series*)

- **Series:** PH 200 / PH 300
- **Housing Material:** Cast iron or ductile iron
- **Bearing Type:** Insert ball bearing (self-aligning)
- **Mounting Type:** Hanger / suspended mount (top support)
- **Shaft Diameter Range:** Typically ~20 mm to 60+ mm
- **Locking Mechanism:** Set screw or eccentric locking collar
- **Sealing:** Rubber contact seals and/or metal shields
- **Lubrication:** Grease lubricated with grease fitting (zerk)
- **Operating Temperature Range:** Approx. -20°C to +120°C
- **Load Direction:** Primarily radial loads, moderate axial support
- **Surface Finish:** Painted or corrosion-resistant coating (often green)
- **Typical Applications:** Screw conveyors, overhead conveyors, grain handling systems, and material processing equipment