



T 200/300 Series

PRODUCT NAME

T 200 / 300 Series Bearing Housing

(Also referred to as **Plummer Block / Pillow Block Housing – T-Type or Take-Up Housing**, depending on manufacturer)

Purpose of Product

The **T 200/300 series bearing housing** is designed to:

- Support rotating shafts with mounted bearings
- Maintain proper shaft alignment
- Reduce friction and vibration during operation
- Protect bearings from contaminants (dust, moisture, debris)
- Handle **moderate to heavy radial and axial loads**

These housings are commonly used in:

- Conveyors
- Mining equipment
- Industrial fans and pumps
- Material handling systems

They are especially useful where **shaft adjustment or tensioning** is required (e.g., belt conveyors).

Key Features

- **Robust construction** for industrial applications
- Designed for **self-aligning ball bearings or spherical roller bearings**
- **Compact and rigid housing design**
- Good resistance to **shock loads and vibration**
- Compatible with **JIS / ISO standard bearing units**
- Enhanced sealing system to **prevent contaminant ingress**
- Supports **high-speed and continuous operation**
- Available with **different locking mechanisms** (grub screw / eccentric locking)
- Easy installation and maintenance

Detailed Specifications

General Technical Specifications

- **Series:** T 200 / T 300
- **Housing Type:** Take-up / Plummer block housing
- **Material:**
 - Cast Iron (standard)
 - Optional: Ductile iron / cast steel for heavy-duty use
- **Shaft Diameter Range:**
 - Typically **25 mm to 160 mm**
- **Bearing Compatibility:**
 - Self-aligning ball bearings (1200 / 1300 series)
 - Deep groove ball bearings (6200 / 6300 series)
 - Spherical roller bearings (depending on design)
- **Mounting Type:**
 - Base-mounted (often with slotted holes for adjustment)
- **Sealing Options:**
 - Felt seals
 - Labyrinth seals
 - Rubber / lip seals
- **Lubrication:**
 - Grease lubrication (standard)
 - Oil lubrication (optional)
- **Operating Conditions:**
 - Suitable for **dusty, high-temperature, and harsh environments**